




TABLE OF CONTENTS

INDOOR LIGHTING

BIANCA 16W SERIES	09, 13
PENDANT LIGHTS	15, 17
T-BIANCA SERIES	19, 23
S-BR SERIES	25, 47
T-BR SERIES	49, 60
V1-BR SERIES	63, 65
V2-BR SERIES	67, 69
VB1-BIANCA SERIES	71, 73
VB2-BIANCA SERIES	75, 77
VENUS	79
MR 9W BR SERIES	81
ROMA SERIES	83
LED PANELS	85, 88
SKYLIGHT	91, 92
TB RGBW SERIES 10W	97, 99
V1 RGBW SERIES	101, 105
V2 RGBW SERIES	107, 110
C SERIES RGBW	113, 115

**PICTURES USED IN THIS PRODUCT CATALOG ARE FOR REFERENCE ONLY AND SHOULD NOT BE INTERPRETED AS THE RESULT OF ANY ONE PRODUCT OR SPECIFIC MODEL OF LUMINAIRE.*

LED TAPES & TRACKS

LED TAPE RGB	119, 124
LED TAPE RGBW	126, 127
LED TAPE WHITE	128, 131
LED TAPE UHP	132, 133
LED TAPE BI-WHITE	134, 137
GIULIA	139, 141
TRACKS	143, 157
TRIMLESS TRACKS	158, 170

OUTDOOR & LANDSCAPE LIGHTING

FL SERIES	175, 179
LL-LLS SERIES	181, 185
TEGA SERIES	187, 193
TEGA SP SERIES	194, 199
BULLET SERIES	200, 201
TEGA- DR SERIES	203, 205
GAIA	206, 207
MAYA	208, 209

**PICTURES USED IN THIS PRODUCT CATALOG ARE FOR REFERENCE ONLY AND SHOULD NOT BE INTERPRETED AS THE RESULT OF ANY ONE PRODUCT OR SPECIFIC MODEL OF LUMINAIRE.*

LIFESTYLE, WELLNESS AND EXPERIENTIAL LIGHTING SOLUTIONS

Colorbeam Lighting delivers revolutionary low voltage lighting systems that create immersive and controllable lighting experiences for residential, commercial and hospitality spaces.




THE FUTURE OF LIGHTING IS HERE

Colorbeam's revolutionary low voltage lighting technology continuously drives innovation in the lighting industry.

With low voltage lighting solutions and patented **GATEway** Processor, Colorbeam is building new innovations in human-centric lighting, the tunability of light and flicker-free dimming that gives users complete control over lighting their spaces.

Our lighting luminaires and innovative low voltage infrastructure eliminate the need for traditional ROMEX wire, giving users complete control over their lighting solutions. Our end-to-end low voltage lighting solutions include a wide array of luminaires that deliver unmatched features and benefits, with a range of interior and exterior applications for both residential and commercial space.



Indoor L



Lighting



BIANCA 16W Series

The Bianca is a low voltage tunable lighting luminaire. With 95+ CRI driving 1600 lumens of light, the Bianca is used in residential, commercial and hospitality applications with ceilings as high as 20 feet. Available in two chip set options: 1800K to 4000K or 2700K to 6500K.



Dimmable Lighting



Tunable Lighting



BIANCA 16W Series Housing


PRE-CONSTRUCTION PLATE & AIR TIGHT CAN

Designed for direct contact with insulation.
Can be installed in 1/2" to 1 1/2" thick ceilings.
Includes adjustable hanger bars.



Pre-Construction Plate	Bianca-NCMP
Air Tight Can	Bianca-H-16-AT
Ceiling Cut-out	Ø 5.5" / Ø 140mm
Ceiling Thickness	1/2" / 12.7mm to 1 1/2" / 38.1mm



PRE-CONSTRUCTION PLATE DIMENSIONS



ADJUSTABLE BRACKETS





BIANCA-16W-BI-RD / Round Air Tight Trim



DESCRIPTION

Bianca 16W LED Recessed luminaire high lumen, tunable lighting.

TYPICAL APPLICATIONS

- Residential, Commercial & Hospitality applications
- Can be installed in 12ft+ high ceilings



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K

4000K

2700K

6500K



Working
Temperature




5 Year Limited
Warranty

FEATURES


Wattage	16 Watts (two channels)			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	1400 lm	1550 lm	1590 lm	1600 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimension	Ø 5.90" / Ø 150mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

BULB DIMENSIONS



PRODUCT CODES

MODEL	DESCRIPTION
Bianca-16W-BI18-40K-W20-RD-AT	Bianca Series White/Black, Round Trim Kit, 16W, 1800-4000K, 20D, Air tight
Bianca-16W-BI18-40K-W40-RD-AT	Bianca Series White/Black, Round Trim Kit, 16W, 1800-4000K, 40D, Air tight
Bianca-16W-BI27-65K-W20-RD-AT	Bianca Series White/Black, Round Trim Kit, 16W, 2700-6500K, 20D, Air tight
Bianca-16W-BI27-65K-W40-RD-AT	Bianca Series White/Black, Round Trim Kit, 16W, 2700-6500K, 40D, Air tight





BIANCA-16W-BI-SQ / Square Air Tight Trim



DESCRIPTION

Bianca 16W LED Recessed luminaire with high lumens, tunable lighting.

TYPICAL APPLICATIONS

- Residential, Commercial & Hospitality applications
- Can be installed in 12ft+ high ceilings



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



Working
Temperature




5 Year Limited
Warranty

FEATURES

Wattage	16 Watts (two channels)			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	1400 lm	1550 lm	1590 lm	1600 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimensions	5.90" X 5.90" / 149.86mm X 149.86mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

BULB DIMENSIONS



PRODUCT CODES

MODEL	DESCRIPTION
Bianca-16W-BI18-40K-W20-SQ-AT	Bianca Series White/Black, Square Trim Kit, 16W, 1800-4000K, 20D, Air tight
Bianca-16W-BI18-40K-W40-SQ-AT	Bianca Series White/Black, Square Trim Kit, 16W, 1800-4000K, 40D, Air tight
Bianca-16W-BI27-65K-W20-SQ-AT	Bianca Series White/Black, Square Trim Kit, 16W, 2700-6500K, 20D, Air tight
Bianca-16W-BI27-65K-W40-SQ-AT	Bianca Series White/Black, Square Trim Kit, 16W, 2700-6500K, 40D, Air tight



BIANCA 16W / Wall wash



Dimmable Lighting



Tunable Lighting





BIANCA-16W-BI-RDR / Wall wash



DESCRIPTION

Bianca 16W LED Recessed luminaire with an asymmetrical reflector.

TYPICAL APPLICATIONS

- Wall wash
- Art lighting
- Cathedral ceiling installation
- Commercial, Residential & Hospitality Applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K



2700K 6500K



Working
Temperature




5 Year Limited
Warranty

FEATURES

Wattage	16 Watts (two channels)			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	1400 lm	1550 lm	1590 lm	1600 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimension	Ø 5.90" / Ø 150mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

BULB DIMENSIONS



30° ASYMMETRIC REFLECTOR



PRODUCT CODES

MODEL	DESCRIPTION
Bianca-16W-BI18-40K-W20-RDR-AT	Bianca Series White/Black, Round Adjustable, Trim Kit, 16W, 1800-4000K, 20D, Air tight
Bianca-16W-BI18-40K-W40-RDR-AT	Bianca Series White/Black, Round Adjustable, Trim Kit, 16W, 1800-4000K, 40D, Air tight
Bianca-16W-BI27-65K-W20-RDR-AT	Bianca Series White/Black, Round Adjustable, Trim Kit, 16W, 2700-6500K, 20D, Air tight
Bianca-16W-BI27-65K-W40-RDR-AT	Bianca Series White/Black, Round Adjustable, Trim Kit, 16W, 2700-6500K, 40D, Air tight


BIANCA - PENDANT LIGHT



Dimmable Lighting



Tunable Lighting





BIANCA-16W-BI-RD-PDT



FEATURES

Wattage	16 Watts (two channels)			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	1400 lm	1550 lm	1590 lm	1600 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Adjustable Tube	Max height 75.5" / 1917.7mm Min height 39.5" / 1003.3mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

MODEL	DESCRIPTION
BIANCA-16W-BI18-40K-B20-RD-PDT-2M	Bianca Series Black, Pendant Fixture Kit, 16W, 1800-4000K, 20D
BIANCA-16W-BI18-40K-B40-RD-PDT-2M	Bianca Series Black, Pendant Fixture Kit, 16W, 1800-4000K, 40D
BIANCA-16W-BI27-65K-B20-RD-PDT-2M	Bianca Series Black, Pendant Fixture Kit, 16W, 2700-6500K, 20D
BIANCA-16W-BI27-65K-B40-RD-PDT-2M	Bianca Series Black, Pendant Fixture Kit, 16W, 2700-6500K, 40D

DESCRIPTION

Pendant lights that can accent any residential, commercial and hospitality space.

TYPICAL APPLICATIONS

- For residential, commercial and hospitality applications
- Fit for installations in ceilings as high as 12ft.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K



2700K 6500K



Working
Temperature




5 Year Limited
Warranty

ADJUSTABLE TUBE



DUOMO – PENDANT LIGHTS

Modular pendant lights that come in 3 different sizes; and their height can be adjusted as required.





DUOMO-BI27-65K



DESCRIPTION

Round-shaped pendant lights that come in 3 different sizes/diameters; their height can be adjusted as required.

TYPICAL APPLICATIONS

- Fit for installations in ceilings as high as 12ft.
- For residential, commercial and hospitality applications

FINISH OPTIONS



Matte White



Matte Black



Gold

FEATURES

Product Codes	DUOMO-BI27-65K-3FT	DUOMO-BI27-65K-4FT	DUOMO-BI27-65K-5FT
Wattage	26 Watts	41 Watts	62 Watts
Total Lumens	473 lm	843 lm	936 lm
Diameters	Ø 35.43" / Ø 900mm	Ø 47.24" / Ø 1200mm	Ø 59.05" / Ø 1500mm
Lamp Body	H31.75mm*W49.21mm / H1.25"W1.93"		
Color Temperature	2700K - 6500K		
LED CRI	≥95Ra		
LM Rating	LM-80		
Input Voltage	24 DVC		
Materials	Iron + Acrylic		
Compatible Decoder	DRV-SRPC2108-24-200CVF		
IP Grade	IP20 Standard		
Life Span	50,000 Hours		
Warranty	5 Year Limited Warranty		

PRODUCT CODES

MODEL	DESCRIPTION
DUOMO-BI27-65K-3FT	Duomo Series, Pendant Fixture Kit, 26W, 2700-6500K
DUOMO-BI27-65K-4FT	Duomo Series, Pendant Fixture Kit, 41W, 2700-6500K
DUOMO-BI27-65K-5FT	Duomo Series, Pendant Fixture Kit, 62W, 2700-6500K



T-BIANCA Series

Colorbeam's tunable 14W, 95+ CRI, 1100 lumen light engine is used in a wide range of architectural lighting applications. Available in a variety of different trim finishes, the T-BIANCA will enhance any space it is installed in; with ceilings up to 12 ft high. Available in 2 chip set options: 1800K to 4000K and 2700K to 6500K.



Dimmable Lighting



Tunable Lighting



US LISTED

T-BIANCA Series Housing

PRE-CONSTRUCTION PLATE & HOUSING


Designed for direct contact with insulation. Can be installed in 1/2" to 1 1/2" thick ceilings. Includes adjustable hanger bars.

**Pre-Construction plate is an optional accessory.*


Pre-Construction Plate	T-NCMP
Housing	T-H-9-5-5/8-CAN
Ceiling Cut-out	Ø 3.54" / Ø 90mm
Ceiling Thickness	1/2" / 12.7mm to 1 1/2" / 38.1mm



PRE-CONSTRUCTION PLATE | T-NCMP



HOUSING | T-H-9-5-5/8-CAN





T-BIANCA SERIES-14W / Round Trim



FEATURES

Wattage	14 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	900 lm	600 lm	1100 lm	900 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimensions	Ø 4.45" x 1.20" / Ø 113mm x 30.5mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			



DESCRIPTION

This matte trim is sleek and stylish with a small aperture; available in both white and black.

TYPICAL APPLICATIONS

- Residential, Commercial & Hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting




Working
Temperature



5 Year Limited
Warranty

TRIM DIMENSIONS



PRODUCT CODES

MATTE WHITE	MATTE BLACK
TB-150-11-14W-BI18-40K-20	TB-150-22-14W-BI18-40K-20
TB-150-11-14W-BI18-40K-40	TB-150-22-14W-BI18-40K-40
TB-150-11-14W-BI27-65K-20	TB-150-22-14W-BI27-65K-20
TB-150-11-14W-BI27-65K-40	TB-150-22-14W-BI27-65K-40



T-BIANCA SERIES-14W / Square Trim



FEATURES

Wattage	14 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	900 lm	600 lm	1100 lm	900 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimensions	4.27" x 4.27" / 108.5mm x 108.5mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			



DESCRIPTION

This matte trim is sleek and stylish with a small aperture; available in both white and black.

TYPICAL APPLICATIONS

- Residential, Commercial & Hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K



2700K 6500K




Working
Temperature



5 Year Limited
Warranty

TRIM DIMENSIONS



PRODUCT CODES

MATTE WHITE	MATTE BLACK
TB-650-11-14W-B118-40K-20	TB-650-22-14W-B118-40K-20
TB-650-11-14W-B118-40K-40	TB-650-22-14W-B118-40K-40
TB-650-11-14W-B127-65K-20	TB-650-22-14W-B127-65K-20
TB-650-11-14W-B127-65K-40	TB-650-22-14W-B127-65K-40

T-BIANCA SERIES – Shower Trims





INDOOR LIGHTING

T-BIANCA SERIES-14W / Shower Trims



FEATURES

Wattage	14 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	900 lm	600 lm	1100 lm	900 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimensions	Ø 4.45" / 4.27" x 4.27"			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			



DESCRIPTION

Sleek, stylish, small aperture

TYPICAL APPLICATIONS

- Use in showers and bathrooms.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting

CRI 95⁺




Working
Temperature



5 Year Limited
Warranty

TRIM DIMENSIONS



PRODUCT CODES

ROUND TRIM	SQUARE TRIM
TB-100-11MG-14W-BI27-65K-W40	TB-700-11MG-14W-BI27-65K-W40
TB-100-11MG-14W-BI18-40K-W40	TB-700-11MG-14W-BI18-40K-W40

S-BR SERIES – Round Trim



Dimmable Lighting



Tunable Lighting




S-BR Series Housing

HOUSING | S-HOUSING_S-9W-HSG-RD




Housing - Round Trim	S-HOUSING_S-9W-HSG-RD
Mounting	Pre-installed mounting brackets allow vertical adjustment of bar hangers up to 1"
Adjustable Brackets	Maximum Length: 25.00" / 635mm Minimum Length: 10.00" / 254mm
Ceiling Cut-out	Ø 3.25" / Ø 83mm
Ceiling Thickness	1/2" / 12.7mm to 1 1/2" / 38.1mm



HOUSING FOR ROUND TRIM



HOUSING FOR ROUND TRIMLESS





S-200-11-11-9W-BR /Adjustable Trim



DESCRIPTION

This matte white trim with a white reflector is sleek and stylish with a small aperture.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K

2700K 6500K



Working
Temperature



5 Year Limited
Warranty


FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimension	Ø 3.346" / Ø 85mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

MODEL	DESCRIPTION
S-200-11-11-9W-BR18-40K-40	S Series, Matte, White, Round Trim Kit, White Reflector, Adjustable, 9W, Rocket 1800-4000K, 40D
S-200-11-11-9W-BR18-40K-20	S Series, Matte, White, Round Trim Kit, White Reflector, Adjustable, 9W, Rocket 1800-4000K, 20D
S-200-11-11-9W-BR27-65K-40	S Series, Matte, White, Round Trim Kit, White Reflector, Adjustable, 9W, Rocket 2700-6500K, 40D
S-200-11-11-9W-BR27-65K-20	S Series, Matte, White, Round Trim Kit, White Reflector, Adjustable, 9W, Rocket 2700-6500K, 20D

TRIM DIMENSIONS





S-300-11-11-9W-BR / Fixed Trim



FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimension	Ø 3.385" / Ø 86mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

MODEL	DESCRIPTION
S-300-11-11-9W-BR18-40K-40	S Series, Matte, White, Fixed Round Trim Kit, White Reflector, 9W, 1800-4000K, 40D
S-300-11-11-9W-BR18-40K-20	S Series, Matte, White, Fixed Round Trim Kit, White Reflector, 9W, 1800-4000K, 20D
S-300-11-11-9W-BR27-65K-40	S Series, Matte, White, Fixed Round Trim Kit, White Reflector, 9W, 2700-6500K, 40D
S-300-11-11-9W-BR27-65K-20	S Series, Matte, White, Fixed Round Trim Kit, White Reflector, 9W, 2700-6500K, 20D

DESCRIPTION

This matte white trim with a white reflector is sleek and stylish with a small aperture.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K



2700K 6500K





Working
Temperature



5 Year Limited
Warranty

TRIM DIMENSIONS





S-300-11-05-9W-BR / Fixed Trim



DESCRIPTION

This matte white trim with a chrome reflector is sleek and stylish with a small aperture.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K



2700K 6500K



Working
Temperature




5 Year Limited
Warranty

FEATURES


Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimension	Ø 3.385" / Ø 86mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

TRIM DIMENSIONS



PRODUCT CODES

MODEL	DESCRIPTION
S-300-11-05-9W-BR18-40K-40	S Series, Matte, White, Fixed Round Trim Kit, Chrome Reflector, 9W, 1800-4000K, 40D
S-300-11-05-9W-BR18-40K-20	S Series, Matte, White, Fixed Round Trim Kit, Chrome Reflector, 9W, 1800-4000K, 20D
S-300-11-05-9W-BR27-65K-40	S Series, Matte, White, Fixed Round Trim Kit, Chrome Reflector, 9W, 2700-6500K, 40D
S-300-11-05-9W-BR27-65K-20	S Series, Matte, White, Fixed Round Trim Kit, Chrome Reflector, 9W, 2700-6500K, 20D





S-340-11-11-9W-BR / Adjustable Trim



DESCRIPTION

This matte white trim with a white reflector is sleek and stylish with a small aperture.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K

2700K 6500K



Working
Temperature



5 Year Limited
Warranty


FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimension	Ø 3.385" / Ø 86mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

MODEL	DESCRIPTION
S-340-11-11-9W-BR18-40K-40	S Series, Matte, White, Adjustable Round Trim Kit, White Slanted Reflector, 9W, 1800-4000K, 40D
S-340-11-11-9W-BR18-40K-20	S Series, Matte, White, Adjustable Round Trim Kit, White Slanted Reflector, 9W, 1800-4000K, 20D
S-340-11-11-9W-BR27-65K-40	S Series, Matte, White, Adjustable Round Trim Kit, White Slanted Reflector, 9W, 2700-6500K, 40D
S-340-11-11-9W-BR27-65K-20	S Series, Matte, White, Adjustable Round Trim Kit, White Slanted Reflector, 9W, 2700-6500K, 20D

TRIM DIMENSIONS





S-340-11-05-9W-BR / Adjustable Trim



DESCRIPTION

This matte white trim with a slanted reflector is sleek and stylish with a small aperture.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K

2700K 6500K



Working
Temperature



5 Year Limited
Warranty


FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimension	Ø 3.385" / Ø 86mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

MODEL	DESCRIPTION
S-340-11-05-9W-BR18-40K-40	S Series, Matte, White, Adjustable Round Trim Kit, Slanted Reflector, 9W, 1800-4000K, 40D
S-340-11-05-9W-BR18-40K-20	S Series, Matte, White, Adjustable Round Trim Kit, Slanted Reflector, 9W, 1800-4000K, 20D
S-340-11-05-9W-BR27-65K-40	S Series, Matte, White, Adjustable Round Trim Kit, Slanted Reflector, 9W, 2700-6500K, 40D
S-340-11-05-9W-BR27-65K-20	S Series, Matte, White, Adjustable Round Trim Kit, Slanted Reflector, 9W, 2700-6500K, 20D

TRIM DIMENSIONS





S-350-11-11-9W-BR / Adjustable Trim



DESCRIPTION

This matte white trim with a flat round surface is sleek and stylish with a small aperture.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K

2700K 6500K



Working
Temperature



5 Year Limited
Warranty


FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimension	Ø 3.385" / Ø 86mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

MODEL	DESCRIPTION
S-350-11-11-9W-BR18-40K-40	S Series, Matte, White, Adjustable Round Trim Kit, Flat Round Surface, 9W, 1800-4000K, 40D
S-350-11-11-9W-BR18-40K-20	S Series, Matte, White, Adjustable Round Trim Kit, Flat Round Surface, 9W, 1800-4000K, 20D
S-350-11-11-9W-BR27-65K-40	S Series, Matte, White, Adjustable Round Trim Kit, Flat Round Surface, 9W, 2700-6500K, 40D
S-350-11-11-9W-BR27-65K-20	S Series, Matte, White, Adjustable Round Trim Kit, Flat Round Surface, 9W, 2700-6500K, 20D

TRIM DIMENSIONS





S-360-11-11-9W-BR / Adjustable Trim



DESCRIPTION

This matte white trim with an oval surface is sleek and stylish with a small aperture.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K



2700K 6500K



Working
Temperature



5 Year Limited
Warranty



FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimension	Ø 3.385" / Ø 86mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

MODEL	DESCRIPTION
S-360-11-11-9W-BR18-40K-40	S Series, Matte, White, Adjustable Round Trim Kit Flat Oval Surface, 9W, 1800-4000K, 40D
S-360-11-11-9W-BR18-40K-20	S Series, Matte, White, Adjustable Round Trim Kit Flat Oval Surface, 9W, 1800-4000K, 20D
S-360-11-11-9W-BR27-65K-40	S Series, Matte, White, Adjustable Round Trim Kit Flat Oval Surface, 9W, 2700-6500K, 40D
S-360-11-11-9W-BR27-65K-20	S Series, Matte, White, Adjustable Round Trim Kit Flat Oval Surface, 9W, 2700-6500K, 20D

TRIM DIMENSIONS





S-300-11-11-TL-9W-BR / Fixed Trimless



DESCRIPTION

Sleek, stylish and trimless with a small aperture.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K

2700K 6500K



Working
Temperature



5 Year Limited
Warranty


FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trimless Dimensions	4.72" x 4.72" / 120mm x 120mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

MODEL	DESCRIPTION
S-300-11-11-TL-9W-BR18-40K-40	S Series, Matte, White, Fixed Round Trimless Kit, Chrome Reflector, 9W, 1800-4000K, 40D
S-300-11-11-TL-9W-BR18-40K-20	S Series, Matte, White, Fixed Round Trimless Kit, Chrome Reflector, 9W, 1800-4000K, 20D
S-300-11-11-TL-9W-BR27-65K-40	S Series, Matte, White, Fixed Round Trimless Kit, Chrome Reflector, 9W, 2700-6500K, 40D
S-300-11-11-TL-9W-BR27-65K-20	S Series, Matte, White, Fixed Round Trimless Kit, Chrome Reflector, 9W, 2700-6500K, 20D

TRIMLESS DIMENSIONS





S-300-11-05-TL-9W-BR / Fixed Trimless



DESCRIPTION

Sleek, stylish and trimless with a small aperture.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K

2700K 6500K



Working
Temperature



5 Year Limited
Warranty


FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trimless Dimensions	4.72" x 4.72" / 120mm x 120mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

MODEL	DESCRIPTION
S-300-11-05-TL-9W-BR18-40K-40	S Series, Matte, White, Fixed Round Trimless Kit, Chrome Reflector, 9W, 1800-4000K, 40D
S-300-11-05-TL-9W-BR18-40K-20	S Series, Matte, White, Fixed Round Trimless Kit, Chrome Reflector, 9W, 1800-4000K, 20D
S-300-11-05-TL-9W-BR27-65K-40	S Series, Matte, White, Fixed Round Trimless Kit, Chrome Reflector, 9W, 2700-6500K, 40D
S-300-11-05-TL-9W-BR27-65K-20	S Series, Matte, White, Fixed Round Trimless Kit, Chrome Reflector, 9W, 2700-6500K, 20D

TRIMLESS DIMENSIONS





S-350-11-11-TL-9W-BR / Adjustable Trimless



DESCRIPTION

Sleek, stylish and trimless with a small aperture.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K

2700K 6500K



Working
Temperature



5 Year Limited
Warranty


FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trimless Dimensions	4.72" x 4.72" / 120mm x 120mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

MODEL	DESCRIPTION
S-350-11-11-TL-9W-BR18-40K-40	S Series, Matte, White, Adjustable Round Trimless Kit, Flat Round Surface, 9W, 1800-4000K, 40D
S-350-11-11-TL-9W-BR18-40K-20	S Series, Matte, White, Adjustable Round Trimless Kit, Flat Round Surface, 9W, 1800-4000K, 20D
S-350-11-11-TL-9W-BR27-65K-40	S Series, Matte, White, Adjustable Round Trimless Kit, Flat Round Surface, 9W, 2700-6500K, 40D
S-350-11-11-TL-9W-BR27-65K-20	S Series, Matte, White, Adjustable Round Trimless Kit, Flat Round Surface, 9W, 2700-6500K, 20D

TRIMLESS DIMENSIONS





S-360-11-11-TL-9W-BR / Adjustable Trimless



DESCRIPTION

Sleek, stylish and trimless with a small aperture.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K

2700K 6500K



Working
Temperature



5 Year Limited
Warranty



FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trimless Dimensions	4.72" x 4.72" / 120mm x 120mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

MODEL	DESCRIPTION
S-360-11-11-TL-9W-BR18-40K-40	S Series, Matte, White, Adjustable Round Trimless Kit Flat Oval Surface, 9W, 1800-4000K, 40D
S-360-11-11-TL-9W-BR18-40K-20	S Series, Matte, White, Adjustable Round Trimless Kit Flat Oval Surface, 9W, 1800-4000K, 20D
S-360-11-11-TL-9W-BR27-65K-40	S Series, Matte, White, Adjustable Round Trimless Kit Flat Oval Surface, 9W, 2700-6500K, 40D
S-360-11-11-TL-9W-BR27-65K-20	S Series, Matte, White, Adjustable Round Trimless Kit Flat Oval Surface, 9W, 2700-6500K, 20D

TRIMLESS DIMENSIONS





S-BR SERIES – Square Trim



Dimmable Lighting



Tunable Lighting





S-BR Series Housing

HOUSING | S-HOUSING_S-9W-HSG-SQ



Housing - Square Trim	S-HOUSING_S-9W-HSG-SQ
Mounting	Pre-installed mounting brackets allow vertical adjustment of bar hangers up to 1"
Adjustable Brackets	Maximum Lenght: 25.00" / 635mm Minimum Lenght: 10.00" / 254mm
Ceiling Cut-out	3.21x3.21" / 81.7x81.7mm
Ceiling Thickness	1/2" / 12.7mm to 1 1/2" / 38.1mm



HOUSING FOR SQUARE TRIM



HOUSING FOR SQUARE TRIMLESS





S-500-11-05-9W-BR / Fixed Trim



DESCRIPTION

This matte white trim with a chrome reflector is sleek and stylish with a small aperture.

TYPICAL APPLICATIONS

For use in commercial, retail and other architectural applications.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K

2700K 6500K



Working
Temperature



5 Year Limited
Warranty



FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimensions	3.34" x 3.34" / 85mm x 85mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

MODEL	DESCRIPTION
S-500-11-05-9W-BR18-40K-40	S Series, Matte, White, Fixed Square Trim Kit, 9W, Chrome Reflector, 1800-4000K, 40D
S-500-11-05-9W-BR18-40K-20	S Series, Matte, White, Fixed Square Trim Kit, 9W, Chrome Reflector, 1800-4000K, 20D
S-500-11-05-9W-BR27-65K-40	S Series, Matte, White, Fixed Square Trim Kit, 9W, Chrome Reflector, 2700-6500K, 40D
S-500-11-05-9W-BR27-65K-20	S Series, Matte, White, Fixed Square Trim Kit, 9W, Chrome Reflector, 2700-6500K, 20D

TRIM DIMENSIONS





S-500-11-11-9W-BR / Fixed Trim



DESCRIPTION

This matte white trim with a white reflector is sleek and stylish with a small aperture.

TYPICAL APPLICATIONS

For use in commercial, retail and other architectural applications.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K

2700K 6500K



Working
Temperature



5 Year Limited
Warranty



FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimensions	3.34" x 3.34" / 85mm x 85mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES


MODEL	DESCRIPTION
S-500-11-11-9W-BR18-40K-40	S Series, Matte, White, Square Trim Kit, White Reflector, 9W, Rocket 1800-4000K, 40D
S-500-11-11-9W-BR18-40K-20	S Series, Matte, White, Square Trim Kit, White Reflector, 9W, Rocket 1800-4000K, 20D
S-500-11-11-9W-BR27-65K-40	S Series, Matte, White, Square Trim Kit, White Reflector, 9W, Rocket 2700-6500K, 40D
S-500-11-11-9W-BR27-65K-20	S Series, Matte, White, Square Trim Kit, White Reflector, 9W, Rocket 2700-6500K, 20D

TRIM DIMENSIONS





S-500-11-05-TL-9W-BR / Fixed Trim



DESCRIPTION

Sleek, stylish, trimless and small aperture.

TYPICAL APPLICATIONS

For use in commercial, retail and other architectural applications.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K

2700K 6500K



Working
Temperature



5 Year Limited
Warranty


FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trimless Dimensions	4.72" x 4.72" / 120mm x 120mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES


MODEL	DESCRIPTION
S-500-11-05-TL-9W-BR18-40K-40	S Series, Matte, White, Fixed Square Trimless Kit, 9W, Chrome Reflector, 1800-4000K, 40D
S-500-11-05-TL-9W-BR18-40K-20	S Series, Matte, White, Fixed Square Trimless Kit, 9W, Chrome Reflector, 1800-4000K, 20D
S-500-11-05-TL-9W-BR27-65K-40	S Series, Matte, White, Fixed Square Trimless Kit, 9W, Chrome Reflector, 2700-6500K, 40D
S-500-11-05-TL-9W-BR27-65K-20	S Series, Matte, White, Fixed Square Trimless Kit, 9W, Chrome Reflector, 2700-6500K, 20D

TRIMLESS DIMENSIONS





S-500-11-11-TL-9W-BR / Fixed Trimless



FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trimless Dimensions	4.72" x 4.72" / 120mm x 120mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

MODEL	DESCRIPTION
S-500-11-11-TL-9W-BR18-40K-40	S Series, Matte, White, Fixed Square Trimless Kit, 9W, White Reflector, 1800-4000K, 40D
S-500-11-11-TL-9W-BR18-40K-20	S Series, Matte, White, Fixed Square Trimless Kit, 9W, White Reflector, 1800-4000K, 20D
S-500-11-11-TL-9W-BR27-65K-40	S Series, Matte, White, Fixed Square Trimless Kit, 9W, White Reflector, 2700-6500K, 40D
S-500-11-11-TL-9W-BR27-65K-20	S Series, Matte, White, Fixed Square Trimless Kit, 9W, White Reflector, 2700-6500K, 20D

DESCRIPTION

Sleek, stylish, trimless and small aperture.

TYPICAL APPLICATIONS

For use in commercial, retail and other architectural applications.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K

2700K 6500K





Working
Temperature



5 Year Limited
Warranty

TRIMLESS DIMENSIONS





S-540-11-05-9W-BR / Adjustable Trim



DESCRIPTION

This matte white trim with a chrome reflector is small, sleek and stylish.

TYPICAL APPLICATIONS

For use in commercial, retail and other architectural applications.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K

2700K 6500K



Working
Temperature



5 Year Limited
Warranty


FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimensions	3.34" x 3.34" / 85mm x 85mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

MODEL	DESCRIPTION
S-540-11-05-9W-BR18-40K-40	S Series, Matte, White, Adjustable Square Trim Kit, 9W, Chrome Reflector, 1800-4000K, 40D
S-540-11-05-9W-BR18-40K-20	S Series, Matte, White, Adjustable Square Trim Kit, 9W, Chrome Reflector, 1800-4000K, 20D
S-540-11-05-9W-BR27-65K-40	S Series, Matte, White, Adjustable Square Trim Kit, 9W, Chrome Reflector, 2700-6500K, 40D
S-540-11-05-9W-BR27-65K-20	S Series, Matte, White, Adjustable Square Trim Kit, 9W, Chrome Reflector, 2700-6500K, 20D

TRIM DIMENSIONS





S-540-11-11-9W-BR / Adjustable Trim



DESCRIPTION

This matte white trim with a white reflector is small, sleek and stylish.

TYPICAL APPLICATIONS

For use in commercial, retail and other architectural applications.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K

2700K 6500K



Working
Temperature




5 Year Limited
Warranty

FEATURES


Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimensions	3.34" x 3.34" / 85mm x 85mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

TRIM DIMENSIONS




PRODUCT CODES

MODEL	DESCRIPTION
S-540-11-11-9W-BR18-40K-40	S Series, Matte, White, Square Trim Kit, White Reflector, 9W, Rocket 1800-4000K, 40D
S-540-11-11-9W-BR18-40K-20	S Series, Matte, White, Square Trim Kit, White Reflector, 9W, Rocket 1800-4000K, 20D
S-540-11-11-9W-BR27-65K-40	S Series, Matte, White, Square Trim Kit, White Reflector, 9W, Rocket 2700-6500K, 40D
S-540-11-11-9W-BR27-65K-20	S Series, Matte, White, Square Trim Kit, White Reflector, 9W, Rocket 2700-6500K, 20D





S-540-11-05-TL-9W-BR / Adjustable Trim



DESCRIPTION

Sleek, stylish, trimless and small aperture.

TYPICAL APPLICATIONS

For use in commercial, retail and other architectural applications.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting

1800K

4000K

2700K

6500K



Working
Temperature



5 Year Limited
Warranty


FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trimless Dimensions	4.72" x 4.72" / 120mm x 120mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

MODEL	DESCRIPTION
S-540-11-05-TL-9W-BR18-40K-40	S Series, Matte, White, Adjustable Square Trimless Kit, 9W, Chrome Reflector, 1800-4000K, 40D
S-540-11-05-TL-9W-BR18-40K-20	S Series, Matte, White, Adjustable Square Trimless Kit, 9W, Chrome Reflector, 1800-4000K, 20D
S-540-11-05-TL-9W-BR27-65K-40	S Series, Matte, White, Adjustable Square Trimless Kit, 9W, Chrome Reflector, 2700-6500K, 40D
S-540-11-05-TL-9W-BR27-65K-20	S Series, Matte, White, Adjustable Square Trimless Kit, 9W, Chrome Reflector, 2700-6500K, 20D

TRIMLESS DIMENSIONS





S-540-11-11-TL-9W-BR / Adjustable Trimless



DESCRIPTION

Sleek, stylish, trimless and small aperture.

TYPICAL APPLICATIONS

For use in commercial, retail and other architectural applications.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting

1800K

4000K

2700K

6500K



Working
Temperature



5 Year Limited
Warranty


FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trimless Dimensions	4.72" x 4.72" / 120mm x 120mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

MODEL	DESCRIPTION
S-540-11-11-TL-9W-BR18-40K-40	S Series, Matte, White, Adjustable Square Trimless Kit, 9W, White Reflector, 1800-4000K, 40D
S-540-11-11-TL-9W-BR18-40K-20	S Series, Matte, White, Adjustable Square Trimless Kit, 9W, White Reflector, 1800-4000K, 20D
S-540-11-11-TL-9W-BR27-65K-40	S Series, Matte, White, Adjustable Square Trimless Kit, 9W, White Reflector, 2700-6500K, 40D
S-540-11-11-TL-9W-BR27-65K-20	S Series, Matte, White, Adjustable Square Trimless Kit, 9W, White Reflector, 2700-6500K, 20D

TRIMLESS DIMENSIONS



T-BR Series

The T-Series - BR is a 9 Watt shower luminaire that delivers tunable white light.



Dimmable Lighting



Tunable Lighting



T-BR SERIES 9W Housing

PRE-CONSTRUCTION PLATE & HOUSING


Designed for direct contact with insulation. Can be installed in 1/2" to 1 1/2" thick ceilings. Includes adjustable hanger bars.

**Pre-construction plate is an optional accessory.*


Pre-Construction Plate	T-NCMP
Housing	T-H-9-5-5/8-CAN
Ceiling Cut-out	Ø 3.54" / Ø 90mm
Ceiling Thickness	1/2" / 12.7mm to 1 1/2" / 38.1mm



PRE-CONSTRUCTION PLATE | T-NCMP



HOUSING | T-H-9-5-5/8-CAN





T-100-9W-BR / Shower Trim



FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimension	Ø4.45" / Ø113mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			



DESCRIPTION

An IP65 rated shower luminaire that offers tunable white light.

TYPICAL APPLICATIONS

For use in bathroom and other architectural applications.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting




Working
Temperature



5 Year Limited
Warranty

TRIM DIMENSIONS



PRODUCT CODES

MODEL	COLOR
T-100-11MG-9W-BR27-65K-W40	☐
T-100-11MG-9W-BR18-40K-W40	☐



T-150-9W-BR / Recessed Adjustable



TRIM FINISH OPTIONS



White (01)



Matte White (11)



Matte Black (22)

FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimension	Ø4.45" / Ø113mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			



DESCRIPTION

A 9W BR fixture that offers tunable white light.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting

1800K 4000K



2700K 6500K




Working
Temperature



5 Year Limited
Warranty

TRIM DIMENSIONS



PRODUCT CODES

20D	40D	COLOR
T-150-01-9W-BR27-65K-W20	T-150-01-9W-BR27-65K-W40	☐
T-150-01-9W-BR18-40K-W20	T-150-01-9W-BR18-40K-W40	☐
T-150-11-9W-BR27-65K-W20	T-150-11-9W-BR27-65K-W40	☐
T-150-11-9W-BR18-40K-W20	T-150-11-9W-BR18-40K-W40	☐
T-150-22-9W-BR27-65K-B20	T-150-22-9W-BR27-65K-B40	☒
T-150-22-9W-BR18-40K-B20	T-150-22-9W-BR18-40K-B40	☒



T-200-9W-BR / Recessed Adjustable



TRIM FINISH OPTIONS



White (11)



Black (22)

REFLECTOR OPTIONS

Matte White
(11)Black
(02)

Aluminium

FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimension	Ø4.45" / Ø113mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			



52 WWW.COLORBEAMLIGHTING.COM

DESCRIPTION

A 9W BR luminaire that offers tunable white light.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting

1800K 4000K



2700K 6500K




Working
Temperature



5 Year Limited
Warranty

TRIM DIMENSIONS



PRODUCT CODES

20D	40D	COLOR
T-200-11-9W-BR18-40K-W20	T-200-11-9W-BR18-40K-W40	
T-200-11-11-9W-BR18-40K-W20	T-200-11-11-9W-BR18-40K-W40	
T-200-11-02-9W-BR18-40K-B20	T-200-11-02-9W-BR18-40K-B40	
T-200-22-9W-BR18-40K-B20	T-200-22-9W-BR18-40K-B40	
T-200-22-02-9W-BR18-40K-B20	T-200-22-02-9W-BR18-40K-B40	

*Bulbs also available in 2700K-6500K



T-250-9W-BR / Recessed Adjustable



TRIM FINISH OPTIONS



White (01)



Matte White (11)



Matte Black (22)

FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimension	Ø4.45" / Ø113mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			



DESCRIPTION

A 9W BR luminaire that offers tunable white light.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting

1800K 4000K



2700K 6500K




Working
Temperature



5 Year Limited
Warranty

TRIM DIMENSIONS



PRODUCT CODES

20D	40D	COLOR
T-250-01-9W-BR27-65K-W20	T-250-01-9W-BR27-65K-W40	
T-250-01-9W-BR18-40K-W20	T-250-01-9W-BR18-40K-W40	
T-250-02-9W-BR27-65K-B20	T-250-02-9W-BR27-65K-B40	
T-250-02-9W-BR18-40K-B20	T-250-02-9W-BR18-40K-B40	



T-300-9W-BR / Recessed Fixed



TRIM FINISH OPTIONS




Matte White (11)




Matte Black (22)

REFLECTOR OPTIONS



FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimension	Ø4.45" / Ø113mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			



54 WWW.COLORBEAMLIGHTING.COM

DESCRIPTION

A 9W BR luminaire that offers tunable white light.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting




Working
Temperature



5 Year Limited
Warranty

TRIM DIMENSIONS



PRODUCT CODES

20D	40D	COLOR
T-300-11-9W-BR18-40K-W20	T-300-11-9W-BR18-40K-W40	
T-300-11-11-9W-BR18-40K-W20	T-300-11-11-9W-BR18-40K-W40	
T-300-11-02-9W-BR18-40K-B20	T-300-11-02-9W-BR18-40K-B40	
T-300-22-9W-BR18-40K-B20	T-300-22-9W-BR18-40K-B40	
T-300-22-02-9W-BR18-40K-B20	T-300-22-02-9W-BR18-40K-B40	

*Bulbs also available in 2700K-6500K



T-400-9W-BR / Recessed Fixed



TRIM FINISH OPTIONS



Matte White (11)



Matte Black (22)

FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimension	4.25" x 4.25" / 108mm x 108mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			



DESCRIPTION

A 9W BR luminaire that offers tunable white light.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting

1800K 4000K



2700K 6500K




Working
Temperature



5 Year Limited
Warranty

TRIM DIMENSIONS



PRODUCT CODES

20D	40D	COLOR
T-400-11-9W-BR18-40K-W20	T-400-11-9W-BR18-40K-W40	
T-400-11-11-9W-BR18-40K-W20	T-400-11-11-9W-BR18-40K-W40	
T-400-11-02-9W-BR18-40K-B20	T-400-11-02-9W-BR18-40K-B40	
T-400-22-9W-BR18-40K-B20	T-400-22-9W-BR18-40K-B40	
T-400-22-02-9W-BR18-40K-B20	T-400-22-02-9W-BR18-40K-B40	

*Bulbs also available in 2700K-6500K



T-500-9W-BR / Recessed Fixed



TRIM FINISH OPTIONS




Matte White (11)



Matte Black (22)

REFLECTOR OPTIONS



FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimensions	4.25" x 4.25" / 108mm x 108mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

DESCRIPTION

A 9W BR luminaire that offers tunable white light.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting





Working
Temperature



5 Year Limited
Warranty

TRIM DIMENSIONS



PRODUCT CODES

20D	40D	COLOR
T-500-11-9W-BR18-40K-W20	T-500-11-9W-BR18-40K-W40	
T-500-11-11-9W-BR18-40K-W20	T-500-11-11-9W-BR18-40K-W40	
T-500-11-02-9W-BR18-40K-B20	T-500-11-02-9W-BR18-40K-B40	
T-500-22-9W-BR18-40K-B20	T-500-22-9W-BR18-40K-B40	
T-500-22-02-9W-BR18-40K-B20	T-500-22-02-9W-BR18-40K-B40	

*Bulbs also available in 2700K-6500K



T-550-9W-BR / Recessed Adjustable



TRIM FINISH OPTIONS




White (01)



Black (22)

FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimension	Ø4.45" / Ø113mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			



DESCRIPTION

A 9W BR luminaire that offers tunable white light.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting

1800K 4000K



2700K 6500K




Working
Temperature



5 Year Limited
Warranty

TRIM DIMENSIONS



PRODUCT CODES

20D	40D	COLOR
T-550-11-9W-BR27-65K-W20	T-550-11-9W-BR27-65K-W40	
T-550-11-9W-BR18-40K-W20	T-550-11-9W-BR18-40K-W40	
T-550-22-9W-BR27-65K-W20	T-550-22-9W-BR27-65K-W40	
T-550-22-9W-BR18-40K-W20	T-550-22-9W-BR18-40K-W40	



T-600-9W-BR / Recessed Adjustable



TRIM FINISH OPTIONS




Matte White (11)



Matte Black (22)

FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimensions	4.25" x 4.25" / 108mm x 108mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			



58 WWW.COLORBEAMLIGHTING.COM

DESCRIPTION

A 9W BR luminaire that offers tunable white light.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting




Working
Temperature



5 Year Limited
Warranty

TRIM DIMENSIONS



PRODUCT CODES

20D	40D	COLOR
T-600-11-9W-BR18-40K-W20	T-600-11-9W-BR18-40K-W40	
T-600-11-11-9W-BR18-40K-W20	T-600-11-11-9W-BR18-40K-W40	
T-600-11-02-9W-BR18-40K-B20	T-600-11-02-9W-BR18-40K-B40	
T-600-22-9W-BR18-40K-B20	T-600-22-9W-BR18-40K-B40	
T-600-22-02-9W-BR18-40K-B20	T-600-22-02-9W-BR18-40K-B40	

*Bulbs also available in 2700K-6500K



T-650-9W-BR / Recessed Adjustable



TRIM FINISH OPTIONS



Matte White (11)



Matte Black (22)

FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimensions	4.27" x 4.27" / 108.5mm x 108.5mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			



DESCRIPTION

A 9W BR luminaire that offers tunable white light.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting




Working
Temperature



5 Year Limited
Warranty

TRIM DIMENSIONS



PRODUCT CODES

20D	40D	COLOR
T-650-01-9W-BR18-40K-W20	T-650-01-9W-BR18-40K-W40	
T-650-01-9W-BR27-65K-W20	T-650-01-9W-BR27-65K-W40	
T-650-11-9W-BR18-40K-W20	T-650-11-9W-BR18-40K-W40	
T-650-11-9W-BR27-65K-W20	T-650-11-9W-BR27-65K-W40	
T-650-22-9W-BR18-40K-B20	T-650-22-9W-BR18-40K-B40	
T-650-22-02-9W-BR18-40K-B20	T-650-22-02-9W-BR18-40K-B40	




T-700-9W-BR / Shower Trim



FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimension	4.25" x 4.25" / 108mm x 108mm			
Certifications	cULus E476753, JA8 Title 24 (27000K-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP65 Standard			
Life Span	50,000 Hours			



DESCRIPTION

An IP65 rated shower luminaire that offers tunable white light.

TYPICAL APPLICATIONS

For use in bathroom and other architectural applications.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting




Working
Temperature



5 Year Limited
Warranty

TRIM DIMENSIONS



PRODUCT CODES

MODEL	COLOR
T-700-11MG-9W-BR27-65K-W40	☐
T-700-11MG-9W-BR18-40K-W40	☐



V1-BR Series

These sleek and stylish luminaires include the 9W tunable, 95+ CRI, 660 lumen light engine. The V1-BR series delivers performance and beautiful aesthetics. Available in both open and closed faceplate options.



Dimmable Lighting



Tunable Lighting



V1-BR Series Housing

HOUSING V1-9W-HSG


Hanger bars can be adjusted from 8.35" to 23.25", to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for easy installation.

**The die-cast aluminum heat sink is painted black.*

Housing	V1-9W-HSG
Ceiling Cut-out	4.5" x 4.5" / 114.3mm x 114.3mm
Ceiling Thickness	1/2" / 12.7mm to 1 1/2" / 38.1mm



HOUSING DIMENSIONS





VI-BR SERIES KIT 9W / Open & Closed Trim



COMPLETE KIT INCLUDES

Housing

One Bulb

Open or Closed Trim



FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimensions	5.02" x 5.02" / 127.6mm x 127.6mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

OPEN TRIM	CLOSED TRIM
VI-9W-11-BR18-40K-20-OP	VI-9W-11-BR18-40K-20-CL
VI-9W-11-BR18-40K-40-OP	VI-9W-11-BR18-40K-40-CL
VI-9W-11-BR27-65K-20-OP	VI-9W-11-BR27-65K-20-CL
VI-9W-11-BR27-65K-40-OP	VI-9W-11-BR27-65K-40-CL

DESCRIPTION

Luminaires available in a wide variety of options, the VBI luminaire adds sophistication to any space.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting

CRI 95⁺

1800K 4000K



2700K 6500K




Working
Temperature




5 Year Limited
Warranty

INDOOR APPLICATION




TRIM DIMENSIONS

CLOSED TRIM



OPEN TRIM





VI-BR SERIES KIT 9W / Open & Closed Trimless



COMPLETE KIT INCLUDES

Housing

One Bulb

Open or Closed Trimless



FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimensions	5.02" x 5.02" / 127.6mm x 127.6mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

OPEN TRIMLESS	CLOSED TRIMLESS
V1-9W-11-BR18-40K-20-TL-OP	V1-9W-11-BR18-40K-20-TL-CL
V1-9W-11-BR18-40K-40-TL-OP	V1-9W-11-BR18-40K-40-TL-CL
V1-9W-11-BR27-65K-20-TL-OP	V1-9W-11-BR27-65K-20-TL-CL
V1-9W-11-BR27-65K-40-TL-OP	V1-9W-11-BR27-65K-40-TL-CL

DESCRIPTION

Luminaires available in a wide variety of options, the VBI luminaire adds sophistication to any space.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications.



Dimmable Lighting

0 to 100% flicker free dimming



Tunable Lighting



1800K

4000K

2700K


6500K

Working
Temperature5 Year Limited
Warranty

COMMERCIAL APPLICATION



TRIMLESS DIMENSIONS



V2-BR Series

These twin 9W tunable luminaires deliver 1320 lumens of light. Each light engine can be directed independently. Available in open or closed faceplate options, trim and trimless.



Dimmable Lighting



Tunable Lighting



V2-BR Series Housing

HOUSING | V2-9W-HSG



Hanger bars can be adjusted from 8.35" to 23.25", to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for easy installation.

**The die-cast aluminum heat sink is painted black.*

Housing	V2-9W-HSG
Housing Description	- Specification grade single/multi-lamp luminaire - Design for new construction insulated ceiling - Made of 18-gauge steel and post painted - Vented housing for maximum heat dissipation and cool operation
Certifications	cULus E476753, JA8 Title 24
Mounting	Made of 18-gauge steel and can be adjusted vertically. Can be installed with 3/4" or 1-1/2" lathing channel, 1/2" EMT, or optional C-Channel mounting bars.
Ceiling Cut-out	8.75" x 4.5" / 222.25mm x 114.3mm
Ceiling Thickness	Perfect fit into ceiling, takes up to 1 1/2" thick ceiling



HOUSING DIMENSIONS





V2-BR SERIES KIT 9W / Open & Closed Trim



COMPLETE KIT INCLUDES

Housing



Two Bulbs



Open or Closed Trim



FEATURES

Wattage	2X9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	1200 lm	1240 lm	1280 lm	1320 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimensions	9.35" x 5.02" / 237.6mm x 127.6mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

OPEN TRIM	CLOSED TRIM
V2-9W-11-BR18-40K-20-OP	V2-9W-11-BR18-40K-20-CL
V2-9W-11-BR18-40K-40-OP	V2-9W-11-BR18-40K-40-CL
V2-9W-11-BR27-65K-20-OP	V2-9W-11-BR27-65K-20-CL
V2-9W-11-BR27-65K-40-OP	V2-9W-11-BR27-65K-40-CL

DESCRIPTION

V2-BR series kit is a high-performance tunable luminaire, can be easily installed in residential, commercial and hospitality spaces. The dual spots are considered as a complete unit including the housing, trim and bulb.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K



2700K 6500K



Working
Temperature




5 Year Limited
Warranty

INDOOR APPLICATION




TRIM DIMENSIONS

CLOSED TRIM



OPEN TRIM





V2-BR SERIES KIT 9W / Open & Closed Trimless



COMPLETE KIT INCLUDES



Housing



Two Bulbs



Open or Closed Trimless



FEATURES

Wattage	2X9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	1200 lm	1240 lm	1280 lm	1320 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimensions	9.35" x 5.02" / 237.6mm x 127.6mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

OPEN TRIMLESS	CLOSED TRIMLESS
V2-9W-11-BR18-40K-20-TL-OP	V2-9W-11-BR18-40K-20-TL-CL
V2-9W-11-BR18-40K-40-TL-OP	V2-9W-11-BR18-40K-40-TL-CL
V2-9W-11-BR27-65K-20-TL-OP	V2-9W-11-BR27-65K-20-TL-CL
V2-9W-11-BR27-65K-40-TL-OP	V2-9W-11-BR27-65K-40-TL-CL

DESCRIPTION

V2-BR series kit is a high-performance tunable luminaire, can be easily installed in residential, commercial and hospitality spaces. The dual spots are considered as a complete unit including the housing, trim and bulb.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



Working
Temperature




5 Year Limited
Warranty

RESIDENTIAL APPLICATION



TRIMLESS DIMENSIONS



VB1-BIANCA Series

These sleek and stylish luminaires include the 14W tunable, 95+ CRI, 1100 lumen light engine. The VB1 series delivers performance and beautiful aesthetics. Available in open and closed faceplate options.



Dimmable Lighting



Tunable Lighting




VB1-BIANCA Series Housing

HOUSING | V1-9W-HSG


Hanger bars can be adjusted from 8.35" to 23.25", to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for easy installation.

**The die-cast aluminum heat sink is painted black.*

Housing	V1-9W-HSG
Housing Description	- Specification grade single/multi-lamp luminaire - Designed for new construction insulated ceiling - Made of 18-gauge steel and post painted - Vented housing for maximum heat dissipation and cool operation.
Certifications	cULus E476753, JA8 Title 24
Mounting	Made of 18-gauge steel and can be adjusted vertically. Can be installed with ¾" or 1-1/2" lathing channel, ½" EMT, or optional C-Channel mounting bars.
Ceiling Cut-out	4.5" x 4.5" / 114.3mm x 114.3mm
Ceiling Thickness	Perfect fit into ceiling, takes up to 1 ½" thick ceiling



HOUSING DIMENSIONS





VB1-SERIES KIT 14W / Open & Closed Trim



COMPLETE KIT INCLUDES

Housing



One Bulb



Open or Closed Trim



FEATURES

Wattage	14 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	900 lm	600 lm	1100 lm	900 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimensions	5.02" x 5.02" / 127.6mm x 127.6mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

OPEN TRIM	CLOSED TRIM
VB1-14W-11-BI18-40K-20-OP	VB1-14W-11-BI18-40K-20-CL
VB1-14W-11-BI18-40K-40-OP	VB1-14W-11-BI18-40K-40-CL
VB1-14W-11-BI27-65K-20-OP	VB1-14W-11-BI27-65K-20-CL
VB1-14W-11-BI27-65K-40-OP	VB1-14W-11-BI27-65K-40-CL

*Trims also available in Matte Black (Color Code: 22)

DESCRIPTION

Luminaires available in a wide variety of options, the VB1 luminaire adds sophistication to any space.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting

CRI 95⁺

1800K 4000K



2700K 6500K



Working
Temperature




5 Year Limited
Warranty

INDOOR APPLICATION




TRIM DIMENSIONS

CLOSED TRIM



OPEN TRIM





VB1-SERIES KIT 14W / Open & Closed Trimless



COMPLETE KIT INCLUDES


Housing



One Bulb



Open or Closed Trimless



FEATURES

Wattage	14 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	900 lm	600 lm	1100 lm	900 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimensions	5.02" x 5.02" / 127.6mm x 127.6mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

OPEN TRIM	CLOSED TRIMLESS
VB1-14W-11-BI18-40K-20-TL-OP	VB1-14W-11-BI18-40K-20-TL-CL
VB1-14W-11-BI18-40K-40-TL-OP	VB1-14W-11-BI18-40K-40-TL-CL
VB1-14W-11-BI27-65K-20-TL-OP	VB1-14W-11-BI27-65K-20-TL-CL
VB1-14W-11-BI27-65K-40-TL-OP	VB1-14W-11-BI27-65K-40-TL-CL

*Trims also available in Matte Black (Color Code: 22)

DESCRIPTION

Luminaires available in a wide variety of options, the VB1 luminaire adds sophistication to any space.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting




Working
Temperature




5 Year Limited
Warranty

COMMERCIAL APPLICATION




TRIMLESS DIMENSIONS



VB2-BIANCA Series

These twin 14W tunable luminaire deliver 2200 lumens of light. Each light engine can be adjusted independently. Available in open and closed faceplate options, trim and trimless.



Dimmable Lighting



Tunable Lighting



US LISTED



VB2-BIANCA Series Housing

HOUSING | V2-9W-HSG



Hanger bars can be adjusted from 8.35" to 23.25", to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for easy installation.

** The die-cast aluminum heat sink is painted black.*

Housing	V2-9W-HSG
Housing Description	- Specification grade single/multi-lamp luminaire - Design for new construction insulated ceiling - Made of 18-gauge steel and post painted - Vented housing for maximum heat dissipation and cool operation
Certifications	cULus E476753, JA8 Title 24
Mounting	Made of 18-gauge steel and can be adjusted vertically. Can be installed with 3/4" or 1-1/2" lathing channel, 1/2" EMT, or optional C-Channel mounting bars.
Ceiling Cut-out	8.75" x 4.5" / 222.25mm x 114.3mm
Ceiling Thickness	Perfect fit into ceiling, takes up to 1 1/2" thick ceiling



HOUSING DIMENSIONS





VB2- SERIES KIT 14W / Open & Closed Trim



COMPLETE KIT INCLUDES

Housing



Two Bulbs



Open or Closed Trim



FEATURES

Wattage	2X14 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	1800 lm	1200 lm	2200 lm	1800 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimensions	9.35" x 5.02" / 237.6mm x 127.6mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

OPEN TRIM	CLOSED TRIM
VB2-14W-11-BI18-40K-20-OP	VB2-14W-11-BI18-40K-20-CL
VB2-14W-11-BI18-40K-40-OP	VB2-14W-11-BI18-40K-40-CL
VB2-14W-11-BI27-65K-20-OP	VB2-14W-11-BI27-65K-20-CL
VB2-14W-11-BI27-65K-40-OP	VB2-14W-11-BI27-65K-40-CL

*Trims also available in Matte Black (Color Code: 22)

DESCRIPTION

VB2-BIANCA series kit is a high-performance tunable luminaire. It is easily installed in residential, commercial and hospitality applications.

The dual spots are considered as a complete kit including the housing, trim and bulb.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K



2700K 6500K




Working
Temperature




5 Year Limited
Warranty

INDOOR APPLICATION




TRIM DIMENSIONS

CLOSED TRIM



OPEN TRIM





VB2- SERIES KIT 14W / Open & Closed Trimless



COMPLETE KIT INCLUDES


Housing



Two Bulbs



Open or Closed Trimless



FEATURES

Wattage	2X14 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	1800 lm	1200 lm	2200 lm	1800 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Trim Dimensions	9.35" x 5.02" / 237.6mm x 127.6mm			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

OPEN TRIM	CLOSED TRIM
VB2-14W-11-B118-40K-20-TL-OP	VB2-14W-11-B118-40K-20-TL-CL
VB2-14W-11-B118-40K-40-TL-OP	VB2-14W-11-B118-40K-40-TL-CL
VB2-14W-11-B127-65K-20-TL-OP	VB2-14W-11-B127-65K-20-TL-CL
VB2-14W-11-B127-65K-40-TL-OP	VB2-14W-11-B127-65K-40-TL-CL

*Trims also available in Matte Black (Color Code: 22)

DESCRIPTION

VB2-BIANCA series kit is a high-performance tunable luminaire. It is easily installed in residential, commercial and hospitality applications.

The dual spots are considered as a complete kit including the housing, trim and bulb.



Dimmable Lighting

0 to 100% flicker free dimming



Tunable Lighting



Working Temperature




5 Year Limited Warranty

RESIDENTIAL APPLICATION




TRIMLESS DIMENSIONS



VENUS

The Venus offers all the features and benefits sought after by luxury homeowners, designers, architects and builders. It is a slim, trimless, tunable luminaire of 1.5" thickness and delivers 1155 lumens of light. With an incredibly small 1.5" aperture, the VENUS combines the best of features in both performance and aesthetics.



Dimmable Lighting



Tunable Lighting




US LISTED



VENUS / Trimless



TRIMLESS DIMENSIONS



FEATURES

Wattage	16 Watts	
CCT	1800K - 4000K	2700K - 6500K
Luminous Flux	995 lumens	1155 lumens
CRI	80+/90+	
Beam Angle	40D	
Light Source	COB	
Dimming	Yes	
Dimensions	9.25*9.25*1.14 Inch / 235*235*29mm	
IP Grade	IP20 Standard	
Life Span	>50,000 hours	

PRODUCT CODES

MODEL	DESCRIPTION
VENUS-BI18-40K-16W	Thin White Trimless, Round or Square LED, 16W, 990-1040lm, 1800-4000K CCT Tunable, CRI 92, 30D
VENUS-BI27-65K-16W	Thin White Trimless, Round or Square, LED, 16W, 1400lm, 2700-6500K CCT Tunable, CRI 90, 30D

DESCRIPTION

This super slim trimless and tunable luminaire, is 1.5" in thickness and delivers 1155 lumens of light.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications..



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K

995 Lm

2700K 6500K

1155 Lm



Working Temperature



5 Year Limited Warranty

RESIDENTIAL APPLICATION




INSTALLED LUMINAIRE



MR 9W BR Series

The MR luminaire boasts ultimate sophistication, flexibility and performance. Housing a 9W tunable white or RGBW light engine, this trimless luminaire has a recessed look with an internal mechanism to position the light engine at any required right angle.



Dimmable Lighting



Tunable Lighting



MR 9W BR SERIES / Trimless



COMPLETE KIT INCLUDES



FEATURES

Wattage	9 Watts			
CCT	1800K - 4000K		2700K - 6500K	
Beam Angle	20D	40D	20D	40D
Total Lumens	600 lm	620 lm	640 lm	660 lm
LED CRI	≥95Ra			
LM Rating	LM-80			
Input Voltage	48 Volts RJ45			
Ceiling Cut Out	Ø 4-1/8"			
Certifications	cULus E476753, JA8 Title 24 (2700-6500K)			
Compatible Decoder	For dimming functionality use DMX-SR2112			
IP Grade	IP20 Standard			
Life Span	50,000 Hours			

PRODUCT CODES

MODEL	DESCRIPTION
MR-9W-BR18-40K-STL-1302-WH	Square Open Downlight, White, Trimless, 9W, White Bulb, 20D
MR-9W-BR27-65K-STL-1302-WH	Square Open Downlight, White, Trimless, 9W, White Bulb, 40D

DESCRIPTION

The super slim profile, trimless, tunable luminaire is 1.5" in thickness and delivers a powerful 660 lumens of light.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications..



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



1800K 4000K

2700K 6500K



Working
Temperature



5 Year Limited
Warranty

COMMERCIAL APPLICATION




INSTALLED LUMINAIRE








ROMA Series / LED Stair Lighting



Square

Round



FEATURES

Wattage	1.245 Watts	
Color Temperature	3000K	6000K
Total Lumens	85 lm	95 lm
Optic	45°	
LED CRI	≥95Ra	
Input Voltage	24VDC	
Luminaire Finish	Anodized aluminum	
Luminaire Material	Aluminium	
Fixation	Spring clips	
Working Temperature	-30 - +55°C	
Life Span	50,000 Hours	

PRODUCT CODES

MODEL	DESCRIPTION
ROMA-FC-W30K-SQ	Mini LED Wall/Ceiling Light, Square, 30K, 1W, 24V
ROMA-FC-W60K-SQ	Mini LED Wall/Ceiling Light, Square, 60K, 1W, 24V
ROMA-FC-W30K-RD	Mini LED Wall/Ceiling Light, Round, 30K, 1W, 24V
ROMA-FC-W60K-RD	Mini LED Wall/Ceiling Light, Round, 60K, 1W, 24V
ROMA-FC-W30K-RDS	Mini LED Wall/Ceiling Light, Round-Square, 30K, 1W, 24V
ROMA-FC-W60K-RDS	Mini LED Wall/Ceiling Light, Round-Square, 60K, 1W, 24V

DESCRIPTION

The Roma Series is our indoor walls & stairs lighting line. The CB-Mini-Roma is a recessed 1 Watt LED source available in both round and square shapes.

TYPICAL APPLICATIONS

For stairs & corridors as well as cabinets, closets & millwork applications.



Dimmable Lighting
0 to 100% flicker free dimming




Working
Temperature




5 Year Limited
Warranty

STAIRS APPLICATION



LIGHTING ANGLE



LED PANELS

Available in a fixed white temperature, tunable or RGB, Colorbeam's 1/2" thick LED panels are the perfect solution for general lighting applications in commercial and hospitality spaces. Dropped into a grid ceiling or suspended, Colorbeam LED panels deliver general lighting requirements and can be used to enhance any space or work environment utilizing Colorbeam's tunability technology or color.



Dimmable Lighting



Tunable Lighting



RGB Lighting



US LISTED





PNL-1X4 /LED Panel 1X4



DESCRIPTION

LED panel fixture uniform and soft light, no glare, delicate structure design and ultra light.

TYPICAL APPLICATIONS

Ideally suited for use in residential, and commercial lighting applications.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



RGB

2700K 6500K

3300 Lm

RGB



Working Temperature



5 Year Limited Warranty


FEATURES

Wattage	40 Watts			
CCT	2700K - 6500K	3000K	4500K	RGB
Total Lumens	3300 lm	3300 lm	3300 lm	
Size	11.81" x 47.24" x 0.55"			
Angle	120 Degree			
Working Temperature	-20°C/-4°F to 45°C/113°F			
Input Voltage	24VDC			
Gross Weight	4 Kg			
Compatible Decoder	DMX-5CH-SR2108			
Protection Grade	IP52			
Life Span	50,000 Hours			


PRODUCT CODES

MODEL	DESCRIPTION
PNL-1x4-BI-40W-CCT	LED Panel 1x4', 3300Lm, 2700K-6500K, 40W, 90+, 8.8lb, 24V, Copper/ Aluminium, IP20
PNL-1x4-RGB-40W	LED Panel 1x4', RGB, 40W, 8.8lb, 24V, Copper/ Aluminium, IP20
PNL-1x4-W30K-40W	LED Panel 1x4', 3300Lm, 3000K, 40W, 90+, 8.8lb, 24V, Copper/ Aluminium, IP20
PNL-1x4-W45K-40W	LED Panel 1x4', 3300Lm, 4500K, 40W, 90+, 8.8lb, 24V, Copper/ Aluminium, IP20

COMMERCIAL LIGHTING



DIMENSIONS



PNL-2X2 /LED Panel 2X2



FEATURES

Wattage	36 Watts	42 Watts	42 Watts	52 Watts
CCT	2700K - 6500K	3000K	4500K	RGB
Total Lumens	2800 lm	2800 lm	2800 lm	
Size	23.42" x 23.42" x 0.40"			
Angle	120 Degree			
Working Temperature	-20°C/-4°F to 45°C/113°F			
Input Voltage	24VDC			
Gross Weight	3.8 Kg			
Compatible Decoder	DMX-5CH-SR2108			
Protection Grade	IP52			
Life Span	50,000 Hours			

PRODUCT CODES

MODEL	DESCRIPTION
PNL-2x2-BI-36W-CCT	LED Panel, 2'x2', 24V, 36W, 2700K, 90+, Aluminium/Cooper, IP20
PNL-2x2-RGB-52W	LED Panel 2'x2', RGB, 52W, 8.37lb, 24V, Copper/ Aluminium, IP52
PNL-2x2-W30K-42W	LED Panel 2'x2', 3200lm, 3000K, 42W, 90+, 8.37lb, 24V, Copper/ Aluminium, IP52
PNL-2x2-W45K-42W	LED Panel 2'x2', 3200lm, 4500K, 42W, 90+, 8.37lb, 24V, Copper/ Aluminium, IP52

DESCRIPTION

LED panel fixture uniform and soft light, no glare, delicate structure design and ultra light.

TYPICAL APPLICATIONS

Ideally suited for use in residential, and commercial lighting applications.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



RGB

2700K

6500K

RGB

3200 Lm



Working
Temperature




5 Year Limited
Warranty

COMMERCIAL LIGHTING



DIMENSIONS





PNL-2X4 /LED Panel 2X4



FEATURES

Wattage	55 Watts	55 Watts	60 Watts	60 Watts
CCT	2700K - 6500K	3000K	4500K	RGB
Total Lumens	4800 lm	4800 lm	4800 lm	
Size	23.42" x 47.04" x 0.55"			
Angle	120 Degree			
Working Temperature	-20°C/-4°F to 45°C/113°F			
Input Voltage	24VDC			
Gross Weight	9 Kg			
Compatible Decoder	DMX-5CH-SR2108			
Protection Grade	IP52			
Life Span	50,000 Hours			

PRODUCT CODES

MODEL	DESCRIPTION
PNL-2x4-BI-55W-CCT	LED Panel 2'x4', 4800lm, 2700K-6500K, 55W, 90+, 18.84lb, 24V, Copper / Aluminium, IP20
PNL-2x4-RGB-55W	LED Panel 2'x4', RGB, 55W, 18.84lb, 24V, Copper / Aluminium, IP20
PNL-2x4-W30K-60W	LED Panel 2'x4', 4800lm, 3000K, 60W, 90+, 18.84lb, 24V, Copper / Aluminium, IP20
PNL-2x4-W45K-60W	LED Panel 2'x4', 4800lm, 4500K, 60W, 90+, 18.84lb, 24V, Copper / Aluminium, IP21

DESCRIPTION

LED panel fixture uniform and soft light, no glare, delicate structure design and ultra light.

TYPICAL APPLICATIONS

Ideally suited for use in residential, and commercial lighting applications.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



RGB




Working Temperature





5 Year Limited Warranty

COMMERCIAL LIGHTING



DIMENSIONS





Skylight

Imagine sunlight anywhere, anytime, and on demand

The revolutionary Colorbeam digital skylight

Sunlight plays a vital role in our well-being, mood, and productivity. Skylight is the first artificial daylight system, which mimics natural light. Colorbeam's Skylight solution integrates the latest LED technology, optical design, and intelligent control system.

Skylight Offers:

- Natural view of high-quality sky simulation
- Natural daylight effect including skylight and sunshine
- Skylight and sunlight can synchronize to the sun over a 24 hour cycle

Typical Applications:

- Residential
- Commercial (offices, schools, hospitals, retail, etc.)



FRAME ON
EW-2x4-BI25-10K-CL-FO



FRAME IN
EW-2x2-BI25-10K-CL-FI

SKYLIGHT 2X2



FEATURES

ITEMS	TYPICAL	MINIMUM	MAXIMUM
Size	23.42" x 23.42" x 3.34"		
Power		10W	260W
Voltage		100V	277V
Current		0.1A	3A
Mains frequency	50/60Hz		
Power Factor	0.95	0.93	0.98
Dimmable Range		1%	100%
Total Lumens		50Lm	7300Lm
Luminous Intensity		17cd	145000cd
CCT	5600K	2500K	10000K
Ra	95	93	98
Working Temperature	25°C	-25°C	45°C
Life Time	50,000Hr		
Certification	CE/CCC		

PRODUCT CODES

MODEL	DESCRIPTION
DSK-2x2-BI25-10K-CL-FO	Skylight, Cloudless, 2X2, BI 2500-10000K, 260W, CCT, Frame On
DSK-2x2-BI25-10K-CL-FI	Skylight, Cloudless, 2X4, BI 2500-10000K, 260W, CCT, Frame In
DSK-2x2-BI25-10K-CD-FO	Skylight with Clouds, 2X4, BI 2500-10000K, 260W, CCT, Frame On
DSK-2x2-BI25-10K-CD-FI	Skylight with Clouds, 2X4, BI 2500-10000K, 260W, CCT, Frame In

DESCRIPTION

Skylight is the first artificial daylight system, which mimics natural light. Colorbeam's Skylight solution integrates the latest LED technology, optical design, and intelligent control system.

TYPICAL APPLICATIONS

For commercial, education and medical facilities as well as retirement homes and office spaces and conference rooms.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



Working
Temperature




5 Year Limited
Warranty

COMMERCIAL LIGHTING



DIMENSIONS





SKYLIGHT 2X4



FEATURES

ITEMS	TYPICAL	MINIMUM	MAXIMUM
Size	46.04" x 22.44" x 3.34"		
Power		10W	260W
Voltage		100V	277V
Current		0.1A	3A
Mains frequency	50/60Hz		
Power Factor	0.95	0.93	0.98
Dimmable Range		1%	100%
Total Lumens		50Lm	7300Lm
Luminous Intensity		17cd	145000cd
CCT	5600K	2500K	10000K
Ra	95	93	98
Working Temperature	25°C	-25°C	45°C
Life Time	50,000Hr		
Certification	CE/CCC		

PRODUCT CODES

MODEL	DESCRIPTION
DSK-2x4-BI25-10K-CL-FI	Skylight, Cloudless, 2X4, BI 2500-10000K, 260W, CCT, Frame On
DSK-2x4-BI25-10K-CL-FO	Skylight, Cloudless, 2X4, BI 2500-10000K, 260W, CCT, Frame In
DSK-2x4-BI25-10K-CD-FI	Skylight with Clouds, 2X4, BI 2500-10000K, 260W, CCT, Frame On
DSK-2x4-BI25-10K-CD-FO	Skylight with Clouds, 2X4, BI 2500-10000K, 260W, CCT, Frame In

DESCRIPTION

Skylight is the first artificial daylight system, which mimics natural light. Colorbeam's Skylight solution integrates the latest LED technology, optical design, and intelligent control system.

TYPICAL APPLICATIONS

For commercial, education and medical facilities as well as retirement homes and office spaces and conference rooms.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



Working
Temperature



5 Year Limited
Warranty

RESIDENTIAL LIGHTING




DIMENSIONS





RGBW L



ighting



T-BIANCA SERIES 10W RGBW

T-BIANCA SERIES 10W RGBW Kit is a complete unit including the luminaire, trim and housing.



Dimmable Lighting



Tunable Lighting



RGB White



US LISTED

T-BIANCA SERIES 10W RGBW

PRE-CONSTRUCTION PLATE & HOUSING


Designed for direct contact with insulation. Can be installed in 1/2" to 1-3/8" thick ceilings. Includes adjustable hanger bars.

**Pre-construction plate is an optional accessory.*


Pre-Construction Plate	T-NCMP
Housing	T-H-9-5-5/8-CAN
Ceiling Cut-out	Ø 3.54" / Ø 90mm
Ceiling Thickness	1/2" / 12.7mm to 1 1/2" / 38.1mm



PRE-CONSTRUCTION PLATE | T-NCMP



HOUSING | T-H-9-5-5/8-CAN






T-BIANCA SERIES-10W-RGBW / Round Trim



FEATURES

Wattage	10 Watts	
CCT	RGB + White	
Beam Angle	20D	40D
Total Lumens	540 lm	500 lm
LED CRI	≥95Ra (White chip only)	
LM Rating	LM-80	
Input Voltage	48 Volts RJ45	
Trim Dimensions	Ø 4.45" x 1.20" / Ø 113mm x 30.5mm	
Certifications	cULus E476753	
Compatible Decoder	For dimming functionality use DMX-SR2112	
IP Grade	IP20 Standard	
Life Span	50,000 Hours	



DESCRIPTION

This matt round trim is sleek and stylish with a small aperture; available in white and black.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



RGBW




Working
Temperature



5 Year Limited
Warranty

TRIM DIMENSIONS



PRODUCT CODES

MATTE WHITE	MATTE BLACK
TB-150-11-10W-RGBW-W20-IP20	TB-150-22-10W-RGBW-B20-IP20
TB-150-11-10W-RBW-W40-IP20	TB-150-22-10W-RGBW-B40-IP20

**IP65 also available




T-BIANCA SERIES-10W-RGBW / Square Trim



FEATURES

Wattage	10 Watts	
CCT	RGB + White	
Beam Angle	20D	40D
Total Lumens	540 lm	500 lm
LED CRI	≥95Ra (White chip only)	
LM Rating	LM-80	
Input Voltage	48 Volts RJ45	
Trim Dimensions	4.27" x 4.27" / 108.5mm x 108.5mm	
Certifications	cULus E476753	
Compatible Decoder	For dimming functionality use DMX-SR2112	
IP Grade	IP20 Standard	
Life Span	50,000 Hours	



DESCRIPTION

This matt square trim is sleek and stylish with a small aperture; available in white and black.

TYPICAL APPLICATIONS

For residential, commercial and hospitality applications.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting

CRI 95⁺

RGBW





Working
Temperature



5 Year Limited
Warranty

TRIM DIMENSIONS




PRODUCT CODES

MATTE WHITE	MATTE BLACK
TB-650-11-10W-RGBW-W20-IP20	TB-650-22-10W-RGBW-B20-IP20
TB-650-11-10W-RBW-W40-IP20	TB-650-22-10W-RGBW-B40-IP20

**IP65 also available

VBI-RGBW Series

VBI-RGBW Series Housing is for the tunable 10W RGBW light engine; it offers the ability to deliver tunable white light. The VBI is available in both open and closed face plate options, as well as a trim and a trimless model.



Dimmable Lighting



Tunable Lighting



RGB White




c US LISTED

VB1-RGBW Series Housing


HOUSING | V1-12/36W-HSG

Hanger bars can be adjusted from 14 ½" to 25", to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for easy installation. Can accommodate a ½" to 1 ¼" ceiling thickness.
* The die-cast aluminum heat sink is painted black.

Housing	V1-12/36W-HSG
Housing Description	- Specification grade single/multi-lamp luminaire - Designed for new construction insulated ceiling - Made of 18-gauge steel and post painted - Vented housing for maximum heat dissipation and cool operation
Certifications	cULus E476753, JA8 Title 24
Mounting	Made of 18-gauge steel and can be adjusted vertically. Can be installed with ¾" or 1-1/2" lathing channel, ½" EMT, or optional C-Channel mounting bars.
Ceiling Cut-out	4.5" x 4.5" / 114.3mm x 114.3mm
Ceiling Thickness	Perfect fit into ceiling, takes up to 1 ½" thick ceiling



HOUSING DIMENSIONS





VBI- SERIES KIT 10W RGBW / Closed Trim



COMPLETE KIT INCLUDES

Housing



One Bulb



Open or Closed Square Trim



Trim Finish: Matte White (11) & Matte Black (22)

FEATURES

Wattage	10 Watts	
CCT	RGB + White	
Beam Angle	20D	40D
Total Lumens	540 lm	500 lm
LED CRI	≥95Ra (White chip only)	
LM Rating	LM-80	
Input Voltage	48 Volts RJ45	
Trim Dimensions	5.02" x 5.02" / 127.6mm x 127.6mm	
Certifications	cULus E476753	
Compatible Decoder	For dimming functionality use DMX-SR2112	
IP Grade	IP20 Standard	
Life Span	50,000 Hours	

PRODUCT CODES

OPEN TRIM	CLOSED TRIM
VB1-10W-11-RGBW-20-OP	VB1-10W-11-RGBW-20-CL
VB1-10W-11-RGBW-40-OP	VB1-10W-11-RGBW-40-CL
VB1-10W-22-RGBW-20-OP	VB1-10W-22-RGBW-20-CL
VB1-10W-22-RGBW-40-OP	VB1-10W-22-RGBW-40-CL

DESCRIPTION

VBI-SERIES KIT is a high performance RGBW and tunable luminaire that can be easily installed into any residential space. The VBI-Series Kit consumes 10 watts and replaces a 50W halogen; saving up to 80% energy for same light output. This kit includes: 10W RGBW bulb, trim and housing.

Available in Open and Closed Square Trim options; and in white and black matte finish.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



RGBW

RGBW



Working Temperature
-30°C
+60°C




5 Year Limited
Warranty

RESIDENTIAL APPLICATION




TRIM DIMENSIONS

CLOSED TRIM



OPEN TRIM





VB1- SERIES KIT 10W RGBW / Trimless



COMPLETE KIT INCLUDES


Housing



One Bulb



Open or Closed Square Trimless



Trim Finish: Matte White (11) & Matte Black (22)

FEATURES

Wattage	10 Watts	
CCT	RGB + White	
Beam Angle	20D	40D
Total Lumens	540 lm	500 lm
LED CRI	≥95Ra (White chip only)	
LM Rating	LM-80	
Input Voltage	48 Volts RJ45	
Trim Dimensions	5.02" x 5.02" / 127.6mm x 127.6mm	
Certifications	cULus E476753	
Compatible Decoder	For dimming functionality use DMX-SR2112	
IP Grade	IP20 Standard	
Life Span	50,000 Hours	

PRODUCT CODES

OPEN TRIM	CLOSED TRIM
VB1-10W-11-RGBW-20-TL-OP	VB1-10W-11-RGBW-20-TL-CL
VB1-10W-11-RGBW-40-TL-OP	VB1-10W-11-RGBW-40-TL-CL
VB1-10W-22-RGBW-20-TL-OP	VB1-10W-22-RGBW-20-TL-CL
VB1-10W-22-RGBW-40-TL-OP	VB1-10W-22-RGBW-40-TL-CL

DESCRIPTION

VB1-SERIES KIT is a high performance RGBW and tunable luminaire that can be easily installed into any residential space. The VB1-Series Kit consumes 10 watts and replaces a 50W halogen; saving up to 80% energy for same light output. This kit includes: 10W RGBW bulb, trimless and housing.

Available in open and closed square trimless options; and in white and black matte finish.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



RGBW

RGBW



Working
Temperature




5 Year Limited
Warranty

RESIDENTIAL APPLICATION



TRIMLESS DIMENSIONS







VI- SERIES KIT 20W RGBW / Trim & Trimless



COMPLETE KIT INCLUDES

Housing



One Bulb



Trim & Trimless



Finish: Matte White

FEATURES

Wattage	20 Watts
CCT	RGB + White
Beam Angle	40D
Total Lumens	1058 lm
LED CRI	≥95Ra (White chip only)
LM Rating	LM-80
Input Voltage	48 Volts RJ45
Trim Dimensions	8" X 8" / 200mm x 200mm
Certifications	cULus E476753
Compatible Decoder	For dimming functionality use DMX-SR2112
IP Grade	IP20 Standard
Life Span	50,000 Hours

PRODUCT CODES

MODEL	DESCRIPTION
VI-20W-RGBW-W40	Trim with 20W, RGBW, White Bulb, 40D
VI-20W-RGBW-B40	Trim with 20W, RGBW, Black Bulb, 40D
VI-20W-RGBW-W40-TL	Trim with 20W, RGBW, White Bulb, 40D, Trimless
VI-20W-RGBW-B40-TL	Trim with 20W, RGBW, Black Bulb, 40D, Trimless

DESCRIPTION

VI-SERIES KIT is a high performance RGBW and tunable luminaire. It can create color changing features that transform a space to any required mood and feel. Available in trim and trimless options with a white matte finish.

TYPICAL APPLICATIONS

For use in residential, commercial and hospitality applications.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



RGBW

RGBW



Working
Temperature




5 Year Limited
Warranty

INDOOR APPLICATION




TRIM DIMENSIONS



VB2-RGBW Series

VB2-RGBW Series Housing is for two of the 10W tunable RGBW light engines; it offers the ability to deliver tunable white light; with twice the lumen output of the VB1. The VB2 is available in both open and closed face plate options, as well as a trim and a trimless model. Each light engine can be adjusted independently.



Dimmable Lighting



Tunable Lighting



RGB White



US LISTED

VB2-RGBW Series Housing

HOUSING | V2-12/36W-HSG


Hanger bars can be adjusted from 8.35" to 23.25", to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for easy installation.

** The die-cast aluminum heat sink is painted black.*

Housing	V2-12/36W-HSG
Housing Description	- Specification grade single/multi-lamp luminaire - Design for new construction insulated ceiling - Made of 18-gauge steel and post painted - Vented housing for maximum heat dissipation and cool operation
Certifications	cULus E476753
Mounting	Made of 18-gauge steel and can be adjusted vertically. Can be installed with 3/4" or 1-1/2" lathing channel, 1/2" EMT, or optional C-Channel mounting bars.
Ceiling Cut-out	8.75" x 4.5" / 222.25mm x 114.3mm
Ceiling Thickness	Perfect fit into ceiling, takes up to 1 1/2" thick ceiling



HOUSING DIMENSIONS





VB2- SERIES KIT 2X10W RGBW / Closed Trim



COMPLETE KIT INCLUDES

Housing



Two Bulbs



Open or Closed Trim



DESCRIPTION

VB2-SERIES KIT is a high performance RGBW and tunable luminaire that can be easily installed in any space. This kit includes: 2X10W Luminaires, Trim and Housing. Available in open and closed trim options.

TYPICAL APPLICATIONS

For use in residential, commercial and hospitality applications.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



RGBW

RGBW



Working
Temperature



5 Year Limited
Warranty

FEATURES

Wattage	10 Watts	
CCT	RGB + White	
Beam Angle	20D	40D
Total Lumens	1080 lm	1000 lm
LED CRI	≥95Ra (White chip only)	
LM Rating	LM-80	
Input Voltage	48 Volts RJ45	
Trim Dimensions	9.35" x 5.02" / 237.6mm x 127.6mm	
Certifications	cULus E476753	
Compatible Decoder	For dimming functionality use DMX-SR2112	
IP Grade	IP20 Standard	
Life Span	50,000 Hours	


PRODUCT CODES

OPEN TRIM	CLOSED TRIM
VB2-10W-11-RGBW-20-OP	VB2-10W-11-RGBW-20-CL
VB2-10W-11-RGBW-40-OP	VB2-10W-11-RGBW-40-CL
VB2-10W-22-RGBW-20-OP	VB2-10W-22-RGBW-20-CL
VB2-10W-22-RGBW-40-OP	VB2-10W-22-RGBW-40-CL

RESIDENTIAL APPLICATION




TRIM DIMENSIONS





VB2- SERIES KIT 2X10W RGBW / Trimless



COMPLETE KIT INCLUDES



Housing



Two Bulbs



Open or Closed Trimless



FEATURES

Wattage	10 Watts	
CCT	RGB + White	
Beam Angle	20D	40D
Total Lumens	1080 lm	1000 lm
LED CRI	≥95Ra (White chip only)	
LM Rating	LM-80	
Input Voltage	48 Volts RJ45	
Trim Dimensions	9.35" x 5.02" / 237.6mm x 127.6mm	
Certifications	cULus E476753	
Compatible Decoder	For dimming functionality use DMX-SR2112	
IP Grade	IP20 Standard	
Life Span	50,000 Hours	

PRODUCT CODES

OPEN TRIM	CLOSED TRIM
VB2-10W-11-RGBW-20-TL-OP	VB2-10W-11-RGBW-20-TL-CL
VB2-10W-11-RGBW-40-TL-OP	VB2-10W-11-RGBW-40-TL-CL
VB2-10W-22-RGBW-20-TL-OP	VB2-10W-22-RGBW-20-TL-CL
VB2-10W-22-RGBW-40-TL-OP	VB2-10W-22-RGBW-40-TL-CL

DESCRIPTION

VB2-SERIES KIT is a high performance RGBW and tunable luminaire that can be easily installed in any space. This kit includes: 2X10W Luminaires, Trim and Housing. Available in open and closed trimless options.

TYPICAL APPLICATIONS

For use in residential, commercial and hospitality applications.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



RGBW

RGBW



Working
Temperature




5 Year Limited
Warranty

COMMERCIAL APPLICATION



TRIMLESS DIMENSIONS





V2- SERIES KIT 20W RGBW / Trim & Trimless



COMPLETE KIT INCLUDES



FEATURES

Wattage	2X20 Watts
CCT	RGB + White
Beam Angle	40D
Total Lumens	2116 lm
LED CRI	≥95Ra (White chip only)
LM Rating	LM-80
Input Voltage	48 Volts RJ45
Trim Dimensions	14.46" X 7.94" / 367.4mm x 201.7mm
Certifications	cULus E476753
Compatible Decoder	For dimming functionality use DMX-SR2112
IP Grade	IP20 Standard
Life Span	50,000 Hours

PRODUCT CODES

MODEL	DESCRIPTION
V1-20W-RGBW-W40	Trim with 20W, RGBW, White Bulb, 40D
V1-20W-RGBW-B40	Trim with 20W, RGBW, Black Bulb, 40D
V1-20W-RGBW-W40-TL	Trim with 20W, RGBW, White Bulb, 40D, Trimless
V1-20W-RGBW-B40-TL	Trim with 20W, RGBW, Black Bulb, 40D, Trimless

DESCRIPTION

V2-SERIES KIT is a high performance RGBW and tunable luminaire that can be easily installed in any space. This kit includes: 2X20W Luminaires, Trim and Housing. Available in trim and trimless options in white matte finish.

TYPICAL APPLICATIONS

For use in residential, commercial and hospitality applications.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



RGBW

RGBW



Working
Temperature




5 Year Limited
Warranty

RESIDENTIAL APPLICATION



TRIM DIMENSIONS





C SERIES RGBW Round & Square Trim

The C series offers a trim for RGBW 20W light engines. Installation requires nothing but a 6.30" cut-out in the sheetrock. The trim's spring clamp sets it in place.



Dimmable Lighting



Tunable Lighting



RGB White



C US LISTED


C SERIES RGBW Pre-construction plate

PRE-CONSTRUCTION PLATE | C-NCMP-RD


Hanger bars are adjustable from 14 1/2"–25" to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting “screw-nail” for easy installation. Can accommodate a 1/2" to 1 1/4" ceiling thickness.

Pre-Construction Plate	C-NCMP-RD
Ceiling Cut-out	Ø 6.30" / Ø 160mm
Ceiling Thickness	1/2" / 12.7mm to 1 1/2" / 38.1mm

PRE-CONSTRUCTION PLATE DIMENSIONS



**Pre-construction plate is an optional accessory.*





C SERIES 20W RGBW/Round Trim



COMPLETE KIT INCLUDES

One Bulb



Trim

Finish: Matte White
Matte Black

DESCRIPTION

C-SERIES KIT is a high performance RGBW and tunable luminaire that can be easily installed in any space. This square trim is available in white and black finish.

TYPICAL APPLICATIONS

For use in residential, commercial and hospitality applications.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



RGBW

RGBW



Working
Temperature



5 Year Limited
Warranty

FEATURES

Wattage	20 Watts
CCT	RGB + White
Beam Angle	40D
Total Lumens	1058 Lumens
LED CRI	≥95Ra (White chip only)
LM Rating	LM-80
Input Voltage	48 Volts RJ45
Trim Dimensions	Ø 7.16" / Ø 182mm
Certifications	cULus E476753
Compatible Decoder	For dimming functionality use DMX-SR2112
IP Grade	IP20 Standard
Life Span	50,000 Hours


PRODUCT CODES

MODEL	DESCRIPTION
C-W-RD-20W-RGBW-W40	White Round Trim, 20W, RGBW, White Bulb, 40D
C-B-RD-20W-RGBW-B40	Black Round Trim, 20W, RGBW, Black Bulb, 40D

RESIDENTIAL APPLICATION




TRIM DIMENSIONS





C SERIES 20W RGBW/Square Trim



COMPLETE KIT INCLUDES

One Bulb



Trim

Finish: Matte White
Matte Black

DESCRIPTION

C-SERIES KIT is a high performance RGBW and tunable luminaire that can be easily installed in any space. This round trim is available in white and black finish.

TYPICAL APPLICATIONS

For use in residential, commercial and hospitality applications.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



RGBW

RGBW



Working
Temperature



5 Year Limited
Warranty

FEATURES

Wattage	20 Watts
CCT	RGB + White
Beam Angle	40D
Total Lumens	1058 Lumens
LED CRI	≥95Ra (White chip only)
LM Rating	LM-80
Input Voltage	48 Volts RJ45
Trim Dimensions	7.16" x 7.16" / 182 x 182mm
Certifications	cULus E476753
Compatible Decoder	For dimming functionality use DMX-SR2112
IP Grade	IP20 Standard
Life Span	50,000 Hours


PRODUCT CODES

MODEL	DESCRIPTION
C-W-SQ-20W-RGBW-W40	White Square Trim, 20W, RGBW, White Bulb, 40D
C-B-SQ-20W-RGBW-B40	Black Square Trim, 20W, RGBW, Black Bulb, 40D



RESIDENTIAL APPLICATION



TRIM DIMENSIONS



LED Tapes



& Tracks



LED TAPES

White, Tunable White, RGB and RGBW

Our LED Tapes are dimmable, tunable and compatible with third party DMX control



Dimmable Lighting



Tunable Lighting



RGB Lighting



US LISTED







TAPE 30 RGB / 16.4FT Roll



TAPE-30-RGB



TAPE-30-RGB-IP68

FEATURES

Power Rating per meter/3.3FT:	8.16W, 24V, 0.34A
LED Quantity:	30 LED/M
Luminous Flux per meter/3.3FT:	600 Lm/M
Color/CCT:	RGB
Chip:	EPISTAR
CRI:	N/A
Beam Angle:	120°
Max Run Length:	5 meters (16.4FT/Roll)
Cut Length:	166mm/6.5" or 5 LEDs
PCB Width:	10mm (IP68 - 12.5mm)
IP Rating:	IP20 Standard / IP68
Life Span:	>50,000 hours

PRODUCT CODES

MODEL	DESCRIPTION
TAPE-30-RGB	Tape 30 LED/M, RGB, 8.16W/M, 95+, 600lm/M, 5M (16.4FT/Roll), 10mm, 24V, IP20
TAPE-30-RGB-IP68	Tape 30 LED/M, RGB, 8.16W/M, 95+, 600lm/M, 5M (16.4FT/Roll), 14mm, Dimmable, 24V, IP68

DESCRIPTION

- Fully dimmable and color controllable
- Double sided 3m tape backing
- Low power consumption
- Low heat emission
- Available in IP20 or IP68
- Easy to install

TYPICAL APPLICATIONS

- Accent lighting
- Decorative lighting
- Architectural lighting



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting




RGB

RGB



3 Year Limited
Warranty






COMPATIBLE TRACKS/TRIMLESS TRACKS

TRACK-OP-002



TRACK-OP-004



TRACK-OP-006



TRACK-OP-008



TRACK-OP-010



TRACK-OP-011



TRACK-OP-013



TRACK-OP-014



TRACK-OP-035



TRACK-OP-036



TRACK-OP-039-TL



TRACK-OP-040-TL



TRACK-OP-055-TL



TRACK-OP-056-TL



TRACK-OP-079-TL



*For a dot-less result use one of these recommended track diffuser combinations.

**Tapes with IP68 fit in tracks with an inner width of 12.4mm or more.

MOUNTING OPTIONS

Ceiling



Recessed



Pendant



Wall





TAPE 60 RGB / 16.4FT Roll



TAPE-60-RGB



TAPE-60-RGB-IP68

FEATURES

Power Rating per meter/3.3FT:	14.4W, 24V, 0.6A
LED Quantity:	60 LED/M
Luminous Flux per meter/3.3FT:	1200lm/M
Color/CCT:	RGB
Chip:	EPISTAR
CRI:	N/A
Beam Angle:	120°
Max Run Length:	5 meters (16.4FT/Roll)
Cut Length:	100mm/4" or 6 LEDs
PCB Width:	10mm (IP68 - 12.4mm)
IP Rating:	IP20 Standard / IP68
Life Span:	>50,000 hours

PRODUCT CODES

MODEL	DESCRIPTION
TAPE-60-RGB	Tape 60 LED/M, RGB, 14.4W/M, 95+, 1200lm/M, 5M (16.4FT/Roll), 10mm, Dimmable, 24V, IP20
TAPE-60-RGB-IP68	Tape 60 LED/M, RGB, 14.4W/M, 95+, 1200lm/M, 5M (16.4FT/Roll), 14mm, Dimmable, 24V, IP68

DESCRIPTION

- Fully dimmable and color controllable
- Double sided 3m tape backing
- Low power consumption
- Low heat emission
- Available in IP20 or IP68
- Easy to install

TYPICAL APPLICATIONS

- Accent lighting
- Decorative lighting
- Architectural lighting



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting




RGB

RGB



3 Year Limited
Warranty



COMPATIBLE TRACKS/TRIMLESS TRACKS

TRACK-OP-002



TRACK-OP-004



TRACK-OP-006



TRACK-OP-008



TRACK-OP-010



TRACK-OP-011



TRACK-OP-013



TRACK-OP-014



TRACK-OP-035



TRACK-OP-036



TRACK-OP-039-TL



TRACK-OP-040-TL



TRACK-OP-055-TL



TRACK-OP-056-TL




TRACK-OP-079-TL



*For a dot-less result use one of these recommended track diffuser combinations.

**Tapes with IP68 fit in tracks with an inner width of 12.4mm or more.

MOUNTING OPTIONS






TAPE 240 RGB / 16.4FT Roll



TAPE-240-RGB*



FEATURES

Power Rating per meter/3.3FT:	26.5W, 24V, 1.1A
LED Quantity:	240 LED/M
Luminous Flux per meter/3.3FT:	1920-2400 Lm
Color/CCT:	RGB
Chip:	EPISTAR
CRI:	N/A
Beam Angle:	120°
Max Run Length:	5 meters (16.4FT/Roll)
Cut Length:	25mm/0.99" or 6 LEDs
PCB Width:	22mm
IP Rating:	IP20 Standard
Life Span:	>50,000 hours

PRODUCT CODES

MODEL	DESCRIPTION
TAPE-240-RGB	Tape 240 LED/M, RGB, 26.5W/M, 1940-2400Lm/Led, 5M (16.4FT/Roll), 22mm, Dimmable, 24V

DESCRIPTION

- Fully dimmable and color controllable
- Double sided 3m tape backing
- Low power consumption
- Low heat emission
- Available in IP20 or IP68
- Easy to install

TYPICAL APPLICATIONS

- Accent lighting
- Decorative lighting
- Architectural lighting



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting




RGB

RGB



3 Year Limited
Warranty





COMPATIBLE TRACKS/TRIMLESS TRACKS

TRACK-OP-051



TRACK-OP-038-TL



TRACK-OP-028



TRACK-OP-056-TL



TRACK-OP-017



TRACK-OP-057-TL



TRACK-OP-080-TL




TRACK-OP-058-TL



**For a dot-less result use one of these recommended track diffuser combinations.*

***Tapes with IP68 fit in tracks with an inner width of 12.4mm or more.*

MOUNTING OPTIONS





TAPE 60 RGBW / 16.4FT Roll



TAPE-60-RGBW



TAPE-60-RGBW-IP68

FEATURES

Power Rating per meter/3.3FT:	14.4W, 24V, 0.6A
LED Quantity:	60 LED/M
Luminous Flux per meter/3.3FT:	2800 Lm/M
Color/CCT:	RGB + 2700K, 3000, 3300K, 5000K
Chip:	EPISTAR
CRI:	N/A
Beam Angle:	120°
Max Run Length:	5 meters (16.4FT/Roll)
Cut Length:	100mm/4" or 6 LEDs
PCB Width:	12mm (IP68 - 15mm)
IP Rating:	IP20 Standard / IP68
Life Span:	>50,000 hours



126 WWW.COLORBEAMLIGHTING.COM

DESCRIPTION

- Fully dimmable and color controllable
- Double sided 3m tape backing
- Low power consumption
- Low heat emission
- Available in IP20 or IP68
- Easy to install

TYPICAL APPLICATIONS

- Accent lighting
- Decorative lighting
- Architectural lighting



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



RGBW

RGBW



3 Year Limited
Warranty

PRODUCT CODES

MODEL	DESCRIPTION
TAPE-60-RGB27K*	Tape 60 LED/M, RGB 2700K, 14.4W
TAPE-60-RGB27K-IP68	Tape 60 LED/M, RGB 2700K, 14.4W
TAPE-60-RGB30K*	Tape 60 LED/M, RGB 3000K, 14.4W
TAPE-60-RGB30K-IP68	Tape 60 LED/M, RGB 3000K, 14.4W
TAPE-60-RGB33K	Tape 60 LED/M, RGB 3300K, 14.4W
TAPE-60-RGB33K-IP68	Tape 60 LED/M, RGB 3300K, 14.4W
TAPE-60-RGB50K	Tape 60 LED/M, RGB 4500K, 14.4W
TAPE-60-RGB50K-IP68	Tape 60 LED/M, RGB 5000K, 14.4W

COMPATIBLE TRACKS/TRIMLESS TRACKS

TRACK-OP-002



TRACK-OP-004



TRACK-OP-006



TRACK-OP-008




TRACK-OP-010



TRACK-OP-011



TRACK-OP-013



TRACK-OP-014



TRACK-OP-035



TRACK-OP-036



TRACK-OP-039-TL



TRACK-OP-040-TL



TRACK-OP-055-TL



TRACK-OP-056-TL




TRACK-OP-079-TL



*For a dot-less result use one of these recommended track diffuser combinations.

**Tapes with IP68 fit in tracks with an inner width of 12.4mm or more.

MOUNTING OPTIONS





TAPE 60 WHITE / 16.4FT Roll



FEATURES

Power Rating per meter/3.3FT:	14.4W, 24V, 0.6A
LED Quantity:	60 LED/M
Luminous Flux per meter/3.3FT:	1200 - 1440 Lm
Color/CCT:	2700K 3000K 3500K 5000K
Chip:	EPISTAR
CRI:	Ra+95
Beam Angle:	120°
Max Run Length:	5 meters (16.4FT/Roll)
Cut Length:	100mm/4" or 6 LEDs
PCB Width:	10mm (IP68 - 12mm)
IP Rating:	IP20 Standard / IP68
Life Span:	>50,000 hours



128 WWW.COLORBEAMLIGHTING.COM

DESCRIPTION

- Fully dimmable
- Double sided 3m tape backing
- Low power consumption
- Low heat emission
- Available in IP20 or IP68
- Easy to install

TYPICAL APPLICATIONS

- Accent lighting
- Decorative lighting
- Architectural lighting




Dimmable Lighting
0 to 100% flicker free dimming



3 Year Limited
Warranty




COLOR TEMPERATURE



PRODUCT CODES

MODEL	DESCRIPTION
TAPE-60-W27K*	Tape 60 LED/M, 2700K, 14.4W/M
TAPE-60-W30K	Tape 60 LED/M, 3000K, 14.4W/M
TAPE-60-W35K	Tape 60 LED/M, 3500K, 14.4W/M
TAPE-60-W35K-IP68	Tape 60 LED/M, 3500K, 14.4W/M
TAPE-60-W50K	Tape 60 LED/M, 5000K, 14.4W/M



COMPATIBLE TRACKS/TRIMLESS TRACKS

TRACK-OP-002	TRACK-OP-004	TRACK-OP-006
TRACK-OP-008	TRACK-OP-010	TRACK-OP-011
TRACK-OP-013	TRACK-OP-014	TRACK-OP-035
TRACK-OP-036	TRACK-OP-039-TL	TRACK-OP-040-TL
TRACK-OP-055-TL	TRACK-OP-056-TL	TRACK-OP-079-TL

**For a dot-less result use one of these recommended track diffuser combinations.*


***Tapes with IP68 fit in tracks with an inner width of 12.4mm or more.*

MOUNTING OPTIONS

Ceiling	Recessed	Pendant	Wall
✓	✓		



TAPE 120 WHITE / 16.4FT Roll



FEATURES

Power Rating per meter/3.3FT:	9.6W, 24V, 0.4A
LED Quantity:	120 LED/M
Luminous Flux per meter/3.3FT:	840 - 960 lm/M
Color/CCT:	2700K
Chip:	EPISTAR
CRI:	Ra+95
Beam Angle:	120°
Max Run Length:	5 meters (16.4FT/Roll)
Cut Length:	50mm/2" or 6 LEDs
PCB Width:	8mm
IP Rating:	IP20 Standard
Life Span:	>50,000 hours

DESCRIPTION

- Fully dimmable
- Double sided 3m tape backing
- Low power consumption
- Low heat emission
- Available in IP20 or IP68
- Easy to install

TYPICAL APPLICATIONS

- Accent lighting
- Decorative lighting
- Architectural lighting



Dimmable Lighting
0 to 100% flicker free dimming



3 Year Limited
Warranty



COLOR TEMPERATURE



2700K

PRODUCT CODES

MODEL	DESCRIPTION
TAPE-120-W27K *	Tape 120 LED/M, 2700K, 9.6W/M



COMPATIBLE TRACKS/TRIMLESS TRACKS

TRACK-OP-002



TRACK-OP-004



TRACK-OP-006



TRACK-OP-008




TRACK-OP-010



TRACK-OP-011



TRACK-OP-013



TRACK-OP-014



TRACK-OP-035



TRACK-OP-036



TRACK-OP-039-TL



TRACK-OP-040-TL



TRACK-OP-055-TL



TRACK-OP-056-TL



TRACK-OP-076-TL



TRACK-OP-077-TL




TRACK-OP-078-TL



TRACK-OP-079-TL



MOUNTING OPTIONS





TAPE 144-UHP / 16.4FT Roll



FEATURES

Power Rating per meter/3.3FT:	20.6W, 24V, 0.86A
LED Quantity:	144 LED/M
Luminous Flux per meter/3.3FT:	2800 Lm/M
Color/CCT:	2400K 2700K 3000K 3300K 4500K
Chip:	EPISTAR
CRI:	Ra+95
Beam Angle:	120°
Max Run Length:	5 meters (16.4FT/Roll)
Cut Length:	41mm/1.63" or 6 LEDs
PCB Width:	10mm (IP 68 - 12.2mm)
IP Rating:	IP20 Standard / IP68
Life Span:	>50,000 hours



132 WWW.COLORBEAMLIGHTING.COM

DESCRIPTION

- Fully dimmable
- Double sided 3m tape backing
- Low power consumption
- Low heat emission
- Available in IP20 or IP68
- Easy to install

TYPICAL APPLICATIONS

- Accent lighting
- Decorative lighting
- Architectural lighting



Dimmable Lighting
0 to 100% flicker free dimming



Ultra High Power



3 Year Limited
Warranty


PRODUCT CODES

MODEL	DESCRIPTION
TAPE-144-W24K-UHP	Tape 144 LED/M, 2400K, 27W/M
TAPE-144-W27K-UHP*	Tape 144 LED/M, 2700K, 27W/M
TAPE-144-W30K-UHP	Tape 144 LED/M, 3000K, 27W/M
TAPE-144-W33K-UHP	Tape 144 LED/M, 3300K, 27W/M
TAPE-144-W33K-UHP-IP68	Tape 144 LED/M, 3300K, 27W/M
TAPE-144-W45K-UHP	Tape 144 LED/M, 4500K, 27W/M




COMPATIBLE TRACKS/TRIMLESS TRACKS

TRACK-OP-002



TRACK-OP-004



TRACK-OP-006



TRACK-OP-008




TRACK-OP-010



TRACK-OP-011



TRACK-OP-013



TRACK-OP-014



TRACK-OP-035



TRACK-OP-036



TRACK-OP-039-TL



TRACK-OP-040-TL



TRACK-OP-055-TL



TRACK-OP-056-TL



TRACK-OP-076-TL



TRACK-OP-077-TL



TRACK-OP-078-TL




TRACK-OP-079-TL



MOUNTING OPTIONS

Ceiling



Recessed



Pendant




Wall





TAPE 120 BI-WHITE TUNABLE / 16.4FT Roll



FEATURES

Power Rating per meter/3.3FT:	15.8W, 24V, 0.66A
LED Quantity:	120 LED/M
Luminous Flux per meter/3.3FT:	840 - 960 Lm/M
Color/CCT:	2700K - 6500K
Chip:	EPISTAR
CRI:	Ra+95
Beam Angle:	120°
Max Run Length:	5 meters (16.4FT/Roll)
Cut Length:	50mm/2" or 6 LEDs
PCB Width:	10mm (IP68 - 12.1mm)
IP Rating:	IP20 Standard / IP68
Life Span:	>50,000 hours

PRODUCT CODES

MODEL	DESCRIPTION
TAPE-120-BI	Tape 120 LED/M, 2700-6500K, 15.8W/M, 95+, 840-960Lm/M, 5M (16.4FT/Roll), 10mm, 24V, IP20
TAPE-120-BI-IP68	Tape 120 LED/M, 2700-6500K, 15.8W/M, 95+, 840-960Lm/M, 5M (16.4FT/Roll), 12.1mm, 24V, IP68

DESCRIPTION

- Fully dimmable & tunable
- Double sided 3m tape backing
- Low power consumption
- Low heat emission
- Available in IP20 or IP68
- Easy to install

TYPICAL APPLICATIONS

- Accent lighting
- Decorative lighting
- Architectural lighting



Dimmable Lighting
0 to 100% flicker free dimming




Tunable Lighting



2700K 6500K



3 Year Limited
Warranty



COMPATIBLE TRACKS/TRIMLESS TRACKS

TRACK-OP-002	TRACK-OP-004	TRACK-OP-006
TRACK-OP-008	TRACK-OP-010	TRACK-OP-011
TRACK-OP-013	TRACK-OP-014	TRACK-OP-035
TRACK-OP-036	TRACK-OP-039-TL	TRACK-OP-040-TL
TRACK-OP-055-TL	TRACK-OP-056-TL	TRACK-OP-076-TL
TRACK-OP-077-TL	TRACK-OP-078-TL	TRACK-OP-079-TL

MOUNTING OPTIONS


Ceiling	Recessed	Pendant	Wall
✓	✓		



TAPE 256 BI-WHITE TUNABLE / 16.4FT Roll



TAPE-256-BI*



FEATURES

Power Rating per meter/3.3FT:	14.4W, 24V, 0.6A
LED Quantity:	256 LED/M
Luminous Flux per meter/3.3FT:	1034 Lm/M
Color/CCT:	2700K - 6500K
Chip:	EPISTAR
CRI:	Ra+95
Beam Angle:	120°
Max Run Length:	5 meters (16.4FT/Roll)
Cut Length:	62mm/2.5" or 16 LEDs
PCB Width:	41mm
IP Rating:	IP20 Standard / IP68
Life Span:	>50,000 hours

PRODUCT CODES

MODEL	DESCRIPTION
TAPE-256-BI	Tape 256 LED/M, 2700K - 6500K, 20W/M, 95+, 1034Lm/M, 5M (16.4FT/Roll), Dimmable, 24V, Compatible with Track-051

DESCRIPTION

- Fully dimmable & tunable
- Double sided 3m tape backing
- Low power consumption
- Low heat emission
- Available in IP20 or IP68
- Easy to install

TYPICAL APPLICATIONS

- Accent lighting
- Decorative lighting
- Architectural lighting


DL Dimmable Lighting
0 to 100% flicker free dimming

TL Tunable Lighting

CRI 95⁺

2700K 6500K


3 Year Limited
Warranty






COMPATIBLE TRACKS/TRIMLESS TRACKS

TRACK-OP-051




TRACK-OP-058-TL



**For a dot-less result use one of these recommended track diffuser combinations.*

MOUNTING OPTIONS



GIULIA – Lighting Cove Drywall

GIULIA is a discreet LED tape channel ideal for wall wash as well as ceiling and pathway illumination. The Giulia's light source is powered by Colorbeam tape light.



LED LUMINAIRE



LED WHITE /2700-6500K



LED RGB-WHITE



LED RGB



Dimmable Lighting



Tunable Lighting



RGB Lighting





US LISTED







GIULIA / Recessed Wall Wash Kit



The GIULIA track is recessed in the ceiling or in-wall, based on the application requirements.



PRODUCT CODES

MODEL	DESCRIPTION
GIULIA-TAPE-120-BI	Giulia Kit LED Fixture, Tape 120 LED, 2700-6500K, 9.6W/M, IP20
GIULIA-TAPE-120-W30K	Giulia Kit LED Fixture, Tape 120 LED, 2700K, 9.6W/M, IP20
GIULIA-TAPE-60-W30K	Giulia Kit LED Fixture, Tape 60LED, 2700K, 14.4W/M, IP20
RGB WHITE	
GIULIA-TAPE-60-RGB30K	Giulia Kit, LED Fixture, Tape 60 LED, RGB 3000K, 12W/M, IP20

DESCRIPTION

GIULIA is a very discreet LED tape channel ideal for uniform illumination of ceiling and wall wash.

CHARACTERISTICS

- Plaster-in LED tape channel, requires a minimum 5/8" thick drywall and 36" distance for best wall wash coverage and effect.
- Available at any custom length up to 20"/6m.
- Made of aluminum
- Perfect for any flexible LED tape up to 12mm wide.
- Available in white. Other colors upon request



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



RGB


1800K 6500K



RGB



5 Year Limited Warranty





COMPATIBLE LED TAPES

SINGLE COLOR

TAPE-60-W30K



TAPE-120-W30K



TAPE-120-BI





RGB-WHITE


TAPE-60-RGB30K



TRACK LENGTH OPTIONS




MOUNTING OPTIONS



COLORBEAM | PRODUCT PORTFOLIO 141

TRACKS & DIFFUSERS

Tracks, Covers, End Caps, and Clips







TRACK-OP-002



SLIM ALUMINUM PROFILE



ACCESSORIES/END CAPS & CLIPS



DESCRIPTION

- **Material:** anodized aluminum 6063
- **Width of suitable LED tape:** Max 12mm
- **Installation of cover:** Press into profile
- **Profile length options:** 1M and 2M
- **Cover material:** PMMA, PC
- Opal cover


TYPICAL APPLICATIONS

- Cove lighting
- Under cabinet
- Toe kick
- Recessed in wall and in ceiling


PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-002-1M	Slim Aluminum Profile with Opal Diffuser Cover (OP-002) - 1M
2 Meter	
TRACK-OP-002-2M	Slim Aluminum Profile with Opal Diffuser Cover (OP-002) - 2M
Accessories	
TR-ENDCAPS-002	End Caps 002 (2 Pack)
TR-CLIPS-002	Clips 002 (2 Pack)

TRACK DIMENSIONS




INSTALLATION DIAGRAM






TRACK-OP-004-RD



SLIM ALUMINUM PROFILE



ACCESSORIES/END CAPS & CLIPS



DESCRIPTION

- **Material:** anodized aluminum 6063
- **Width of suitable LED tape:** Max 12mm
- **Installation of cover:** Press into profile
- **Profile length:** 1M and 2M
- **Cover material:** PMMA, PC
- Opal cover


TYPICAL APPLICATIONS

- Cove lighting
- Under cabinet
- Toe kick
- Recessed in wall and in ceiling


PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-004-1M-RD	Slim Aluminum Profile with Opal Diffuser Cover (OP-004-RD) ~ 1M
2 Meter	
TRACK-OP-004-2M-RD	Slim Aluminum Profile with Opal Diffuser Cover (OP-004-RD) ~ 2M
Accessories	
TR-ENDCAPS-004-RD	End Caps 004-RD (2 Pack)
TR-CLIPS-004-RD	Clips 004-RD (2 Pack)

TRACK DIMENSIONS



INSTALLATION DIAGRAM






TRACK-OP-004



SLIM ALUMINUM PROFILE



ACCESSORIES/END CAPS & CLIPS



DESCRIPTION

- **Material:** anodized aluminum 6063
- **Width of suitable LED tape:** Max 12mm
- **Installation of cover:** Press into profile
- **Profile length:** 1M and 2M
- **Cover material:** PMMA, PC
- Opal cover


TYPICAL APPLICATIONS

- Cove lighting
- Under cabinet
- Toe kick
- Recessed in wall and in ceiling


PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-004-1M	Slim Aluminum Profile with Opal Diffuser Cover (OP-004) - 1M
2 Meter	
TRACK-OP-004-2M	Slim Aluminum Profile with Opal Diffuser Cover (OP-004) - 2M
Accessories	
TR-ENDCAPS-004	End Caps 004 (2 Pack)
TR-CLIPS-004	Clips 004 (2 Pack)

TRACK DIMENSIONS



INSTALLATION DIAGRAM





TRACK-OP-006



SLIM ALUMINUM PROFILE



ACCESSORIES/END CAPS & CLIPS



DESCRIPTION

- **Material:** anodized aluminum 6063
- **Width of suitable LED tape:** Max 10mm
- **Installation of cover:** Press into profile
- **Profile length:** 1M and 2M
- **Cover material:** PMMA, PC
- Opal cover


TYPICAL APPLICATIONS

- Cove lighting
- Under cabinet
- Toe kick
- Recessed in wall and in ceiling


PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-006-1M	Slim Aluminum Profile with Opal Diffuser Cover (OP-006) - 1M
2 Meter	
TRACK-OP-006-2M	Slim Aluminum Profile with Opal Diffuser Cover (OP-006) - 2M
Accessories	
TR-ENDCAPS-006	End Caps 006 (2 Pack)
TR-CLIPS-006	Clips 006 (2 Pack)

TRACK DIMENSIONS



INSTALLATION DIAGRAM





TRACK-OP-008



SLIM ALUMINUM PROFILE



ACCESSORIES/END CAPS, ROPE & BRACKETS



DESCRIPTION

- **Material:** anodized aluminum 6063
- **Width of suitable LED tape:** Max 12mm
- **Installation of cover:** Press into profile
- **Profile length:** 1M and 2M
- **Cover material:** PMMA, PC
- Opal cover


TYPICAL APPLICATIONS

- Cove lighting
- Under cabinet
- Toe kick
- Recessed in wall and in ceiling


PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-008-1M	Slim Aluminum Profile with Opal Diffuser Cover (OP-008) - 1M
2 Meter	
TRACK-OP-008-2M	Slim Aluminum Profile with Opal Diffuser Cover (OP-008) - 2M
Accessories	
TR-ENDCAPS-008	End Caps 008 (2 Pack)
TR-ROPE-008	ROPE 008 (2 Pack)
TR-BRACKETS-008	Clips 008 (2 Pack)

TRACK DIMENSIONS



INSTALLATION DIAGRAM





TRACK-OP-010



SLIM ALUMINUM PROFILE



ACCESSORIES/END CAPS



DESCRIPTION

- **Material:** anodized aluminum 6063
- **Width of suitable LED tape:** Max 16mm
- **Installation of cover:** Press into profile
- **Profile length:** 1M and 2M
- **Cover material:** PMMA, PC
- Opal cover


TYPICAL APPLICATIONS

- Cove lighting
- Under cabinet
- Toe kick
- Recessed in wall and in ceiling


PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-010-1M	Slim Aluminum Profile with Opal Diffuser Cover (OP-010) - 1M
2 Meter	
TRACK-OP-010-2M	Slim Aluminum Profile with Opal Diffuser Cover (OP-010) - 2M
Accessories	
TR-ENDCAPS-010	End Caps 010 (2 Pack)

TRACK DIMENSIONS



INSTALLATION DIAGRAM





TRACK-OP-011



SLIM ALUMINUM PROFILE



ACCESSORIES/END CAPS



DESCRIPTION

- **Material:** anodized aluminum 6063
- **Width of suitable LED tape:** Max 16mm
- **Installation of cover:** Press into profile
- **Profile length:** 1M and 2M
- **Cover material:** PMMA, PC
- Opal cover


TYPICAL APPLICATIONS

- Cove lighting
- Under cabinet
- Toe kick
- Recessed in wall and in ceiling


PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-011-1M	Slim Aluminum Profile with Opal Diffuser Cover (OP-011) - 1M
2 Meter	
TRACK-OP-011-2M	Slim Aluminum Profile with Opal Diffuser Cover (OP-011) - 2M
Accessories	
TR-ENDCAPS-011	End Caps 011 (2 Pack)

TRACK DIMENSIONS



INSTALLATION DIAGRAM





TRACK-OP-035



SLIM ALUMINUM PROFILE



ACCESSORIES/END CAPS & CLIPS



DESCRIPTION

- **Material:** anodized aluminum 6063
- **Width of suitable LED tape:** Max 16mm
- **Installation of cover:** Press into profile
- **Profile length:** 1M and 2M
- **Cover material:** PMMA, PC
- Opal cover


TYPICAL APPLICATIONS

- Cove lighting
- Under cabinet
- Toe kick
- Recessed in wall and in ceiling


PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-035-1M	Slim Aluminum Profile with Opal Diffuser Cover (OP-035) - 1M
2 Meter	
TRACK-OP-035-2M	Slim Aluminum Profile with Opal Diffuser Cover (OP-035) - 2M
Accessories	
TR-ENDCAPS-035	End Caps 035 (2 Pack)
TR-CLIPS-035	Clips 035 (2 Pack)

TRACK DIMENSIONS



INSTALLATION DIAGRAM





TRACK-OP-036



SLIM ALUMINUM PROFILE



ACCESSORIES/END CAPS & CLIPS



DESCRIPTION

- **Material:** anodized aluminum 6063
- **Width of suitable LED tape:** Max 16mm
- **Installation of cover:** Press into profile
- **Profile length:** 1M and 2M
- **Cover material:** PMMA, PC
- Opal cover


TYPICAL APPLICATIONS

- Cove lighting
- Under cabinet
- Toe kick
- Recessed in wall and in ceiling


PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-036-1M	Slim Aluminum Profile with Opal Diffuser Cover (OP-036) - 1M
2 Meter	
TRACK-OP-036-2M	Slim Aluminum Profile with Opal Diffuser Cover (OP-036) - 2M
Accessories	
TR-ENDCAPS-036	End Caps 036 (2 Pack)
TR-CLIPS-036	Clips 036 (2 Pack)

TRACK DIMENSIONS



INSTALLATION DIAGRAM





TRACK-OP-013



SLIM ALUMINUM PROFILE



ACCESSORIES/END CAPS & CLIPS



DESCRIPTION

- **Material:** anodized aluminum 6063
- **Width of suitable strip light:** Max 20mm
- **Installation of cover:** Press into profile
- **Profile length:** 1M and 2M
- **Cover material:** PMMA, PC
- Opal cover


TYPICAL APPLICATIONS

- Cove lighting
- Under cabinet
- Toe kick
- Recessed in wall and in ceiling


PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-013-1M	Slim Aluminum Profile with Opal Diffuser Cover (OP-013) - 1M
2 Meter	
TRACK-OP-013-2M	Slim Aluminum Profile with Opal Diffuser Cover (OP-013) - 2M
Accessories	
TR-ENDCAPS-013	End Caps 013 (2 Pack)
TR-CLIPS-013	Clips 013 (2 Pack)

TRACK DIMENSIONS



INSTALLATION DIAGRAM





TRACK-OP-014



SLIM ALUMINUM PROFILE



ACCESSORIES/END CAPS & CLIPS



DESCRIPTION

- **Material:** anodized aluminum 6063
- **Width of suitable LED tape:** Max 20mm
- **Installation of cover:** Press into profile
- **Profile length:** 1M and 2M
- **Cover material:** PMMA, PC
- Opal cover


TYPICAL APPLICATIONS

- Cove lighting
- Under cabinet
- Toe kick
- Recessed in wall and in ceiling


PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-014-1M	Slim Aluminum Profile with Opal Diffuser Cover (OP-014) - 1M
2 Meter	
TRACK-OP-014-2M	Slim Aluminum Profile with Opal Diffuser Cover (OP-014) - 2M
Accessories	
TR-ENDCAPS-014	End Caps 014 (2 Pack)
TR-CLIPS-014	Clips 014 (2 Pack)

TRACK DIMENSIONS



INSTALLATION DIAGRAM





TRACK-OP-028



SLIM ALUMINUM PROFILE



ACCESSORIES/END CAPS & ROPE



DESCRIPTION

- **Material:** anodized aluminum 6063
- **Compatible LED tape:** Max 35mm
- **Installation of cover:** Press into profile
- **Profile length:** 1M and 2M
- **Cover material:** PMMA, PC
- Opal cover


TYPICAL APPLICATIONS

- Cove lighting
- Suspended lighting
- Toe kick
- Recessed in wall and in ceiling


PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-028-1M	Slim Aluminum Profile with Opal Diffuser Cover (OP-028) - 1M
2 Meter	
TRACK-OP-028-2M	Slim Aluminum Profile with Opal Diffuser Cover (OP-028) - 2M
Accessories	
TR-ENDCAPS-028	End Caps 028 (2 Pack)
TR-ROPE-028	Rope 028 (2 Pack)

TRACK DIMENSIONS



INSTALLATION DIAGRAM





TRACK-OP-017



SLIM ALUMINUM PROFILE



ACCESSORIES/END CAPS & CLIPS



DESCRIPTION

- **Material:** anodized aluminum 6063
- **Width of suitable LED tape:** Max 31mm
- **Installation of cover:** Press into profile
- **Profile length:** 1M and 2M
- **Cover material:** PMMA, PC
- Opal cover


TYPICAL APPLICATIONS

- Cove lighting
- Architectural lighting
- Toe kick
- Recessed in wall and in ceiling


PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-017-1M	Slim Aluminum Profile with Opal Diffuser Cover (OP-017) - 1M
2 Meter	
TRACK-OP-017-2M	Slim Aluminum Profile with Opal Diffuser Cover (OP-017) - 2M
Accessories	
TR-ENDCAPS-017	End Caps 017 (2 Pack)
TR-CLIPS-017	Clips 017 (2 Pack)

TRACK DIMENSIONS



INSTALLATION DIAGRAM





TRACK-OP-051



SLIM ALUMINUM PROFILE



ACCESSORIES/END CAPS & Rope



DESCRIPTION

- **Material:** anodized aluminum 6063
- **Width of suitable LED tape:** Max 40mm
- **Installation of cover:** Press into profile
- **Profile length:** 1M and 2M
- **Cover material:** PMMA, PC
- Opal cover


TYPICAL APPLICATIONS

- Cove lighting
- Suspended lighting
- Toe kick
- Recessed in wall and in ceiling


PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-051-1M	Slim Aluminum Profile with Opal Diffuser Cover (OP-051) - 1M
2 Meter	
TRACK-OP-051-2M	Slim Aluminum Profile with Opal Diffuser Cover (OP-051) - 2M
Accessories	
TR-ENDCAPS-051	End Caps 051 (2 Pack)
TR-ROPE-051	Rope 051 (2 Pack)


TRACK DIMENSIONS



INSTALLATION DIAGRAM



158



TRIMLESS TRACKS

Tracks, Covers & End Caps



TRACK-OP-038-TL / Trimless



TRIMLESS ALUMINUM PROFILE

ACCESSORIES




End cap



Connector



Cover




DESCRIPTION

- **Material:** aluminum 6063 + PC/PMMA
- **Lighting source width:** 31mm
- **Profile length:** 1M and 2M
- **Installation:** Trimless recessed in drywall
- **Cover material:** PMMA, PC
- Opal cover


PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-038-1M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-038) - 1M
2 Meter	
TRACK-OP-038-2M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-038) - 2M
Accessories	
TR-ENDCAPS-038	End Caps 038 (2 Pack)
TR-TL-CNR-038	Connectors 038 (2 Pack)

TRACK DIMENSIONS



INSTALLATION DIAGRAM





TRACK-OP-039-TL / Trimless



TRIMLESS ALUMINUM PROFILE

ACCESSORIES



End cap



Aluminum Profile



Cover


DESCRIPTION

- **Material:** aluminum 6063 + PC/PMMA
- **Lighting source width:** 12mm
- **Profile length:** 1M and 2M
- **Installation:** Trimless recessed in drywall
- **Cover material:** PMMA, PC
- Opal cover


PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-039-1M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-039) - 1M
2 Meter	
TRACK-OP-039-2M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-039) - 2M
Accessories	
TR-ENDCAPS-039	End Caps 039 (2 Pack)

TRACK DIMENSIONS



INSTALLATION DIAGRAM





TRACK-OP-040-TL / Trimless



TRIMLESS ALUMINUM PROFILE

ACCESSORIES



End cap



Aluminum Profile



Cover


DESCRIPTION

- **Material:** aluminum 6063 + PC/PMMA
- **Lighting source width:** 12mm
- **Profile length:** 1M and 2M
- **Installation:** Trimless recessed in drywall
- **Cover material:** PMMA, PC
- Opal cover



PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-040-1M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-040) ~ 1M
2 Meter	
TRACK-OP-040-2M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-040) ~ 2M
Accessories	
TR-ENDCAPS-014	End Caps 014 (2 Pack)

TRACK DIMENSIONS



INSTALLATION DIAGRAM





TRACK-OP-055-TL / Trimless



TRIMLESS ALUMINUM PROFILE

ACCESSORIES



End cap



Aluminum Profile



Cover


DESCRIPTION

- **Material:** aluminum 6063 + PC/PMMA
- **Lighting source width:** 14mm
- **Profile length:** 1M and 2M
- **Installation:** Trimless recessed in drywall
- **Cover material:** PMMA, PC
- Opal cover


PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-055-1M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-055) - 1M
2 Meter	
TRACK-OP-055-2M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-055) - 2M
Accessories	
TR-ENDCAPS-055	End Caps 055 (2 Pack)

TRACK DIMENSIONS



INSTALLATION DIAGRAM





TRACK-OP-056-TL / Trimless



TRIMLESS ALUMINUM PROFILE

ACCESSORIES



End cap



Aluminum Profile



Cover


DESCRIPTION

- **Material:** aluminum 6063 + PC/PMMA
- **Lighting source width:** 25mm
- **Profile length:** 1M and 2M
- **Installation:** Trimless recessed in drywall
- **Cover material:** PMMA, PC
- Opal cover



PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-056-1M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-056) - 1M
2 Meter	
TRACK-OP-056-2M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-056) - 2M
Accessories	
TR-ENDCAPS-056	End Caps 014 (2 Pack)

TRACK DIMENSIONS




INSTALLATION DIAGRAM





TRACK-OP-057-TL / Trimless



TRIMLESS ALUMINUM PROFILE

ACCESSORIES



End cap



Aluminum Profile



Cover




DESCRIPTION

- **Material:** aluminum 6063 + PC/PMMA
- **Lighting source width:** 39mm
- **Profile length:** 1M and 2M
- **Installation:** Trimless recessed in drywall
- **Cover material:** PMMA, PC
- Opal cover


PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-057-1M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-057) - 1M
2 Meter	
TRACK-OP-057-2M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-057) - 2M
Accessories	
TR-ENDCAPS-057	End Caps 057 (2 Pack)

TRACK DIMENSIONS




INSTALLATION DIAGRAM





TRACK-OP-058-TL / Trimless



TRIMLESS ALUMINUM PROFILE

ACCESSORIES



End cap



Aluminum Profile



Cover




DESCRIPTION

- **Material:** aluminum 6063 + PC/PMMA
- **Lighting source width:** 54mm
- **Profile length:** 1M and 2M
- **Installation:** Trimless recessed in drywall
- **Cover material:** PMMA, PC
- Opal cover


PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-058-1M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-058) - 1M
2 Meter	
TRACK-OP-058-2M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-058) - 2M
Accessories	
TR-ENDCAPS-058	End Caps 058 (2 Pack)

TRACK DIMENSIONS



INSTALLATION DIAGRAM





TRACK-OP-076-TL / Trimless



TRIMLESS ALUMINUM PROFILE

ACCESSORIES



End Cap



Aluminum Profile



Alu Profile (Back)



Cover




DESCRIPTION

- **Material:** aluminum 6063 + PC/PMMA
- **Lighting source width:** 8mm
- **Profile length:** 1M and 2M
- **Installation:** Trimless recessed in drywall
- **Cover material:** PMMA, PC
- Opal cover


PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-076-1M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-076) - 1M
2 Meter	
TRACK-OP-076-2M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-076) - 2M
Accessories	
TR-ENDCAPS-076	End Caps 076 (2 Pack)

TRACK DIMENSIONS



INSTALLATION DIAGRAM





TRACK-OP-077-TL / Trimless



TRIMLESS ALUMINUM PROFILE

ACCESSORIES



End Cap



Aluminum Profile



Alu Profile (Back)



Cover


DESCRIPTION

- **Material:** aluminum 6063 + PC/PMMA
- **Lighting source width:** Max 8mm
- **Profile length:** 1M and 2M
- **Installation:** Trimless recessed in drywall
- **Cover material:** PMMA, PC
- Opal cover


PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-077-1M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-077) - 1M
2 Meter	
TRACK-OP-077-2M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-077) - 2M
Accessories	
TR-ENDCAPS-077	End Caps 077 (2 Pack)

TRACK DIMENSIONS



INSTALLATION DIAGRAM





TRACK-OP-078-TL / Trimless



TRIMLESS ALUMINUM PROFILE

ACCESSORIES



End Cap



Aluminum Profile



Alu Profile (Back)



Cover


DESCRIPTION

- **Material:** aluminum 6063 + PC/PMMA
- **Lighting source width:** Max 8mm
- **Profile length:** 1M and 2M
- **Installation:** Trimless recessed in drywall
- **Cover material:** PMMA , PC
- Opal cover


PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-078-1M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-078) - 1M
2 Meter	
TRACK-OP-078-2M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-078) - 2M
Accessories	
TR-ENDCAPS-078	End Caps 078 (2 Pack)

TRACK DIMENSIONS



INSTALLATION DIAGRAM





TRACK-OP-079-TL / Trimless



TRIMLESS ALUMINUM PROFILE

ACCESSORIES



End Cap



Aluminum Profile



Alu Profile (Back)



Cover




DESCRIPTION

- **Material:** aluminum 6063 + PC/PMMA
- **Lighting source width:** Max 18mm
- **Profile length:** 1M and 2M
- **Installation:** Trimless recessed in drywall
- **Cover material:** PMMA, PC
- Opal cover


PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-079-1M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-079) - 1M
2 Meter	
TRACK-OP-079-2M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-079) - 2M
Accessories	
TR-ENDCAPS-079	End Caps 079 (2 Pack)

TRACK DIMENSIONS



INSTALLATION DIAGRAM





TRACK-OP-080-TL / Trimless



TRIMLESS ALUMINUM PROFILE

ACCESSORIES



End Cap



Aluminum Profile



Alu Profile (Back)



Cover


DESCRIPTION

- **Material:** aluminum 6063 + PC/PMMA
- **Lighting source width:** Max 28mm
- **Profile length:** 1M and 2M
- **Installation:** Trimless recessed in drywall
- **Cover material:** PMMA, PC
- Opal cover



PRODUCT CODES

MODEL	DESCRIPTION
1 Meter	
TRACK-OP-080-1M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-080) - 1M
2 Meter	
TRACK-OP-080-2M-TL	Trimless Aluminum Profile with Opal Diffuser Cover (OP-080) - 2M
Accessories	
TR-ENDCAPS-080	End Caps 080 (2 Pack)

TRACK DIMENSIONS




INSTALLATION DIAGRAM






Outdoor & Land



scape Lighting



FL SERIES – Flood Lights Tunable /White/ RGBW

FL Series offers high lumen output while reducing energy consumption. Our selection of flood lights are ideal for landscape lighting, small driveways as well as other indoor and outdoor applications.



Dimmable Lighting



Tunable Lighting



RGBW Lighting



175





FL1-SERIES-WHITE / Flood Lights



FL1-W50K-25D



FL1-W27K-25D

DESCRIPTION

- Built with 18 high powered LEDs
- A light, compact and heat dissipating aluminum extrusion design
- High quality waterproof design and construction
- Condensation valve regulates internal housing temperature
- Modular LED board design offers quick and easy maintenance



Dimmable Lighting
0 to 100% flicker free dimming

5000K

4600 Lm

2700K

4200 Lm



Waterproof
IP67




3 Year Limited
Warranty

FEATURES

Wattage:	50 Watts
Color Temperature:	Cool White/5000K - 4600 Lm Warm White/2700K - 4200 Lm
Beam Angle:	25°, 40° and 60°
Work Temperature:	-10°C ~ 40°C
Lamp Life:	> 50,000 hours
Compatible Driver:	SR-2108A-M5-5
Housing Material:	Premium Grade Aluminum, Weatherproof PC (UV-resistant)

DIMENSIONS



OUTDOOR LIGHTING



PRODUCT CODES

MODEL	DESCRIPTION
FL1-W50K-25D	Floodlight 24V, 50W, White, 5000K, 25D, IP67
FL1-W50K-40D	Floodlight 24V, 50W, White, 5000K, 40D, IP67
FL1-W50K-60D	Floodlight 24V, 50W, White, 5000K, 60D, IP67
FL1-W27K-25D	Floodlight 24V, 50W, Warm White, 2700K, 25D, IP67
FL1-W27K-40D	Floodlight 24V, 50W, Warm White, 2700K, 40D, IP67
FL1-W27K-60D	Floodlight 24V, 50W, Warm White, 2700K, 60D, IP67



FL2-SERIES-WHITE / Flood Lights



FL2-W50K-25D



FL2-W27K-25D

DESCRIPTION

- Built with 36 high powered LEDs
- A light, compact and heat dissipating aluminum extrusion design
- High quality waterproof design and construction
- Condensation valve regulates internal housing temperature
- Modular LED board design offers quick and easy maintenance



Dimmable Lighting
0 to 100% flicker free dimming

5000K

9200 Lm

2700K

8400 Lm



Waterproof
IP67



3 Year Limited
Warranty


FEATURES

Wattage:	100 Watts
Color Temperature:	Cool White/5000K - 9200 Lm Warm White/2700K - 8400 Lm
Beam Angle:	25°, 40° and 60°
Work Temperature:	-10°C ~ 40°C
Lamp Life:	> 50,000 hours
Compatible Driver:	SR-2108A-M5-5
Housing Material:	Premium Grade Aluminum, Weatherproof PC (UV-resistant)

PRODUCT CODES

MODEL	DESCRIPTION
FL2-W50K-25D	Floodlight 24V, 100W, White, 5000K, 25D, IP67
FL2-W50K-40D	Floodlight 24V, 100W, White, 5000K, 40D, IP67
FL2-W50K-60D	Floodlight 24V, 100W, White, 5000K, 60D, IP67
FL2-W27K-25D	Floodlight 24V, 100W, WARM White, 2700K, 25D, IP67
FL2-W27K-40D	Floodlight 24V, 100W, WARM White, 2700K, 40D, IP67
FL2-W27K-60D	Floodlight 24V, 100W, WARM White, 2700K, 60D, IP67

DIMENSIONS



OUTDOOR LIGHTING





FL1-SERIES-RGBW / Flood Lights



FL1-W50K-25D



FL1-W27-25D

DESCRIPTION

- Built with 6 high powered LEDs
- The RGBW 4 color process delivers smooth and saturated colors for all applications
- A light, compact and heat dissipating aluminum extrusion design
- High quality waterproof design and construction
- Condensation valve regulates internal housing temperature



Dimmable Lighting
0 to 100% flicker free dimming



RGB WHITE

RGB

1750 Lm



Waterproof
IP67



3 Year Limited
Warranty


FEATURES

Wattage:	50 Watts
Color Temperature:	RGBW
Beam Angle:	30°, 50° and 70°
Work Temperature:	-10°C ~ 40°C
Lamp Life:	> 50,000 hours
Compatible Driver:	SR-2108A-M5-5
Housing Material:	Premium Grade Aluminum, Weatherproof PC (UV-resistant)

PRODUCT CODES

MODEL	DESCRIPTION
FL1-RGB60K-30D	Floodlight 24V, 50W, RGB 6000K, 30D, IP67
FL1-RGB60K-50D	Floodlight 24V, 50W, RGB 6000K, 50D, IP67
FL1-RGB60K-70D	Floodlight 24V, 50W, RGB 6000K, 70D, IP67

DIMENSIONS



OUTDOOR LIGHTING





FL2-SERIES-RGBW / Flood Lights



FL2-W50K-25D



FL2-W27-25D

DESCRIPTION

- Built with 12 high powered LEDs
- The RGBW 4 color process delivers smooth and saturated colors for all applications
- A light, compact and heat dissipating aluminum extrusion design
- High quality waterproof design and construction
- Condensation valve regulates internal housing temperature



Dimmable Lighting
0 to 100% flicker free dimming



RGB WHITE

RGB

3500 Lm



Waterproof
IP67




3 Year Limited
Warranty

FEATURES

Wattage:	100 Watts
Color Temperature:	RGBW
Beam Angle:	30°, 50° and 70°
Work Temperature:	-10°C ~ 40°C
Lamp Life:	> 50,000 hours
Compatible Driver:	SR-2108A-M5-5
Housing Material:	Premium Grade Aluminum, Weatherproof PC (UV-resistant)

DIMENSIONS



PRODUCT CODES

MODEL	DESCRIPTION
FL2-RGB60K-30D	Floodlight 24V, 100W, RGB 6000K, 30D, IP67
FL2-RGB60K-50D	Floodlight 24V, 100W, RGB 6000K, 50D, IP67
FL2-RGB60K-70D	Floodlight 24V, 100W, RGB 6000K, 70D, IP67

OUTDOOR LIGHTING



LLS SERIES RGB/RGBW – Linear light bars

These high-lumen output linear bars are for indoor and outdoor wall-wash as well as accent lighting applications; available in 1, 2, 3 and 4 foot lengths.



Dimmable Lighting



Tunable Lighting



RGBW Lighting



US LISTED







LLS SERIES RGB – Indoor/Outdoor



DIMENSIONS

MODEL	INSTALLATION	DIMENSIONS	
LL1 (300mm) 15W			Weight 625 g
LL2 (600mm) 30W			Weight 1150 g
LL3 (900mm) 45W			Weight 1600 g
LL4 (1200mm) 60W			Weight 2100 g

FEATURES

SPECIFICATIONS								
MODEL	Power Consumption	Power Requirement	Color Temp	Luminous Flux (lm)	Efficiency (lm/W)	LEDs	IP Rating	Beam Angle
LLS-1F	15W	12VDC 1.25A	R:620nm G:520nm B:460nm	R:154 G:252 B:63 ALL 469	31	Prolight 3535 LED Rx3/Gx3/Bx3	IP 67	25° 40° 60°
LLS-2F	30W	12VDC 2.25A	R:620nm G:520nm B:460nm	R:308 G:504 B:126 ALL 938	31	Prolight 3535 LED Rx6/Gx6/Bx6	IP 67	25° 40° 60°
LLS-3F	45W	12VDC 3.75A	R:620nm G:520nm B:460nm	R:462 G:756 B:189 ALL 1407	31	Prolight 3535 LED Rx9/Gx9/Bx9	IP 67	25° 40° 60°
LLS-4F	60W	12VDC 5A	R:620nm G:520nm B:460nm	R:616 G:1008 B:252 ALL 1876	31	Prolight 3535 LED Rx12/Gx12 /Bx12	IP 67	25° 40° 60°
		24VDC 2.5A						25° 40° 60°


DESCRIPTION

- The RGB 3 colors deliver smooth and saturated color renderings for all applications
- A light, compact and heat dissipating aluminum extrusion design
- High Quality waterproof design and construction
- Modular LED board design offers quick and easy maintenance



Dimmable Lighting
0 to 100% flicker free dimming

RGB



Waterproof
IP67



3 Year Limited
Warranty

PRODUCT CODES

MODEL	DESCRIPTION
2 Feet	
LLS-2F-RGB-25D	Wall Washer 24V, 30W, RGB 25D, 2 FEET, IP67
LLS-2F-RGB-40D	Wall Washer 24V, 30W, RGB 40D, 2 FEET, IP67
LLS-2F-RGB-60D	Wall Washer 24V, 30W, RGB 60D, 2 FEET, IP67
4 Feet	
LL-4F-W50K-25D	Wall Washer 24V, 60W, RGB 25D, 4 FEET, IP67
LL-4F-W27K-25D	Wall Washer 24V, 60W, RGB 40D, 4 FEET, IP67
LL-4F-W50K-40D	Wall Washer 24V, 60W, RGB 60D, 4 FEET, IP67





LLS SERIES RGB WHITE - Indoor/Outdoor



DIMENSIONS

MODEL	INSTALLATION	DIMENSIONS	
LL1 (300mm) 15W			Weight 625 g
LL2 (600mm) 30W			Weight 1150 g
LL3 (900mm) 45W			Weight 1600 g
LL4 (1200mm) 60W			Weight 2100 g

FEATURES

SPECIFICATIONS								
MODEL	Power Consumption	Power Requirement	Color Temp	Luminous Flux (lm)	Efficiency (lm/W)	LEDs	IP Rating	Beam Angle
LLS-1F	15W	12VDC 1.25A	R:620nm G:520nm B:460nm	R154 G:252 B:63 ALL 469	31	Prolight 3535 LED Rx3/Gx3/Bx3	IP 67	25° 40° 60°
LLS-2F	30W	12VDC 2.25A	R:620nm G:520nm B:460nm	R:308 G:504 B:126 ALL 938	31	Prolight 3535 LED Rx6/Gx6/Bx6	IP 67	25° 40° 60°
LLS-3F	45W	12VDC 3.75A	R:620nm G:520nm B:460nm	R:462 G:756 B:189 ALL 1407	31	Prolight 3535 LED Rx9/Gx9/Bx9	IP 67	25° 40° 60°
LLS-4F	60W	12VDC 5A	R:620nm G:520nm B:460nm	R:616 G:1008 B:252 ALL 1876	31	Prolight 3535 LED Rx12/Gx12 /Bx12	IP 67	25° 40° 60°
		24VDC 2.5A						25° 40° 60°

DESCRIPTION

- The RGB 4 colors deliver smooth and saturated color renderings for all applications
- A light, compact and heat dissipating aluminum extrusion design
- High Quality waterproof design and construction
- Modular LED board design offers quick and easy maintenance



Dimmable Lighting
0 to 100% flicker free dimming

5000K



2700K



RGB WHITE


RGB



Waterproof
IP67



3 Year Limited
Warranty



PRODUCT CODES

MODEL	DESCRIPTION
2 Feet	
LLS-2F-RGB50K-25D	Wall Washer 24V, 30W, RGB 5000K, 25D, 2 FEET, IP67
LLS-2F-RGB27K-25D	Wall Washer 24V, 30W, RGB 2700K, 25D, 2 FEET, IP67
LLS-2F-RGB50K-40D	Wall Washer 24V, 30W, RGB 5000K, 40D, 2 FEET, IP67
LLS-2F-RGB27K-40D	Wall Washer 24V, 30W, RGB 2700K, 40D, 2 FEET, IP67
LLS-2F-RGB50K-60D	Wall Washer 24V, 30W, RGB 5000K, 60D, 2 FEET, IP67
LLS-2F-RGB27K-60D	Wall Washer 24V, 30W, RGB 2700K, 60D, 2 FEET, IP67
4 Feet	
LLS-4F-RGB50K-25D	Wall Washer 24V, 60W, RGB 5000K, 25D, 4 FEET, IP67
LLS-4F-RGB27K-25D	Wall Washer 24V, 60W, RGB 2700K, 25D, 4 FEET, IP67
LLS-4F-RGB50K-40D	Wall Washer 24V, 60W, RGB 5000K, 40D, 4 FEET, IP67
LLS-4F-RGB27K-40D	Wall Washer 24V, 60W, RGB 2700K, 40D, 4 FEET, IP67
LLS-4F-RGB50K-60D	Wall Washer 24V, 60W, RGB 5000K, 60D, 4 FEET, IP67
LLS-4F-RGB27K-60D	Wall Washer 24V, 60W, RGB 2700K, 60D, 4 FEET, IP67



TEGA SERIES – Spot Lights and Up Lights

Tunable /White/ RGB/ RGBW

Create impactful accent lighting by illuminate small trees, bushes and pathways in outdoor and landscape lighting applications.



Dimmable Lighting



Tunable Lighting



RGB Lighting





TEGA-IN-1-WHITE 2W



TEGA-IN-1-W30K-2W-30D



TEGA-IN-1-W40K-2W-30D

DESCRIPTION

TEGA-IN is an in-ground surface white light, LED luminaire that can also be used for downlighting. Used for wet locations such as: landscaping and architectural accent lighting, showers, saunas and spas.

Dimmable Lighting
0 to 100% flicker free dimming

4000K

3000K

Waterproof
IP67

3 Year Limited
Warranty


FEATURES

Wattage:	2 Watts
Color Temperature:	3000K
Lumens:	176 lm
Optic:	30° 45° Asymmetrical
Voltage:	24 VDC
Lamp Life:	> 50,000 hours
Fixation:	Spring clips for recessed use PVC leeve base for landscape use.
Application:	In ground, wall, ceiling and floor

PRODUCT CODES

MODEL	DESCRIPTION
TEGA-IN-1-W30K-2W-30D	Outdoor Round LED Fixture 3000K, 30D, 2W, 24V, 5.5CM, IP67
TEGA-IN-1-W30K-2W-AS	Outdoor Round LED Fixture 3000K, Asymmetrical, 2W, 24V, 5.5CM, IP67

OPTIC OPTIONS



RESIDENTIAL LIGHTING





TEGA-IN-1-RGB-3W



TEGA-IN-1-W30K-2W-30D



TEGA-IN-1-W40K-2W-30D

FEATURES

Wattage:	3 Watts
Color Temperature:	RGB
Lumens:	85 lm
Optic:	30° 45° Asymmetrical
Voltage:	24 VDC
Lamp Life:	> 50,000 hours
Fixation:	Spring clips for recessed use PVC leeve base for landscape use.
Application:	In ground, wall, ceiling and floor

PRODUCT CODES

MODEL	DESCRIPTION
TEGA-IN-1-RGB-3W-30D	Outdoor Round LED Fixture 3000K, 30D, 2W, 24V, 5.5CM, IP67
TEGA-IN-1-RGB-3W-AS	Outdoor Round LED Fixture 3000K, Asymmetrical, 2W, 24V, 5.5CM, IP67

DESCRIPTION

TEGA-IN is an in-ground surface RGB light, LED luminaire that can also be used for downlighting. Used in wet locations such as: landscaping and architectural accent lighting, showers, saunas and spas.



Dimmable Lighting

0 to 100% flicker free dimming



Tunable Lighting



RGB

4000K


5000K

RGB


Waterproof
IP673 Year Limited
Warranty

OPTIC OPTIONS

30°



45° Asymmetrical



RESIDENTIAL LIGHTING





TEGA-IN-1-RGBW-4W-30D



TEGA-IN-1-RGBW-4W-30D



DESCRIPTION

TEGA-IN is an in-ground surface RGBW light, LED luminaire that can also be used for downlighting. Used in wet locations such as: landscaping and architectural accent lighting, showers, saunas and spas.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



RGB

RGBW



Waterproof
IP67




3 Year Limited
Warranty

FEATURES

Wattage:	4 Watts
Color Temperature:	RGB+4000K
Optic:	30°
Voltage:	24 VDC
Lamp Life:	> 50,000 hours
Fixation:	Spring clips for recessed use PVC leeve base for landscape use.
Application:	In ground, wall, ceiling and floor

OPTIC OPTION



RESIDENTIAL LIGHTING



PRODUCT CODE

MODEL	DESCRIPTION
TEGA-IN-1-RGBW-4W-30D	Outdoor Round LED Fixture, RGBW, 4W, 30D, 24V, 5.5CM, IP67





TEGA-IN-9W



TEGA-IN-RGB-9W



TEGA-IN-WHITE-9W



DESCRIPTION

TEGA-IN is an in-ground surface LED luminaire. Used in wet locations such as: showers, saunas and spas as well as landscape and pathway lighting.



DL Dimmable Lighting
0 to 100% flicker free dimming



TL Tunable Lighting



RGB RGB



Waterproof
IP67



3 Year Limited
Warranty


FEATURES

Wattage:	9 Watts	
Color Temperature:	4000K	RGB
Lumens:	479 lm	290 lm
Optic:	30° or 45° Asymmetrical	
Voltage:	24 VDC	
Lamp Life:	> 50,000 hours	
Fixation:	Spring clips for recessed use PVC leeve base for landscape use.	
Application:	In ground, wall, ceiling and floor	


PRODUCT CODES

MODEL	DESCRIPTION
TEGA-IN-W40K-9W-30D	Outdoor In-ground Round LED Fixture, 4000K, 9W, 30D, 24V, 11CM, IP67
TEGA-IN-W40K-9W-AS	Outdoor In-ground Round LED Fixture, 4000K, 9W, Asym, 24V, 11CM, IP67
TEGA-IN-RGB-9W-30D	Outdoor In-ground Round LED Fixture, RGB, 9W, 30D, 24V, 11CM, IP67
TEGA-IN-RGB-9W-AS	Outdoor In-ground Round LED Fixture, RGB, 9W, Asym, 24V, 11CM, IP67

OPTIC OPTIONS



RESIDENTIAL LIGHTING





TEGA-IN-RGBW-12W



TEGA-IN-RGBW-12W-30D



TEGA-IN-RGBW-12W-45D



DESCRIPTION

TEGA-IN is an in-ground surface LED luminaire. Used in wet locations such as: showers, saunas and spas as well as landscape and pathway lighting.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



RGB



Waterproof
IP67




3 Year Limited
Warranty

FEATURES

Wattage:	12 Watts
Color Temperature:	RGB + 3000K
Optic:	30° 45°
Voltage:	24 VDC
Lamp Life:	> 50,000 hours
Fixation:	Spring clips for recessed use PVC leeve base for landscape use.
Application:	In ground, wall, ceiling and floor

OPTIC OPTIONS



RESIDENTIAL LIGHTING



PRODUCT CODES

MODEL	DESCRIPTION
TEGA-IN-RGBW-12W-30D	Outdoor In-ground Round LED Fixture RGBW, 12W, 30D, 24V, 12CM, IP67
TEGA-IN-RGBW-12W-45D	Outdoor In-ground Round LED Fixture RGBW, 12W, 45D, 24V, 12CM, IP67

194





TEGA-SP-3W / Tunable Projector



TEGA-SP-W30K-3W-SV

TEGA-SP-W40K-3W-SV



FEATURES

Wattage:	1 x 3 Watts for monochrome color
Light color:	3000K Warm white 4000K White
CRI:	> 80
Optic:	30°
Voltage:	24 VDC standard, 12VDC optional
Lamp Life:	> 50,000 hours
IP:	IP65
Fixation:	Round base 65 mm standard fixation for electrical box. Canopy 100mm as an option
Diffuser:	Tempered glass T:3 mm
Working Temperature:	-30 ±55°C

PRODUCT CODES

MODEL	DESCRIPTION	COLOR
TEGA-SP-W30K-3W-SV	Outdoor Silver Round LED Fixture, 3000K, 3W, 24V, IP65	
TEGA-SP-W40K-3W-SV	Outdoor Silver Round LED Fixture, 4000K, 3W, 24V, IP65	
TEGA-SP-W40K-3W-BK	Outdoor Black Round LED Fixture, 4000K, 3W, 24V, IP65	
TEGA-SP-W30K-3W-BK	Outdoor Black Round LED Fixture, 3000K, 3W, 24V, IP65	

DESCRIPTION

The TEGA-SP is a LED projector with spikes and transparent glass diffuser. The light source is a high powered LED 3W adjustable projector, ideal for garden lighting to enhance decorative elements.



Dimmable Lighting

0 to 100% flicker free dimming



Tunable Lighting




Waterproof
IP65




3 Year Limited
Warranty

OPTIC OPTIONS



LANDSCAPE LIGHTING



196





TEGA-SP-RGB-3W / RGB Projector



TEGA-SP-W30K-3W-SV

TEGA-SP-W40K-3W-SV



DESCRIPTION

The TEGA-SP is a LED projector with spikes and transparent glass diffuser. The light source is a high powered RGB LED 3W adjustable projector, ideal for garden lighting to enhance decorative elements.



Dimmable Lighting

0 to 100% flicker free dimming




RGB

Waterproof
IP653 Year Limited
Warranty

FEATURES

Wattage:	1 x 3 Watts for monochrome color
Light color:	RGB, controller need
CRI:	> 80
Optic:	30°
Voltage:	24 VDC standard, 12VDC optional
Lamp Life:	> 50,000 hours
IP:	IP65
Fixation:	Round base 65 mm Standard Fixation for electrical box: Canopy 100mm as an option
Diffuser:	Tempered glass T:3 mm
Working Temperature:	-30 ±55°C

OPTIC OPTIONS



LANDSCAPE LIGHTING



PRODUCT CODES

MODEL	DESCRIPTION	COLOR
TEGA-SP-RGB-3W-SV	Outdoor Silver Round LED Fixture, RGB, 3W, 24V, IP65	
TEGA-SP-RGB-3W-BK	Outdoor Black Round LED Fixture, RGB, 3W, 24V, IP65	



TEGA-SP-RGBW-5W / RGB Projector



TEGA-SP-RGBW-5W-SV

TEGA-SP-RGBW-5W-BK



DESCRIPTION

The TEGA-SP is a LED projector with spikes and transparent glass diffuser. The light source is a high powered RGBW LED 5W adjustable projector, ideal for garden lighting to enhance decorative elements.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



RGBW

4000K 5000K



RGB



Waterproof
IP65




3 Year Limited
Warranty


FEATURES

Wattage:	5W
Light color:	RGB / White
CRI:	> 80
Optic:	30°
Voltage:	24 VDC standard, 12VDC optional
Lamp Life:	> 50,000 hours
IP:	IP65
Fixation:	Round base 65 mm Standard Fixation for electrical box: Canopy 100mm as an option
Diffuser:	Tempered glass T:3 mm
Working Temperature:	-30 ±55°C

OPTIC OPTION



LANDSCAPE LIGHTING



PRODUCT CODES

MODEL	DESCRIPTION	COLOR
TEGA-SP-RGBW-5W-SV	Outdoor Silver Round LED Fixture, RGB, 5W, 24V, IP65	
TEGA-SP-RGBW-5W-BK	Outdoor Black Round LED Fixture, RGB, 5W, 24V, IP65	



TEGA ACCESSORIES

PRODUCT CODES

MODEL	DESCRIPTION	COLOR
TEGA-STAKE-SV	Plastic Stake For Up Lighting - Silver	
TEGA-BASE-SV	Plastic Circular Base For Up Lighting - Silver	
TEGA-STAKE-BK	Plastic Stake For Up lighting - Black	
TEGA-BASE-BK	Plastic Circular Base For Up Lighting - Black	




Stake



Base

200





BULLET SERIES / High Powered Spotlight



DESCRIPTION

This solid brass high performance spotlight is available in a 10W RGBW and 17W BI-White model. Adjustable/tilt options, this high lumen output outdoor fixture is used for just about all landscape lighting applications.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



RGBW

4000K

5000K

RGBW



Waterproof
IP65




3 Year Limited
Warranty

FEATURES

Wattage:	14W / RGBW	10W / White
Color Temperature:	RGB - 2700K	2700K - 6500K
Total Luminous Flux:	543 lm	444 lm
Beam Angle:	40D	
Voltage:	36V	
Working Temperature:	-30 ±45°C	
IP Grade:	IP65	
Weig:	1.82 Kg	
Housing material	Solid brass	
Life Span	50,000 Hours	

LIGHT ANGLE FROM -50°~90°



LANDSCAPE LIGHTING



COLORBEAM | PRODUCT PORTFOLIO 201

PRODUCT CODES

MODEL	DESCRIPTION
BULLET-BI-10W	Outdoor spotlight CCT Tunable, Adjustable, 24V, 10W, IP65
BULLET-RGB27W-14W	Outdoor spotlight RGB 2700K, Adjustable, 24V, 14W, IP65
BLT-STAKE-UP	Copper Brass Stake For Up Lighting
BLT-TREE-MOUNT	Copper Tree Mount For Lighting

TEGA- DR SERIES

Inground Tunable/White/RGB/RGBW

TEGA-DR is available in a variety of options that illuminate driveways, pathways, patios and docks.



Dimmable Lighting



Tunable Lighting



RGBW Lighting





TEGA-DR SERIES / 1 Side




HIGHLIGHTS

- DL** Dimmable Lighting
0 to 100% flicker free dimming
- TL** Tunable Lighting
3000K 4000K
2 Watts
- RGB** RGB
3 Watts
- RGBW** RGBW
RGB - White
4 Watts
- IP67** Waterproof IP67
- 3 YEAR WARRANTY** 3 Year Limited Warranty


FEATURES

Wattage:	2W White / 3000K - 4000K
	3W RGB
	4W RGB White
Light color:	Tunable White, RGB and RGBW
CRI:	> 80
Optic:	1 Side 60°
Voltage:	24 VDC standard, 12VDC optional
Lamp Life:	> 50,000 hours
IP:	IP67
Luminaire Material:	Housing: Aluminum.
	Front Cover: #316 stainless steel
Working Temperature:	-20 ±40°C

DIMENSIONS



INGROUND LIGHTING



PRODUCT CODES

MODEL	DESCRIPTION
TEGA-DR-W30K-2W-60-1S	Outdoor LED Fixture White 3000K, 60D, 2W, 24V, IP67, One sided
TEGA-DR-W40K-2W-60-1S	Outdoor LED Fixture White 4000K, 60D, 2W, 24V, IP67, One sided
TEGA-DR-RGB-3W-60-1S	Outdoor LED Fixture, RGB, 60D, 3W, 24V, IP67, One sided
TEGA-DR-RGBW-4W-60-1S	Outdoor LED Fixture, RGB White, 60D, 4W, 24V, IP67, One sided



TEGA-DR SERIES / 2 Sides



HIGHLIGHTS



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting 3000K 4000K
2 Watts



RGB RGB
3 Watts



RGBW RGBW
4 Watts



Waterproof
IP67




3 Year Limited
Warranty

FEATURES

Wattage:	2W White / 3000K - 4000K
	3W RGB
	4W RGB White
Light color:	Tunable White, RGB and RGBW
CRI:	> 80
Optic:	2 Sides 60°
Voltage:	24 VDC standard, 12VDC optional
Lamp Life:	> 50,000 hours
IP:	IP67
Luminaire Material:	Housing: Aluminum.
	Front Cover: #316 stainless steel
Working Temperature:	-20 ±40°C

DIMENSIONS



INGROUND LIGHTING



PRODUCT CODES

MODEL	DESCRIPTION
TEGA-DR-W30K-2W-60-2S	Outdoor LED Fixture White 3000K, 60D, 2W, 24V, IP67, Two sided
TEGA-DR-W40K-2W-60-2S	Outdoor LED Fixture White 4000K, 60D, 2W, 24V, IP67, Two sided
TEGA-DR-RGB-3W-60-2S	Outdoor LED Fixture, RGB, 60D, 3W, 24V, IP67, Two sided
TEGA-DR-RGBW-4W-60-2S	Outdoor LED Fixture, RGB White, 60D, 4W, 24V, IP67, Two sided



TEGA-DR SERIES / 4 Sides



HIGHLIGHTS



DL Dimmable Lighting
0 to 100% flicker free dimming



TL Tunable Lighting
3000K 4000K
2 Watts



RGB RGB
3 Watts



RGBW RGBW
RGB - White
4 Watts



Waterproof
IP67




3 Year Limited
Warranty

FEATURES

Wattage:	2W White / 3000K - 4000K
	3W RGB
	4W RGB White
Light color:	Tunable White, RGB and RGBW
CRI:	> 80
Optic:	4 Sides 60°
Voltage:	24 VDC standard, 12VDC optional
Lamp Life:	> 50,000 hours
IP:	IP67
Luminaire Material:	Housing: Aluminum.
	Front Cover: #316 stainless steel
Working Temperature:	-20 ±40°C

DIMENSIONS



INGROUND LIGHTING



206





GAIA / LED Wall Sconce



GAIA-WS-W30K-6W-SW



DESCRIPTION

The GAIA: A LED wall sconce in sand white color. This outdoor luminaire emits soft white illumination from the top and the bottom of the luminaire.



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting
3000K 4000K 6000K



Waterproof
IP54




3 Year Limited Warranty

FEATURES

Wattage:	6W
Maximum Wattage:	2 x 3W COB-Epistar
Light color:	3000K
	4000K
	6000K
Dimensions:	5.31 X 3.54 X 2.08 Inch.
CRI:	80
Voltage:	24 VDC standard, 12VDC optional
Lamp Life:	> 50,000 hours
Luminaire Material:	Finish: Sand white Material: Made of die-casting aluminum
Working Temperature:	-40 ±50°C

DIMENSIONS



WALL UP LIGHTING





MAYA / LED Wall Sconce




DESCRIPTION

MAYA-WS Wall mounted luminaire finished in sand grey coated aluminum; used in lighting front doors, fences and pathways.



Dimmable Lighting
0 to 100% flicker free dimming

4000K



3000K



Waterproof
IP54




3 Year Limited
Warranty

FEATURES

Wattage:	12W
Max Wattage:	2 x 3W COB-Epistar
Light color:	3000K
	4000K
	6000K
Dimensions:	15 cm diameter/5.90 Inch. 5 cm in height/1.96 Inch.
CRI:	80
Voltage:	24 VDC standard, cable 20 cm
Lamp Life:	> 50,000 hours
IP:	IP54
Luminaire Material:	Made of die-casting aluminum and acrylic. Finish sand grey.
Working Temperature:	-20 ±40°C

DIMENSIONS



OUTDOOR WALL LIGHTING



PRODUCT CODES

MODEL	DESCRIPTION
MAYA-WS-W30K-12W-SG	LED Wall Sconce White, Sand Grey, 3000K, 12W, 24V, IP54
MAYA-WS-W40K-12W-SG	LED Wall Sconce White, Sand Grey, 4000K, 12W, 24V, IP54
MAYA-WS-W60K-12W-SG	LED Wall Sconce, White, Sand Grey, 6000K, 12W, 24V, IP54



MAYA PT / Bollard LED Pathway



DESCRIPTION

MAYA-PT Bollard style luminaire features the MAYA-WS luminaire horizontally mounted to a vertical inground mounted pipe. Ideal for pathway illumination.



Dimmable Lighting
0 to 100% flicker free dimming

4000K



3000K



Waterproof
IP54



3 Year Limited
Warranty

FEATURES

Wattage:	12W
Application:	Outdoor garden lamp
Light color:	3000K
	4000K
	6000K
Dimensions:	15 cm diameter/5.90 Inch. 60 cm in height/ 23.62 Inch.
CRI:	80
Voltage:	24 VDC standard, cable 20 cm
Lamp Life:	> 50,000 hours
IP:	IP54
Luminaire Material:	Made of die-casting aluminum and acrylic. Finish sand grey.
Working Temperature:	-20 ±40°C

PRODUCT CODES

MODEL	DESCRIPTION
MAYA-PT-W30K-12W-SG	LED Pathway, White, Sand Grey, 3000K, 12W, 24V, IP54
MAYA-PT-W40K-12W-SG	LED Pathway, White, Sand Grey, 4000K, 12W, 24V, IP54
MAYA-PT-W60K-12W-SG	LED Pathway, White, Sand Grey, 6000K, 12W, 24V, IP54


OUTDOOR PATHWAY LIGHTING



GATEway DMX PROCESSOR

Optimize Control - Enhance Lighting





Colorbeam unveils the next generation **GATeWay**

The Colorbeam Lighting GATeWay-IDMX is a stand-alone lighting processor with an integrated real-time, configurable web software with 1 DMX output.

FEATURES:

- Built-in Web Application
- Fanless enclosure
- Reset Button
- Status LED
- 1 Ethernet port (10/100)
- 1 Independent DMX Universe
- Galvanic Isolation
- 3 year warranty

World-Class Lighting Exp




Experiences for Every Space



Colorbeam's complete lineup of indoor and outdoor lighting products enhances lifestyle, wellness and productivity in residential, commercial and hospitality sectors.

Working closely with architects, builders, designers and AV Integrators, we strive to deliver a transformation experience through lighting in every space be it residential, landscape, commercial or hospitality.



Colorbeam Lighting

450 Montée de Liesse, Montreal, QC, Canada H4T 1N8

844-301-2262 | info@colorbeamlighting.com | www.colorbeamlighting.com