

## PORTABLE ELECTRIC INDOOR FAN FORCED HEATERS



### FES SERIES HEATWAVE SALAMANDER



**NO OPEN FLAMES  
NO DEADLY FUMES TO VENT  
NO "OUT OF FUEL" SHUT-DOWNS**

Use in areas with ceiling heights less than 15'

- Safety yellow heater enclosure with safety screens on both air intake and output openings
- Optional 25' long SO type cord, ready for plug attachment is available for each model (10KW model is included)
- Long-life finned tubular heating elements
- Thermostat adjustment 40° to 100° F
- High-limit thermal cutout switch / Automatic reset
- Housing features 90° pivot a djustment from center axis, except 45KW unit
- 10" wheels and heavy-duty handle / wheel-base assembly for easy portability over all surface types
- 800 CFM: 10-15KW, 1100 CFM: 30KW; 2200 CFM: 45KW
- Shipped fully assembled
- Made in U.S.A.



FES SIZING CHART

UNIT	MAX SQ. FT.
10KW	750 up to 1000
15KW	1000 up to 1500
30 KW	1500 up to 2000
45KW	2000 up to 2400

MFG MODEL	KW	VOLTS	BTUs	PH	AMPS	CFM	TEMP RISE	WT. (LBS)	PRICE EACH	OPTIONAL 25' POWER CORD	
										MFG MODEL	PRICE EACH
FES-1024-1CA	10	240	34,130	1	42	800	30 °F	60	<b>1044.45</b>	N/A*	-
FES-1520-3A	15	208	51,195	3			45 °F	65	<b>1097.25</b>	6/4 SO	<b>205.70</b>
FES-1524-1A		240		1	63	69	4/4 SO	<b>209.00</b>			
FES-1524-3E		240		3	36	65	6/4 SO	<b>205.70</b>			
FES-1548-3E		480		3	18	65	12/4 SO	<b>99.00</b>			
FES-3048-3A	30	480	102,390	3	36	1100	45 °F	83	<b>1730.30</b>	6/4 SO	<b>205.70</b>
FES-4548-3	45	480	153,585	3	54.2	2200	70 °F	125	<b>2860.55</b>	4/4 SO	<b>209.00</b>

\*Cordset included

### 60 Kilowatt FES Model

- Safety yellow heater enclosure with safety screens on both air intake and output openings
- Optional 25' long SO type cord, ready for plug attachment is available for each model
- Long-life finned tubular heating elements
- Thermostat adjustment 40° to 110° F
- Two 10" rear wheels and front locking casters
- High-limit thermal cutout switch with manual reset
- 2500 CFM
- Fan only operation feature
- Made in U.S.A.

MFG MODEL	KW	BTUs	VOLTS	PH	AMPS	TEMP RISE	SO TYPE*	dB @ 2 FT.	WT. (LBS)	LIST	OPTIONAL 25' POWER CORD*	
											MFG MODEL	LIST
FES-6048-3	60	204780	480	3	73.5	74°F	2/4	79	225	<b>3163.00</b>	SO 4/4	<b>209.00</b>
FES-6057-3			575		60.3		4/4			<b>3370.00</b>	SO 2/4	<b>234.00</b>

\*Plug not included



Lift Assist Handles

# OCH2 SERIES OUTDOOR / INDOOR RATED QUARTZ ELECTRIC INFRARED HEATERS



**HEATS SOLID OBJECTS, NOT THE AIR!**


- 2 Frosted Quartz Tube heating elements (included)
- Listed for suspended, totally exposed (outdoor) and indoor\*\* spot heating applications (\*\*not for residential use)
- Finish: High-temp brown powder coated finish or corrosion resistant stainless steel 20 gauge housing
- 60° Symmetric Heat Pattern
- Gold anodized Aluminum reflector and end caps
- 6" long lead wires for direct field connection
- Two 2' ft. long mounting chains and four S-Hooks included
- The OCH2-Series can be wall or ceiling mounted using the supplied mounting brackets which allow up to a 45° horizontal tilt adjustment
- Made in U.S.A.

Series: OCH2-55 OCH2-66  
 Dimensions: Length: 66"; Width: 7.5"; Height: 7"  
 Length: 66"; Width: 7.5"; Height: 7"

Product Models												
MFG CATALOG NUMBER	PAINTED BROWN		LIST	MFG CATALOG NUMBER	STAINLESS STEEL		LIST	WATTS	BTUs	VOLTS	AMPS	Qtz. Tube Repl. Element
	MFG MODEL NUMBER				MFG MODEL NUMBER							
04915502	OCH2-55-208V		279.40	04915902	OCH2-55-208V-SS		342.65	4000	13652	208	19.23	671-5062
04915602	OCH2-55-240V			04916002	OCH2-55-240V-SS							671-5063
04915702	OCH2-55-277V			04916102	OCH2-55-277V-SS							671-5064
04915802	*OCH2-55-480V			04916202	*OCH2-55-480V-SS							*671-5063
04916302	OCH2-66-208V		309.65	04916702	OCH2-66-208V-SS		359.15	6000	20478	208	28.85	671-5065
04916402	OCH2-66-240V			04916802	OCH2-66-240V-SS							671-5066
04916502	OCH2-66-277V			04916902	OCH2-66-277V-SS							671-5067
04916602	*OCH2-66-480V			04917002	*OCH2-66-480V-SS							*671-5066

\*480V models use (2) 240V elements wired in series.

Product Accessories				
MFG CATALOG NUMBER	MFG MODEL NUMBER	DESCRIPTION	FOR USE WITH	LIST
04917102	OCH2/WG-55	Wire Guards	OCH2-55 Series Models	45.10
04917202	OCH2/WG-66		OCH2-66 Series Models	54.45




# FSP SERIES PORTABLE FLAT PANEL EMITTER ELECTRIC INFRARED HEATERS



FSP-95      FSP-43      FSP-31      FSP-14

- High density medium wave radiant heat with 60° symmetrical heat pattern
- Electrical enclosure included for direct wire installation
- 25,000 hour element life expectancy
- Approximately 78.5% efficient versus 50% for metal sheath type elements
- Rugged flat panel emitter can be used in high vibration areas
- FSP-14/31 include heavy duty steel (12ga.) 12"x12" base; FSP-43/95 include (2) 6" diameter wheel portable cart base powder coated black
- Heavy duty wire guard mounted on long lasting gold anodized reflector
- Shipped fully assembled
- Made in U.S.A.




MFG MODEL	WATTS	VOLTS	PHASE	BTUs / HOUR	AMPS		WT. (LBS)	PRICE EACH
					1 PH	3 PH		
FSP-1412-1C	1450	120	1	4,947	12.1	N/A	17	629.75
FSP-3124-1	3150	240		10,749	13.13	23	739.20	
FSP-4324-3	4300	240	1 or 3	14,972	17.91	10.36	32	950.40
FSP-4348-3		480			8.96	5.18		
FSP-9524-3	9500	240			39.68	22.89	46	1317.25
FSP-9548-3	9500	480			19.79	11.44		



# FSS SERIES OVERHEAD FLAT PANEL EMITTER ELECTRIC INFRARED HEATERS



MFG MODEL	WATTS	VOLTS	PHASE	BTUs / HOUR	AMPS		WT. (LBS)	PRICE EACH		
					1 PH	3 PH				
FSS-4320-3	4300	208	1 or 3	14,672	20.67	11.94	18	809.60		
FSS-4324-3		240			17.91	10.36				
FSS-4348-3		480			8.96	5.18				
FSS-9520-3	9500	208			1 or 3	32,414	45.67	26.39	31	1194.60
FSS-9524-3		240					39.6	22.89		
FSS-9548-3		480					19.8	11.44		



## 5100 SERIES FAN FORCED SUSPENDED ELECTRIC UNIT HEATERS



### Horizontal or Vertical Discharge Airflow

- Heavy gauge welded steel cabinet with powder-coated finish and control compartment housing a master terminal board with a hinged and latched access door, simplifying wiring, installation and maintenance
- Copper clad steel sheath element with continuously brazed steel fins formed to allow side draw through airflow
- Units equipped with automatic resetting type limit control.
- Adjustable louvers for directional air flow control
- Units with model numbers ending in CA are factory wired for low voltage controls
- Shipped fully assembled
- Made in U.S.A.

MFG MODEL	KW	VOLTS	PHASE	AMPS	CONTROL VOLTAGE	PRICE EACH
HF2B5105N	5	240	1 / 3	20.8 / 18.1	240	<b>503.80</b>
	3.7	208		12.1 / 10.4	208	
HF2B5107CA1L	7.5	240		27.1 / 31.3	24	<b>776.05</b>
	5.6	208		31.3 / 27.1		
HF2B5110CA1L	10	240		41.2 / 24.0		<b>855.25</b>
	7.5	208		36.1 / 20.8		
P3P5105CA1N	5	480	3	6.1		<b>666.60</b>
P3P5107CA1N	7.5			9.1		<b>837.10</b>
P3P5110CA1N	10			12.1	<b>886.80</b>	

### HEATER ACCESSORIES:

MFG MODEL	DESCRIPTION	MODEL SIZE / TYPE	WT. (LBS)	PRICE EACH
A5105	Mounting Brackets	3.3 KW to 5.0 KW	9	<b>73.15</b>
A5120		7.5 KW to 20.0 KW	13	<b>84.15</b>
T5100	Field Installed	SPST Line Voltage (Built-In) Stat		<b>87.45</b>
T5102	Thermostat	DPST Line Voltage (Built-In) Stat		<b>118.25</b>



## 3310 SERIES FAN FORCED WALL HEATER



- White powder coated 18-gauge steel front grill with rounded corners
- Steel block element design
- Built-in double pole thermostat, temperature range of 50°F - 90°F
- Automatic reset thermal limit
- Quiet, but proves a high 175 CFM output of down flow air
- Covers room size of 75-275 square foot
- Optional surface mounting frame & extenders available
- Made in U.S.A.

*Designed for spot, supplement, and even primary comfort heating systems.*



*Units are ideal for small, hard to heat areas; such as vestibule areas, bathrooms, hallways, offices, hotels, stairways, and many more!*

MFG MODEL	WATTS	VOLTS	BTUs	AMPS	GRILL	ROUGH-IN	WT. (LBS)	PRICE EACH
E3313T2RPW	1500 / 750	120	5120 / 2560	12.5 / 6.25	15 3/4" Wide 20 3/4" High (18-gauge)	14 3/4" Wide 19 3/4" High 4" Deep	22	<b>327.25</b>
HF3315T2RPW	3000 / 2250 1500 / 1125	240 / 208	10240 / 5120	12.5 / 6.2 6.2 / 5.4				<b>331.65</b>
HF3316T2RPW	4000 / 3000 2000 / 1500		13648 / 6826	16.8 / 14.4 8.3 / 7.2				<b>332.20</b>



## 3200 SERIES FAN FORCED WALL HEATER

- White powder coated 18-gauge steel front grill with rounded corners
- Finned tubular steel element design
- Built-in double pole thermostat, temperature range of 40°F - 100°F
- Standard manual reset thermal limit
- Approved for horizontal mounting to allow right or left discharge
- Quiet, but provides 70 CFM (2200 RPM) output of flow air
- Optional surface mounting frame & extenders available
- Made in U.S.A.



**COMPACT DESIGN**  
*(With Thermostat)*

MFG MODEL	WATTS	VOLTS	BTUs	AMPS	PRICE EACH
E3215TRPW	1500	120	5120	12.5	<b>160.05</b>
HF3215T2RPW	1500 / 1125	240/208	5120 / 3840	6.3 / 5.4	<b>169.95</b>
HF3222T2RPW	2250 / 1688		7680 / 5762	9.4 / 8.1	

## 680 SERIES "BULLDOG" 240/208 VOLT FAN FORCED PORTABLE UNIT HEATER



- Operates on 240V or 208V electrical service
- Finned steel tubular heating element
- Internal manual reset thermal cut-out
- 6' long cord with molded plug
- Temperature control thermostat with 60°F to 110°F range
- 10' air throw - 262 CFM
- Width: 13 1/2", Height: 17 1/2", Depth: 11 1/2"
- Imported to TPI Corporation specifications



30 AMP Plug  
NEMA #6-30P

Swivel base allows unit to be wall, floor, or ceiling mounted.



MFG MODEL	WATTS	BTUs	VOLTS	PHASE	AMPS	TEMP RISE	WT. (LBS)	PRICE EACH
HF686TC	5600 / 4200	19107 / 14330	240 / 208	1	23.4 / 20.2	75°F	20	<b>302.50</b>

## 5800 SERIES FAN FORCED GARAGE / SHOP HEATER

- Up to 4800 Watts of heating comfort for garage or utility room applications
- 4000 Watts available for smaller areas
- Built in bi-metal double pole thermostat: 50°F - 90°F range.
- 6' long cord with molded plug
- Steel tubular heating element
- Wall/Ceiling bracket included
- Manual reset standard
- Power on and overheat pilot lights
- Imported to TPI Corporation specifications

### DIMENSIONS

Heater: 10 3/4" x 11" x 9 3/4"  
Bracket: 2 1/2" x 10" x 14"

MFG MODEL	WATTS	MAX BTUs	VOLTS	AMPS	WT. (LBS)	PRICE EACH
HF5840TC	4000/3000	13652	240 / 208	16.6 / 14.4	17	<b>153.45</b>
HF5848TC	4800/3600	15086		20 / 17.3		<b>205.15</b>



HF584TC  
20 AMP Plug  
NEMA #6-20P



HF5848TC  
30 AMP Plug  
NEMA #6-30P



Adjustable thermostat on back

## 120V PORTABLE ELECTRIC HEATERS



188 TASA  
**\$60.50**



178 TMC  
**\$63.80**



198 TMC  
**\$101.75**

- Agency approved for indoor residential, commercial & industrial areas
- All steel construction with powder coated finish
- 120-Volt, single phase operation; ready for pull-in operation
- Cord set; black 16/3 SJT, 6' long with NEMA 5-15 grounded plug

MFG MODEL	WATTS	MAX BTUs	VOLTS	AMPS	# HEAT SETTINGS	AGENCY LISTING	WEIGHT (LBS)
188-TASA	1500 / 1300	5,120	120	12.5	2	ETL CAJ5	9
178-TMC	1500 / 950					UL CAJ5	8
198-TMC	1500 / 900 / 750					ETL CAJ5	9

Ui Supplies | 855-326-8958  
www.uisupplies.com  
website@uisupplies.com