

THE FUTURE OF LIGHTING



PRODUCT LOOKBOOK CEDIA EDITION




CONTENTS

INDOOR LIGHTING



LINEAR LIGHTING



OUTDOOR LIGHTING



POWER & CONTROL




THE RIGHT LIGHT FOR ALL OCCASIONS


Colorbeam Lighting delivers revolutionary low voltage lighting solutions which create immersive and controllable lighting experiences for residential, commercial and hospitality spaces.

Colorbeam's innovative low voltage technology is changing how we think about lighting. The GATEway processor enables users to customize their environment with tunable light for ultimate control over the lighting experience.

The result is an immersive experience that engages the senses and enhances the quality of life.



The New HEKA LED Chip



Tunable Range from: 2200K-5000K



RGBW



HEKA LED CHIP SERIES

Colorbeam Lighting introduces a new line of **BI-White and RGBW LED chips**. The HEKA LED chips are engineered to be the next advancement in Human-Centric Lighting. These energizing and productivity-enhancing LED light sources can deliver warmer, more comfortable light.

The HEKA chips bridge the gap between warm CCTs and high MRs for healthy and relaxed environments. The chips contain an improved melonopic spectral content of 680nm with exceptional red-rendering, ideal for enriching natural skin tones.

Colorbeam continues to further wellness applications in the lighting category with the **HEKA LED Chip Series**.

FEATURES

- Compatible with any Colorbeam light engine
- Tunable Range: 2200K-5000K and RGBW



INDOOR LIGHTING

Colorbeam's luminaires offer true tunability which delivers any warm or cool setting at any dim level for unmatched flexibility. Ranging from 1800K to 6500K + RGBW, any mood or task setting is a button press away.

When your lighting needs are as diverse as the day itself, Colorbeam offers endless possibilities.

Colorbeam offers recessed, surface mount and decorative lighting options.



Dimmable Lighting
0 to 100% flicker-free dimming



Tunable Lighting



RGBW Lighting



5 Year
Limited Warranty



CRI 95⁺

BIANCA 16W

TUNABLE & CIRCADIAN LIGHTING

LED COLOR TECHNOLOGY OPTIONS

1800K to 4000K

2200K to 5000K

2700K to 6500K

FEATURES

Wattage:	16 Watts (two channels)
LED CRI:	>95Ra
Lumens Range:	1200 Lm - 1400Lm
Input Voltage:	48 Volts RJ45
Compatible Decoder:	For dimming use DMX-SR2112
IP Grade:	IP20 Standard
Warranty:	50,000 Hours 5 Years

STANDARDS



CRI 95+

TRIM FINISH

Matte White

Matte Black

BEAM ANGLE



20 Degrees



40 Degrees



www.colorbeamlighting.com

BIANCA 16W-SERIES

TRIM OPTIONS



BIANCA-16W-BI-SQ

Square Airtight Trim



BIANCA-16W-BI-RD

Round Airtight Trim

WALL WASH TRIM DOWNLIGHT



BIANCA-16W-BI-RDR

Wall Wash Trim



APERTURE

Ø 3.25" / Ø 82.55mm



BIANCA 14W

TUNABLE & CIRCADIAN LIGHTING

LED COLOR TECHNOLOGY OPTIONS

1800K to 4000K

2200K to 5000K

2700K to 6500K

FEATURES

Wattage:	14 Watts (two channels)
LED CRI:	≥95Ra
Lumens Range:	700 Lm - 1020 Lm
Input Voltage:	48 Volts RJ45
Compatible Decoder:	For dimming use DMX-SR2112
IP Grade:	IP20 Standard
Warranty:	50,000 Hours 5 Years

BEAM ANGLE



20 Degrees



40 Degrees



STANDARDS



FINISH

Matte White

Matte Black

RGBW 10W

RGBW LIGHTING

LED COLOR TECHNOLOGY OPTION

RGB + 3000K

FEATURES

Wattage:	10 Watts
LED CRI:	≥95Ra (White chip only)
Lumens Range:	480 Lm - 525 Lm
Input Voltage:	48 Volts RJ45
Compatible Decoder:	For dimming use DMX-SR2112
IP Grade:	IP20 Standard
Warranty:	50,000 Hours 5 Years

BEAM ANGLE



20 Degrees



40 Degrees



STANDARDS



FINISH

Matte White

Matte Black


COMPATIBLE PRODUCT FAMILY



TB-SERIES



VB-SERIES



S-SERIES

TB SERIES


The TB Trim Series is a sleek and versatile recessed fixture that doesn't require a pre-construction can. Used in residential or commercial settings, the TB may be considered for retro and new construction applications.

ROUND TRIM MODELS

TB-150-11
Adjustable Trim



TB-150-22
Adjustable Trim



SQUARE TRIM MODELS

TB-650-11
Adjustable Trim



TB-650-22
Adjustable Trim



SHOWER TRIM MODELS

TB-100-11
Adjustable Trim



TB-700-11
Adjustable Trim



VB SERIES

Offered with an open or closed faceplate, single or double light engine configuration, trim or trimless, the VB offers an array of features that meet aesthetic and application requirements.




OPEN & CLOSED TRIM MODELS


VB1-10W/14W-11-OP
Adjustable Open Trim



TRIM SIZE
5.02" x 5.02"
127.6 x 127.6mm




VB1-10W/14W-11-CL
Adjustable Closed Trim




OPEN & CLOSED TRIMLESS MODELS


VB1-10W/14W-11-TL-OP
Adjustable Open Trimless



TRIMLESS PLATE SIZE
8" x 8"
203.2 x 203.2mm



VB1-10W/14W-11-TL-CL
Adjustable Closed Trimless



S SERIES

S Series is the perfect blend of performance, style and aesthetics. The S Series delivers ideal lighting for your home or office with round and square faceplates.

Paired with the appropriate light engine for the application, the S Series luminaire delivers a stunning look and performance.



ROUND TRIM MODELS

S-200-11-11
Round Adjustable Trim



S-300-11-11 | S-300-11-05
Round Fixed Trim




S-340-11-11 | S-340-11-05
Round Adjustable Trim



S-350-11-11
Round Fixed Trim



S-360-11-11
Round Fixed Trim



ROUND TRIMLESS MODELS

S-300-11-11-TL
Fixed Trimless



S-300-11-05-TL
Fixed Trimless



S-340-11-11-TL
Adjustable Trimless



S-340-11-05-TL
Adjustable Trimless



S-350-11-11-TL
Adjustable Trimless



S-360-11-11-TL
Adjustable Trimless



A modern living room with a large, curved sofa, a coffee table, and a large window. The ceiling features a recessed lighting design with a long, thin, white LED strip light forming a large, open square shape. Several small, square, recessed lights are also installed in the ceiling.

RESIDENTIAL LIGHTING

A modern office space with a long, white, curved reception desk. The ceiling is white and features several small, square, recessed lights. A glass display case is visible on the left side of the desk.

COMMERCIAL LIGHTING

SQUARE TRIM MODELS

S-500-11-11
Square Fixed Trim



S-500-11-05
Square Fixed Trim



S-540-11-11
Square Adjustable Trim



S-540-11-05
Square Adjustable Trim



SQUARE TRIMLESS MODELS

S-500-11-11-TL
Square Fixed Trimless



S-500-11-05-TL
Square Fixed Trimless



S-540-11-11-TL
Square Adjustable Trimless



S-540-11-05-TL
Square Adjustable Trimless



ROCKET 9W

TUNABLE & CIRCADIAN LIGHTING

LED COLOR TECHNOLOGY OPTIONS

1800K to 4000K

2200K to 5000K

2700K to 6500K

FEATURES

Wattage:	9 Watts (two channels)
LED CRI:	>95Ra
Lumens range:	550lm - 650 Lm
Input Voltage:	48 Volts RJ45
Compatible Decoder:	For dimming use DMX-SR2112
IP Grade:	IP20 Standard
Warranty:	50,000 Hours 5 Years

STANDARDS



CRI 95⁺

FINISH

White

BEAM ANGLE



20 Degrees



40 Degrees




COMPATIBLE PRODUCT FAMILY




T-SERIES



V-SERIES



MR-SERIES



S-SERIES

T SERIES

The T Series is a simple and versatile recessed fixture used in residential or commercial settings that doesn't require a pre-construction back can.

Available in round, square and shower trim options.



ADJUSTABLE TRIM MODELS

T-150-11



T-200-11



T-250-01



T-550-11



FIXED TRIM MODELS

T-300-22



T-500-22



T-400-11



T-600-11



SHOWER TRIM MODELS

T-100-22



T-700-11



V SERIES 9W

The V Series is an aesthetically pleasing and functional trim compatible with the 9W BI-White tunable light engine.

The trim is available in an open or closed faceplate option. Both are available in trim or trimless.

V1 SERIES - COMPATIBLE TRIMS

V1-9W-11-OP
Open Trim



V1-9W-11-CL
Closed Trim



V1-9W-11-TL-OP
Open Trimless



V1-9W-11-TL-CL
Closed Trimless



V2 SERIES - COMPATIBLE TRIMS

V2-9W-11-OP
Open Trim



V2-9W-11-CL
Closed Trim



V2-9W-11-TL-OP
Open Trimless



V2-9W-11-TL-CL
Closed Trimless




MR-SERIES

The MR luminaire boasts ultimate sophistication, flexibility and performance. Housing a 9W tunable white light engine, this trimless luminaire has a recessed look with an internal mechanism to position the light engine at any required angle.



COMPLETE KIT INCLUDES



HOUSING



TRIMLESS
PLATE



ROCKET 9W
BULB

RIVA 16W

TUNABLE & CIRCADIAN LIGHTING

LED COLOR TECHNOLOGY OPTIONS

1800K to 4000K

2200K to 5000K

2700K to 6500K

FEATURES

Wattage:	16 Watts (two channels)
LED CRI:	≥95Ra
Lumens Range:	1400 Lm - 1700 Lm
Input Voltage:	48 Volts RJ45
Compatible Decoder:	For dimming use DMX-SR2112
IP Grade:	IP20 and IP65
Warranty:	50,000 Hours 5 Years

BEAM ANGLE



40 Degrees



STANDARDS



FINISH

Matte White

Matte Black

RGBW 20W

RGBW LIGHTING

LED COLOR TECHNOLOGY OPTION

RGB + 3000K

FEATURES

Wattage:	20 Watts
LED CRI:	≥95Ra (White chip only)
Lumens Range:	1200 Lm
Input Voltage:	48 Volts RJ45
Compatible Decoder:	For dimming use DMX-SR2112
IP Grade:	IP20 and IP65
Warranty:	50,000 Hours 5 Years

BEAM ANGLE



40 Degrees



STANDARDS



FINISH

Matte White

Matte Black

COMPATIBLE PRODUCT FAMILY



V-SERIES



C-SERIES

V-SERIES



V1 SERIES - COMPATIBLE TRIMS

V1-16W/20W-W
Adjustable Open Trim



V1-16W/20W-B
Adjustable Open Trim



V1-16W/20W-W-TL
Adjustable Trimless



V1-16W/20W-B-TL
Adjustable Trimless



V2 SERIES - COMPATIBLE TRIMS

V2-16W/20W-W
Adjustable Open Trim



V2-16W/20W-B
Adjustable Open Trim



V2-16W/20W-W-TL
Adjustable Trimless



V2-16W/20W-B-TL
Adjustable Trimless



C-SERIES

C Series recessed trim is designed specifically for the BI White 16W and RGBW 20W light engines, no pre-construction can required.

ROUND TRIM OPTIONS

C-W-RD-16W/20W
Adjustable Round Trim



C-B-RD-16W/20W
Adjustable Round Trim



SQUARE TRIM OPTIONS

C-W-SQ-16W/20W
Adjustable Square Trim



C-B-SQ-16W/20W
Adjustable Square Trim



VENUS 16W

TUNABLE & CIRCADIAN LIGHTING

LED COLOR TECHNOLOGY OPTIONS

1800K to 4000K

2200K to 5000K

2700K to 6500K

FEATURES

Wattage:	16 Watts
LED CRI:	>95Ra
Lumens Range:	995 Lm - 1155 Lm
Input Voltage:	48 Volts RJ45
Compatible Decoder:	For dimming use DMX-SR2112
IP Grade:	IP20 Standard
Warranty:	50,000 Hours 5 Years

STANDARDS




FINISH

Matte
White

BEAM ANGLE



40 Degrees



Combining the ultimate in performance and aesthetics, the VENUS offers all features and benefits sought after by luxury homeowners, designers, architects and other professional specifiers. The super slim profile, trimless and tunable fixture is 1.5" in thickness and delivers an incredible 1150 lumens of light from a single source. No pre-construction back can required.




LUNA SERIES



Designed for shallow ceiling applications, the LUNA's **3.3" housing** allows for shallow ceiling restrictions. The LUNA delivers a high-lumen directional light source for maximum flexibility.



COMPATIBLE TRIMS



FIXTURE DIMENSIONS



LUNA 14W

TUNABLE & CIRCADIAN LIGHTING

LED COLOR TECHNOLOGY OPTIONS

1800K to 4000K

2200K to 5000K

2700K to 6500K

FEATURES

Wattage:	14 Watts
LED CRI:	≥95Ra
Lumens Range:	930 Lm - 1193 Lm
Input Voltage:	48 Volts RJ45
Compatible Decoder:	For dimming use DMX-SR2112
IP Grade:	IP20 Standard
Warranty:	50,000 Hours 5 Years

STANDARDS



FINISH

Matte
White

BEAM ANGLE



20 Degrees



40 Degrees



LUNA 10W

RGBW LIGHTING

LED COLOR TECHNOLOGY OPTION

RGB + 3000K

FEATURES

Wattage:	10 Watts
LED CRI:	≥95Ra
Lumens Range:	480 Lm - 525 Lm
Input Voltage:	48 Volts RJ45
Compatible Decoder:	For dimming use DMX-SR2112
IP Grade:	IP20 Standard
Warranty:	50,000 Hours 5 Years

STANDARDS



FINISH

Matte
White

BEAM ANGLE



20 Degrees



40 Degrees



BIANCA PDT

The BIANCA Pendant is the perfect addition to any kitchen or similar application. The easily adjustable wire length allows for perfect height adjustment. The new design offers a sleek and minimalist look.



BIANCA-16W-PDT

DECORATIVE PENDANT LIGHTING

LED COLOR TECHNOLOGY OPTIONS

1800K to 4000K

2200K to 5000K

2700K to 6500K

FEATURES

Wattage:	16 Watts (two channels)
Lumens Rate:	1200 Lm - 1400 Lm
Beam Angle:	20° and 40°
LM Rating:	LM-80
Input Voltage:	48 Volts RJ45
Compatible Decoder:	For dimming use DMX-SR2112
IP Grade:	IP20 Standard
Warranty:	50,000 Hours 5 Years

STANDARDS




FINISH OPTIONS

Matte
White

Matte
Black

ADJUSTABLE CORD



DUOMO

The DUOMO Pendant is a modern circular LED chandelier that enhances a room with elegance & sophistication.

The three available sizes allow you to create a unique layering effect, perfect for adding dimension to any space.



DUOMO SERIES

DECORATIVE PENDANT LIGHTING

FEATURES

	DUOMO-B-BI27-65K-3FT	DUOMO-B-BI27-65K-4FT	DUOMO-B-BI27-65K-5FT
Wattage:	26 Watts	41 Watts	62 Watts
Total Luminous Flux:	473 lm	843 lm	936 lm
Diameter:	Ø 35.43"	Ø 47.24"	Ø 59.05"
Color Temperature:	2700K - 6500K and RGBW		
IP Grade:	IP20 Standard		
Warranty:	50,000 Hours 5 Years		

FINISH OPTIONS



STANDARDS



LED COLOR TECHNOLOGY

2700K to 6500K

RGBW

SURFACE MOUNT

Colorbeam introduces a new line of adjustable Surface Mount spotlights, ideal for decorative applications.



ORBITA-14W-BI




CCT OPTIONS

1800K to 4000K

2200K to 5000K

2700K to 6500K

DIMENSIONS



LUMENS RANGE

1000 to 1230 Lm

FINISH OPTIONS

Matte White

Matte Black

BEAM ANGLE




20°



40°



ORBITA-9W-BR-PDT



CCT OPTIONS

1800K to 4000K

2200K to 5000K

2700K to 6500K

LUMENS RANGE


400 Lm to 430 Lm

BEAM ANGLE



40°

DIMENSIONS




FINISH OPTIONS

Matte White

Matte Black



ORBITA-9W-BR



CCT OPTIONS

1800K to 4000K

2200K to 5000K

2700K to 6500K

LUMENS RANGE


400 Lm to 430 Lm

BEAM ANGLE



40°

DIMENSIONS



FINISH OPTIONS

Matte White

Matte Black

ALTA-14W-BI-SQ-PDT



CCT OPTIONS

1800K to 4000K

2200K to 5000K

2700K to 6500K

LUMENS RANGE


860 Lm to 965 Lm

BEAM ANGLE



50°


DIMENSIONS



FINISH OPTION

Matte White

ALTA-14W-BI-SQ



CCT OPTIONS

1800K to 4000K

2200K to 5000K

2700K to 6500K

LUMENS RANGE


860 Lm to 965 Lm

BEAM ANGLE



50°

DIMENSIONS



FINISH OPTIONS

Matte White

Matte Black



ALTA-14W-BI-RD-PDT



CCT OPTIONS

1800K to 4000K

2200K to 5000K

2700K to 6500K

LUMENS RANGE


850 Lm to 1030 Lm

BEAM ANGLE



50°

DIMENSIONS



FINISH OPTION

Matte White



ALTA-14W-BI-RD



CCT OPTIONS

1800K to 4000K

2200K to 5000K

2700K to 6500K

LUMENS RANGE


850 Lm to 1030 Lm

BEAM ANGLE



50°

DIMENSIONS




FINISH OPTIONS

Matte White


Matte Black

SUMA

SURFACE MOUNT



SUMA-24W-BI



CCT OPTIONS

1800K to 4000K

2700K to 6500K

LUMENS RANGE

1780 to 2200 Lm

BEAM ANGLE




20°



40°

DIMENSIONS



FINISH OPTIONS



Matte
White

Matte
Black

RECESSED LIGHTING GUIDE

TUNABLE & CIRCADIAN LIGHTING

RGBW LIGHTING

PICTURE								
LIGHT ENGINE	BIANCA 16W	BIANCA 14W	ROCKET 9W	VENUS 16W	RIVA 16W	LUNA	10W RGBW	RIVA 20W
FAMILY PRODUCT	BIANCA-16W-BI-RD BIANCA-16W-BI-SQ BIANCA-16W-BI-RDR BIANCA-16W-BI-PTD	TB-SERIES VB1-SERIES VB2-SERIES S-SERIES	S-SERIES T-SERIES MR-SERIES V1-SERIES V2-SERIES	VENUS SERIES	V1-SERIES V2-SERIES C-SERIES	LUNA-14W-BI-SERIES LUNA-10W-RGBW-SERIES	TB-SERIES VB1-SERIES VB2-SERIES S-SERIES	V1-SERIES V2-SERIES C-SERIES
WATTAGE	16W	14W	9W	16W	16W	14W	10W	20W
CCT	18K - 40K 22K-50K 27K-65K	18K - 40K 22K-50K 27K-65K	18K - 40K 22K-50K 27K-65K	18K - 40K 22K-50K 27K-65K	18K - 40K 22K-50K 27K-65K	18K - 40K 22K-50K 27K-65K	RGBW	RGB+White
LUMENS RANGE	1200 lm - 1400 lm	700 lm - 1020 lm	550 lm - 650 lm	995 lm - 1155 lm	1400 lm - 1700 lm	929 lm - 1193 lm	480 lm - 525 lm	480 lm 525 lm
BEAM ANGLE	20° and 40°	20° and 40°	20° and 40°	40°	40°	20° and 40°	20° and 40°	40°
LED CRI	≥95Ra	≥95Ra	≥95Ra	≥95Ra	≥95Ra	≥95Ra	≥95Ra (White chip only)	≥95Ra (White chip only)
IP GRADE	IP20 Standard	IP20 Standard	IP20 Standard	IP20 Standard	IP20 and IP65	IP20 Standard	IP20 and IP65	IP20 and IP65
COMPATIBLE DECODER	For dimming use DMX-SR2112	For dimming use DMX-SR2112	For dimming use DMX-SR2112	For dimming use DMX-SR2112	For dimming use DMX-SR2112	For dimming use DMX-SR2112	For dimming use DMX-SR2112	For dimming use DMX-SR2112
CEILING THICKNESS	½" to 1 ½" / 12.7mm to 38.1mm	½" to 1 ½" / 12.7mm to 38.1mm	½" to 1 ½" / 12.7mm to 38.1mm	Perfect fit into ceiling, takes up to 1/2" thick ceiling	½" to 1 ½" / 12.7mm to 38.1mm	1/2" or 2" / 12.7mm or 50.8mm	½" to 1 ½" / 12.7mm to 38.1mm	½" to 1 ½" / 12.7mm to 38.1mm



LINEAR LIGHTING

Colorbeam's indoor and outdoor tape light products are the perfect solution to meet the growing linear lighting applications.

Available in Bi-White, RGBW, RGB+WW and Neon Flex, our LED Tapes deliver quality, reliability and versatility.

TYPICAL APPLICATIONS

- Accent & decorative lighting
- Architectural lighting
- Indoor and outdoor applications



Dimmable Lighting
0 to 100% flicker-free dimming



Tunable Lighting



RGB+WW Lighting



RGBW Lighting



3 Year
Limited Warranty



UL LISTED

NEON FLEX TAPE

Colorbeam Lighting's new Neon Flex Tape delivers an ultra-rich, high-saturation light source.

The flexible, waterproof tape is bendable and allows for limitless, creative linear lighting solutions. Available in RGBW, Pixel Tape & Tunable White options.





TAPE-120-NF15-BI

Wattage per m:	12W, 24V
Lumens per m:	220 Lm + 265 Lm
LED Quantity:	120 LEDs/m
Color CCT:	1800K + 6500K
CRI:	Ra+90
Beam Angle:	120°
IP Grade:	IP68

LED COLOR TECHNOLOGY

1800K-6500K






TAPE-60-NF15-RGBW

Wattage per m:	17W, 24V
Lumens per m:	234 Lm
LED Quantity:	60 LEDs/m
Color CCT:	RGB+3000K
CRI:	Ra+80
Beam Angle:	120°
IP Grade:	IP68

LED COLOR TECHNOLOGY

RGBW = 234 Lm/m






TAPE-120-NF16-BI

Wattage per m:	12W, 24V
Lumens per m:	263 Lm + 294 Lm
LED Quantity:	120 LEDs/m
Color CCT:	1800K + 6500K
CRI:	Ra+90
Beam Angle:	120°
IP Grade:	IP68

LED COLOR TECHNOLOGY

1800K-6500K




TAPE-72-NF16-RGBW

Wattage per m:	17W, 24V
Lumens per m:	331 Lm
LED Quantity:	72 LEDs/m
Color CCT:	RGB + 3000K
CRI:	Ra+90
Beam Angle:	120°
IP Grade:	IP68

LED COLOR TECHNOLOGY

RGBW = 331 Lm/m




NEON-TAPE-N18-BI

Wattage per m:	12W, 24V
Lumens per m:	348 Lm + 395 Lm
LED Quantity:	120 LEDs/m
Color CCT:	1800K + 6500K
CRI:	Ra+90
Beam Angle:	210°
IP Grade:	IP68

LED COLOR TECHNOLOGY

1800K-6500K




TAPE-72-NF18-RGBW

Wattage per m:	17W, 24V
Lumens per m:	332 Lm
LED Quantity:	72 LEDs/m
Color CCT:	RGB + 3000K
CRI:	Ra+90
Beam Angle:	210°
IP Grade:	IP68

LED COLOR TECHNOLOGY

RGBW = 332 Lm/m




TAPE-70-PX16-RGBW

Wattage per m:	18W, 24V
Lumens per m:	399 Lm
LED Quantity:	70 LEDs/m
Color CCT:	RGB + 3000K
CRI:	Ra+80
Beam Angle:	120°
IP Grade:	IP68

LED COLOR TECHNOLOGY

RGBW = 339 Lm/m

*PIXEL TAPE




TAPE-60-NF21-RGBW

Wattage per m:	17W, 24V
Lumens per m:	269 Lm
LED Quantity:	60 LEDs/m
Color CCT:	RGB + 3000K
CRI:	Ra+90
Beam Angle:	270°
IP Grade:	IP68

LED COLOR TECHNOLOGY

RGBW = 332 Lm/m





TAPE-180-RGB+WW

Wattage per m:	15.5W, 24V, 0.6A
Lumens per m:	Up to 1250 Lm/m
LED Quantity:	180 LEDs/m
Color CCT:	RGB + WW
CRI:	Ra+95
Beam Angle:	120°
IP Grade:	IP20
Tape Length:	5 meters (16.4FT/Roll)

LED COLOR TECHNOLOGY

RGB + WW = 1250 Lm/m






TAPE-120-BI

Wattage per m:	14.4 W, 24V, 0.4A
Lumens per m:	Up to 1150Lm/M
LED Quantity:	120 LED/m
Color CCT:	2700K-6500K
CRI:	Ra+95
Beam Angle:	120°
IP Grade:	IP20 and IP68
Tape Length:	5 meters (16.4FT/Roll)

LED COLOR TECHNOLOGY

2700K-6500K






TAPE-60-RGBW

Wattage per m:	14.4W, 24V, 0.6A
Lumens per m:	Up to 750 Lm/m
LED Quantity:	60 LED/m
Color CCT:	RGB + White / 2700K or 3000K
CRI:	Ra+95
Beam Angle:	120°
IP Grade:	IP20/IP68
Tape Length:	5 meters (16.4FT/Roll)

LED COLOR TECHNOLOGY

RGBW = Up to 750 Lm/m



TAPE-240-RGBW

Wattage per m:	20W, 24V, 1.1A
Lumens per m:	1600 Lm/m
LED Quantity:	240 LED/m
Color CCT:	RGB+3000K
CRI:	Ra+95
Beam Angle:	120°
IP Grade:	IP20
Tape Length:	5 meters (16.4FT/Roll)

LED COLOR TECHNOLOGY

RGB+3000K = 1600 Lm/m





OUTDOOR & LANDSCAPE LIGHTING

Outdoor and backyard space is quickly becoming an important extension of the home.

As a multitude of outdoor entertainment equipment floods the market, enhancing the setting with proper lighting will truly transform the space and give family, friends and customers a memorable experience.



Dimmable Lighting
0 to 100% flicker-free dimming



Tunable Lighting



RGB Lighting



RGBW Lighting



Waterproof IP68



3 Year
Limited Warranty



US LISTED

LLS-SERIES

The LLS Series is a high-lumen output linear bar for indoor and outdoor use.

Driving attention to a building or highlighting a building's architectural details are just some of the growing building illumination applications.

WALL WASH - LED LINEAR LIGHTING



LED COLOR TECHNOLOGY



FEATURES

Wattage:	2FT 30W, 4FT 60W
Lumens Range:	1040 Lm to 2280 Lm
LED CRI:	≥95Ra (White Chip Only)
Beam Angle:	25°, 40° and 60°
Driver:	DRV-SRPC2108-24-200CVF
IP Grade:	IP67
Lifespan:	50,000 Hours



BALZO SERIES

SPOTLIGHT

BALZO SERIES

BALZO-9W-BR-AL



BALZO-10W-RGBW-B




LED COLOR TECHNOLOGY



FEATURES

Wattage:	9W 10W
Lumens Range:	360 - 400 Lm 250 Lm
LED CRI:	≥95Ra
Beam Angle:	40°
Input Voltage:	48VDC
IP Grade:	IP68
Lifespan:	50,000 Hours

FINISH OPTIONS



BALZO SERIES LG


BALZO-9W-BR-LG-AL



BALZO-10W-RGBW-LG-SS




LED COLOR TECHNOLOGY



FEATURES

Wattage:	9W 10W
Lumens Range:	360 - 400 Lm 250 Lm
LED CRI:	≥95Ra
Beam Angle:	40°
Input Voltage:	48VDC
IP Grade:	IP68
Lifespan:	50,000 Hours

FINISH OPTIONS



BALZO SERIES

SPOTLIGHT

BALZO-10W-RGBW

BALZO-10W-RGBW-AL



BALZO-10W-RGBW-B





LED COLOR TECHNOLOGY



FEATURES

Wattage:	10W
Lumens Range:	650 Lm
LED CRI:	≥95Ra
Beam Angle:	20° and 40°
Input Voltage:	48VDC
IP Grade:	IP68
Lifespan:	50,000 Hours

FINISH OPTIONS




BALZO-14W-BI

BALZO-14W-BI-SS





LED COLOR TECHNOLOGY



FEATURES

Wattage:	14W
Lumens Range:	630 – 730 Lm
LED CRI:	≥95Ra
Beam Angle:	20° and 40°
Input Voltage:	48VDC
IP Grade:	IP68
Lifespan:	50,000 Hours

FINISH OPTIONS



PALMA-9W SERIES

INDOOR & OUTDOOR

PALMA-9W-BR

PALMA-9W-BR-AL



PALMA-9W-BR-B



LED COLOR TECHNOLOGY

1800K - 4000K

2200K - 5000K

2700K - 6500K

FEATURES

Wattage:	9W
Lumens Range:	320 - 380 lm
LED CRI:	≥95Ra
Beam Angle:	20° and 40°
Dimensions:	Ø59*H108.85 mm
Input Voltage:	48VDC
IP Grade:	IP67
Lifespan:	50,000 Hours

FINISH OPTIONS

Aluminum
(AL)

Stainless Steel
(SS)

Brass
(B)

PALMA-L-9W-BR

PALMA-L-9W-BR-AL



PALMA-L-9W-BR-B



LED COLOR TECHNOLOGY

1800K - 4000K

2200K - 5000K

2700K - 6500K

FEATURES

Wattage:	9W
Lumens Range:	390 - 400 lm
LED CRI:	≥95Ra
Beam Angle:	40°
Dimensions:	Ø 50*H109.2mm
Input Voltage:	48VDC
IP Grade:	IP67
Lifespan:	50,000 Hours

FINISH OPTIONS

Aluminum
(AL)

Stainless Steel
(SS)

Brass
(B)



TEGA-IN SERIES

Create impactful accent lighting by illuminating small trees, bushes, pathways, walls and columns.

ACCENT LIGHTING

TEGA-IN-14W-BI



TEGA-IN-10W-RGBW



LED COLOR TECHNOLOGY



FEATURES

Wattage:	14W 10W
Lumens Range:	690 - 980 Lm 420 Lm
LED CRI:	≥95Ra
Beam Angle:	20° or 40°
Driver:	DRV-SRPC2108-24-200CVF
IP Grade:	IP67
Lifespan:	50,000 Hours

TEGA-IN-1 SERIES

Make the texture of materials pop with the TEGA series in-ground up-lights.

ACCENT LIGHTING


TEGA-IN-1-9W



TEGA-IN-1-RGBW-10W



LED COLOR TECHNOLOGY



FEATURES

Wattage:	9W 10W
Lumens Range:	390 - 470 Lm 270 Lm
LED CRI:	≥95Ra
Beam Angle:	20° or 40°
Driver:	DRV-SRPC2108-24-200CVF
IP Grade:	IP67
Lifespan:	50,000 Hours

TEGA-DR

Light up pathways, driveways, patios and docks with the NEW and more powerful TEGA-DR.

Tough enough to be driven over.

PATHWAY LIGHTING

TEGA-DR-BR-9W



LED COLOR TECHNOLOGY

3000K

RGBW

FEATURES

Wattage:	9W 10W
Side:	1 Side, 2 Sides and 4 Sides
LED CRI:	≥ 95 Ra
Driver:	DRV-SRPC2108-24-200CVF
IP Grade:	IP67
Lifespan:	50,000 Hours


ROMA SERIES

The Roma Series is our indoor walls & stairs lighting line. Roma Series is a recessed 2 Watts LED source available in both round and square shapes.

STEP LIGHTING

ROMA-FC-W30K-SQ

ROMA-FC-W30K-RD




LED COLOR TECHNOLOGY

3000K

FEATURES

Wattage:	2W
Lumens Range:	35 Lm
Beam Angle:	82°
LED CRI:	≥ 95 Ra
Driver:	DRV-SRPC2108-24-200CVF
IP Grade:	IP67
Lifespan:	50,000 Hours



POWER & CONTROL

GATEWAY-IDMX


DESCRIPTION

Colorbeam's patented GATEway Processor is the heart and soul of our system, and it keeps getting better.

Working in tandem with leading control manufacturers, the GATEway delivers the most advanced wellness application in addition to scene settings, tunability, color and perfect dimming. All at a press of a keypad button.

FEATURES

- Built-in circadian rhythm application
- New user interface (tablet & mobile friendly)
- Autonomous lighting system
- Native 3rd party integration with industry-leading control manufacturers
- Input ports for occupancy sensors and alarm system
- DIN-RAIL Mounted
- Integrated RS485 port for future Colorbeam keypad integrations



RACKMOUNT SOLUTION



NEW 1U RACKMOUNT MODULES

ETH-RM-4164

Features:

- 16 individual zone control, digital display, easy to set and configure
- 64 selectable channels
- New IP or DMX control
- Master & decoder mode
- 1U rack space



PS-RM-4164

The power supplies are entirely isolated, each one providing 96 watts 48V DC.

The LED indicator provides clear functionality status. First Class 2, UL listed product of its kind.

- 1U rack space



NEW DIN-RAIL MODULES

FOR TAPE LIGHT AND OUTDOOR LIGHTING PRODUCTS

DMX-SR2216



DMX-SR2216

- Master & decoder mode, RDM function.
- Metal housing, digital display of data for easy setup and configuration.
- Dual power supply input. Switchable between one and two power supplies.
- Constant input voltage 12V-36V.
- Each channel can provide up to 8 amps depending on the input voltage.
- The driver is a common VCC, and each channel controls the current via ground.
- Total 16 PWM output channels.
- The DMX Input/Output is optically isolated from the outputs and the power in.

PS-SR2216-96

The new power supply utilizes two AC connectors to extend the power from one power supply to another. The connector for power input is IEC Appliance Inlet C6, and the output is Female Sockets NEMA 5-15R.

PS-SR2216-96





Learn More

Colorbeam Lighting

450 Montee de Liesse,
Montreal, QC, Canada H4T 1N8

1.844.301.2262

info@colorbeamlighting.com

www.colorbeamlighting.com

Follow Us

[@colorbeamlighting](https://www.instagram.com/colorbeamlighting)



SCAN ME



Visit Our Website!

Get In Touch!

Colorbeam Lighting

450 Montee de Liesse, Montreal, QC, Canada H4T 1N8

1.844.301.2262 | info@colorbeamlighting.com

www.colorbeamlighting.com

Follow Us

[@colorbeamlighting](#)

