



Straight Solid Pin Terminal Connectors



- Straight Solid Pin
- All-Aluminum Pin Terminal designed for Termination of both Aluminum and Copper Conductors - Tin Plated
- Barrel is Pre-Filled with Oxide Inhibitor
- Die Index and Crimp Marks on Barrel
- Supplied with EPDM Insulating Cover
- Rated 600 Volt

DIMENSIONS = INCHES

CAT. NO.	WIRE SIZE	PIN SIZE	O.D.	I.D.	PIN DIA.	TOTAL LENGTH	PIN LENGTH	BODY LENGTH	COLOR CODE	INNER BOX	OUTER BOX
90970	6	4	.598	.220	.240	1.85	.681	1.17	GRAY	25	250
90971	4	4	.598	.236	.240	1.85	.681	1.17	GREEN	25	250
90972	2	4	.598	.299	.240	1.84	.680	1.16	PINK	25	250
90973	1	3	.598	.318	.250	1.99	.830	1.16	GOLD	10	100
90974	1/0	2	.598	.370	.290	1.99	.830	1.16	TAN	10	100
90975	2/0	1	.850	.429	.330	2.20	.830	1.37	OLIVE	10	100
90976	3/0	1/0	.850	.476	.370	2.59	1.22	1.37	RUBY	10	100
90977	4/0	2/0	.850	.476	.370	2.59	1.22	1.37	WHITE	10	100
90978	250 MCM	3/0	1.09	.594	.460	2.62	1.22	1.40	RED	10	100
90979	300 MCM	4/0	1.09	.653	.530	2.73	1.33	1.40	BLUE	10	100
90980	350 MCM	250	1.09	.716	.570	2.73	1.33	1.40	BROWN	10	100
90981	400 MCM	300	1.31	.763	.620	3.07	1.59	1.48	GREEN	10	100
90982	500 MCM	350	1.31	.826	.680	3.07	1.59	1.48	PINK	10	100
90983	600 MCM	400	1.46	.921	.720	3.67	1.64	2.03	YELLOW	3	30
90984	750 MCM	500	1.46	1.03	.810	3.78	1.75	2.03	YELLOW	3	30