

Amplifier For JBL CS Commercial Solution Series Public Address System



The JBL Commercial<sup>®</sup> CSA-2120 power amplifier is a professional tool designed and built for installed sound applications. The amplifier is two-channel model providing simple analog front-end processing, with a switch-mode universal power supply.

The amplifier includes two optional accessories: rack mounting kit and transformer module. With the rack mounting kit, you can install the amplifier to a cabinet or wall. If your loudspeaker system requires higher impedance, the transformer module can be connected between the amplifier and loudspeaker systems to obtain the impedance matching.

## Features


- Two input channels and two output channels, Power of each channel: 120W
- Output impedance of each channel:  $4\Omega$  and  $8\Omega$

CSA-2120

- High power output, compact size, light weight
- Accurate, uncoloured sound with very low distortion for the best in music and voice
- Over heat auto protection
- Low voltage auto protection
- The auto-standby mode allows the amplifier to save energy by disabling the amplifier pulse width modulation generator when there is no input signal
- Detachable Euroblock input and output
- Switch-mode universal power supply

# Line drawing







# CSA-2120

**Amplifier For** JBL CS Commercial Solution Series **Public Address System** 

	CSA-2120 Specifications
Output Power:	4 ohms / 8 ohms 120 W (two channels at 1 kHz power, THD+N<0.5%)
Frequency Response:	+/- 1dB (At 1watt into 4 or 8 ohms)
Load Impedance:	Rated for 4 or 8 ohms
Sensitivity (8 ohms load):	1.4 Vrms
Signal to Noise Ratio :	>100 dB (below rated 8-ohm power at 1 kHz, A weighted)
Crosstalk (A weighted):	70 dB below rated from 20 Hz to 1 kHz;
	50 dB below rated at 20 kHz
Input Impedance :	Balanced: 20 k ohms (nominal)
	Unbalanced: 10 k ohms (nominal)

AC Line Voltage and **Frequency Configurations** Available: 100-240 V, 50/60 Hz **Maximum Input Signal:** +20 dBu typical **Operating Temperature:** 0° C to 40° C at 95% relative humidity (non-condensing) Dimensions (W x H x D) : 8.2" x 1.7 x 7" (209 mm x 44 mm x 178 mm) **Shipping Weight:** 1.5 KG (3.4 lbs) (Rack mounting kit attached forunits with the part number "NCSA2120R-U-CN") 1.3 KG (2.9 lbs) (No rack mounting kit attached for units with the part number "NCSA2120-U-CN")

### **Contact Information**

#### On The World Wide Web:

www.jblcommercialporducts.com **Professional Contacts, Outside the USA:** Contact the JBL Professional Distributor in your area. A complete list of JBL Professional international distributors is provided at our U.S.A. website: www.jblpro.com

### **Ordering Information**

CSA-2120 Amplifier