



Model CA2120

Key Features:

- 1 rack unit high
- High power class-D power amplifier module
- Toroidal 100 V output transformers
- Bridgeable 2 channel amplifier
- Each output can be used in either LowZ or constant voltage mode without changing settings.
- High thermal efficiency
- Signal clip indicators on the rear for fast and easy configuration of the input gain.
- Universal switching power supply unit
- No cooling fan – maintenance free
- Low power consumption
- Balanced euroblock inputs
- Unbalanced inputs on RCA with pass through
- Input level attenuators on all inputs
- Euroblock speaker output connectors with multiple taps: 35 volt, 50 volt, 70 volt, 100 volt and 4 ohm
- Extended speaker and amp protection circuits: over current protect, over temperature protect, input overload
- Individual channel mute buttons and versatile LED status indicators
- Removable rack-ears

Specifications:

Model	CA2120	
Power Rating	4 Ohms	2 x 120Watt RMS
output power bridged	8 Ohms	240Watt RMS
Input impedance	22 kΩ	
Input sensitivity	0 dBV / 1 V	
S/N ratio	>90 dB A weighted	
Channel separation	> 60 dB @ 1 kHz	
Frequency Response	50 Hz-20 KHz	
Distortion (THD)	<0.1%	
Net weight product	6.1 kg	
Dimensions: (W x D x H)	430 x 238 x 50 mm	