





ED3AI-16

16 Ch TVI/AHD/CVI/Analog/IP Universal Port Recorder (8 MP), with 4 Bonus IP Ch (8 MP), Up to 20 cameras total, 2 HD Bays, 4K

Features

- 16 Channel Universal Port DVR (TVI/AHD/CVI/Analog/IP)
- Up to 8MP Support on HD Analog Channels
- 4 Bonus IP Channels Up to 8 Megapixel in Full IP
- Total Max IP Input: 20 (Including Bonus IPC)
- H.265/H.265+/H.264/H.264+ Video Compression
- True P2P Connectivity with QR Code Connect
- Simultaneous HDMI/VGA up to 1080p Resolution
- CVBS Main or Spot Monitor
- HDMI up to 4K Resolution
- Supports up to 16 Channel Simultaneous Playback
- Multiple video search options including Smart and Thumbnail Search for quick retrieval of footage.
- Store and access video storage to the Cloud
- Upgrade your recorder via the Cloud
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software to easily manage your system from your Apple computer

	LLL VAIL SERIES
Model	ED3AI-16
Chipset	2*Hi3531D
Video & Audio Input	
Analog Video Input	16ch(1.0Vp-p, 75 Ω)
HDTVI Input	8MP,5MP,4MP,1080P, 720P
CVI Input	8MP,4MP,1080P, 720P
AHD Input	8MP,5MP,4MP,1080P, 720P
CVBS Input	Support
IP video Input	Support
Audio Input	4-ch, RCA(2.0 Vp-p, 1 KΩ)
Two-Way Audio	1-ch, multiplex with Audio Input(RCA)
Video & Audio Output HDMI	4K(3840×2160)/30Hz,1920×1080/60Hz,1280×1024/60Hz,1280×720/60Hz,1 024×768/60Hz
VGA	1920×1080/60Hz,1280×1024/60Hz,1280×720/60Hz,1024×768/60Hz
CVBS	BNC(1.0Vp-p,75Ω),resolution:PAL:704x576,NTSC:704x480
Audio Output	1-ch, RCA(Linear, 1kΩ)
Recording	110/5 #10/5#10/4 #10/4
Video Compression	H.265+/H.265/H.264+/H.264
Encoding Resolution Resolution	8MP/5MP/4MP/1080P/1080P Lite/720P/960H/D1 Main stream:8MP@7fps, 8MP-N@15fps, 5MP@12fps,4MP@15f-
Frame Rate(fps)	ps,1080P/720P/960H/D1@25fps(P)/30fps(N) 1-25fps
Video Bit Rate	11Kbps~ 10Mbps
Record Mode	Manual, Schedule, Alarm
Audio Compression	G.711a
Audio Bit Rate	64kbps
Bonus IPC Input	
Resolution	8MP/5MP/4MP/3MP/2MP/720p/960H
Frame Rate	8MP/5MP/4MP/3MP/2MP/720p/960H @ 30 FPS
IP Input	
Resolution	8MP/5MP/4MP/3MP/2MP/720p/960H
Frame Rate	8MP/5MP/4MP/3MP/2MP/720p/960H @ 30 FPS
IPC Input/Access Band- width	IPC x 4 / 72Mbps (Hybrid), IPC x 20 / 72MBps (Full)
Total Max IP Input	20 (including Bonus IPC)
Playback & Backup	
Playback Number	4CH 8MP Playback, 8CH 8MP-N Playback
Playback Mode	Smart Playback/Normal/Time Division/ Label/ Event/ Picture playback
Backup Mode Advanced Features	USB Device/Network/External HDD
Smart Detection for	
Analog	16 line crossing detection,intrusion detection
Video Quality Detection	16CH Defocus Detection
Smart Detection for IPC	Line crossing detection, Area Intrusion detection, Region Entrance, Region Exiting, Fast moving, Unattached Object, Object Missing, Face Detection
Smart Playback for Analog	Line Crossing/Are Intrution/Motion Detection
Smart Playback for IPC	Face detection/Line Crossing/Are Intrution/Motion Detection
Cloud Storage	Support
Cloud Upgrade	Support
Network	
Ethernet	1 RJ-45 10 /100/1000 Mbps self-adaptive Ethernet interface HTTPs: HTTPTCP/IPIPV4 LIPPPOnvif 2 6 RTSPRTCPLIDE SMTPSNMPMulti-
Network Function	HTTPs, HTTP,TCP/IP,IPv4,UPnP,Onvif 2.6,RTSP,RTCP,UDP, SMTP,SNMP,Multi- cast,IGMP,NTP, DHCP,DNS,DDNS, FTP, P2P
Network Function Web Client	HTTPs, HTTP,TCP/IP,IPv4,UPnP,Onvif 2.6,RTSP,RTCP,UDP, SMTP,SNMP,Multi-
Network Function Web Client Hard Disk	HTTPs, HTTP,TCP/IP,IPv4,UPnP,Onvif 2.6,RTSP,RTCP,UDP, SMTP,SNMP,Multi-cast,IGMP,NTP, DHCP,DNS,DDNS, FTP, P2P User Defined, Max 32 Users
Network Function Web Client	HTTPs, HTTP,TCP/IP,IPv4,UPnP,Onvif 2.6,RTSP,RTCP,UDP, SMTP,SNMP,Multi-cast,IGMP,NTP, DHCP,DNS,DDNS, FTP, P2P User Defined, Max 32 Users 2 SATA interfaces Up to 12TB capacity for each HDD (Western Digital Only for 10TB
Network Function Web Client Hard Disk SATA Capacity	HTTPs, HTTP,TCP/IP,IPv4,UPnP,Onvif 2.6,RTSP,RTCP,UDP, SMTP,SNMP,Multi-cast,IGMP,NTP, DHCP,DNS,DDNS, FTP, P2P User Defined, Max 32 Users 2 SATA interfaces
Network Function Web Client Hard Disk SATA Capacity External Interface	HTTPs, HTTP,TCP/IP,IPv4,UPnP,Onvif 2.6,RTSP,RTCP,UDP, SMTP,SNMP,Multi-cast,IGMP,NTP, DHCP,DNS,DDNS, FTP, P2P User Defined, Max 32 Users 2 SATA interfaces Up to 12TB capacity for each HDD (Western Digital Only for 10TB Drives)
Network Function Web Client Hard Disk SATA Capacity External Interface Serial Interface	HTTPs, HTTP,TCP/IP,IPv4,UPnP,Onvif 2.6,RTSP,RTCP,UDP, SMTP,SNMP,Multi-cast,IGMP,NTP, DHCP,DNS,DDNS, FTP, P2P User Defined, Max 32 Users 2 SATA interfaces Up to 12TB capacity for each HDD (Western Digital Only for 10TB Drives) 1*Standard RS-485(half-duplex)
Network Function Web Client Hard Disk SATA Capacity External Interface Serial Interface USB Interface	HTTPs, HTTP,TCP/IP,IPv4,UPnP,Onvif 2.6,RTSP,RTCP,UDP, SMTP,SNMP,Multi-cast,IGMP,NTP, DHCP,DNS,DDNS, FTP, P2P User Defined, Max 32 Users 2 SATA interfaces Up to 12TB capacity for each HDD (Western Digital Only for 10TB Drives) 1*Standard RS-485(half-duplex) Front panel: 1 × USB 2.0; Rear panel: 1 × USB 2.0
Network Function Web Client Hard Disk SATA Capacity External Interface Serial Interface USB Interface Alarm Input	HTTPs, HTTP,TCP/IP,IPv4,UPnP,Onvif 2.6,RTSP,RTCP,UDP, SMTP,SNMP,Multi-cast,IGMP,NTP, DHCP,DNS,DDNS, FTP, P2P User Defined, Max 32 Users 2 SATA interfaces Up to 12TB capacity for each HDD (Western Digital Only for 10TB Drives) 1*Standard RS-485(half-duplex) Front panel: 1 × USB 2.0; Rear panel: 1 × USB 2.0 8ch
Network Function Web Client Hard Disk SATA Capacity External Interface Serial Interface USB Interface	HTTPs, HTTP,TCP/IP,IPv4,UPnP,Onvif 2.6,RTSP,RTCP,UDP, SMTP,SNMP,Multi-cast,IGMP,NTP, DHCP,DNS,DDNS, FTP, P2P User Defined, Max 32 Users 2 SATA interfaces Up to 12TB capacity for each HDD (Western Digital Only for 10TB Drives) 1*Standard RS-485(half-duplex) Front panel: 1 × USB 2.0; Rear panel: 1 × USB 2.0
Network Function Web Client Hard Disk SATA Capacity External Interface Serial Interface USB Interface Alarm Input Alarm Output	HTTPs, HTTP,TCP/IP,IPv4,UPnP,Onvif 2.6,RTSP,RTCP,UDP, SMTP,SNMP,Multi-cast,IGMP,NTP, DHCP,DNS,DDNS, FTP, P2P User Defined, Max 32 Users 2 SATA interfaces Up to 12TB capacity for each HDD (Western Digital Only for 10TB Drives) 1*Standard RS-485(half-duplex) Front panel: 1 × USB 2.0; Rear panel: 1 × USB 2.0 8ch
Network Function Web Client Hard Disk SATA Capacity External Interface Serial Interface USB Interface USB Interface Alarm Input Alarm Output General	HTTPs, HTTP,TCP/IP,IPv4,UPnP,Onvif 2.6,RTSP,RTCP,UDP, SMTP,SNMP,Multi-cast,IGMP,NTP, DHCP,DNS,DDNS, FTP, P2P User Defined, Max 32 Users 2 SATA interfaces Up to 12TB capacity for each HDD (Western Digital Only for 10TB Drives) 1*Standard RS-485(half-duplex) Front panel: 1 × USB 2.0; Rear panel: 1 × USB 2.0 8ch 4ch
Network Function Web Client Hard Disk SATA Capacity External Interface Serial Interface USB Interface Alarm Input Alarm Output General Power Supply	HTTPs, HTTP,TCP/IP,IPv4,UPnP,Onvif 2.6,RTSP,RTCP,UDP, SMTP,SNMP,Multi-cast,IGMP,NTP, DHCP,DNS,DDNS, FTP, P2P User Defined, Max 32 Users 2 SATA interfaces Up to 12TB capacity for each HDD (Western Digital Only for 10TB Drives) 1*Standard RS-485(half-duplex) Front panel: 1 × USB 2.0; Rear panel: 1 × USB 2.0 8ch 4ch DC12V,5A
Network Function Web Client Hard Disk SATA Capacity External Interface Serial Interface USB Interface Alarm Input Alarm Output General Power Supply Power Consumption	HTTPs, HTTP,TCP/IP,IPv4,UPnP,Onvif 2.6,RTSP,RTCP,UDP, SMTP,SNMP,Multi-cast,IGMP,NTP, DHCP,DNS,DDNS, FTP, P2P User Defined, Max 32 Users 2 SATA interfaces Up to 12TB capacity for each HDD (Western Digital Only for 10TB Drives) 1*Standard RS-485(half-duplex) Front panel: 1 × USB 2.0; Rear panel: 1 × USB 2.0 8ch 4ch DC12V,5A \$20W(without HDD)

Ordering Information

ED3AI-16: 16 Ch Universal Port Recorder Available with 2/4/8/10/12 TB Hard Drive Options