

HDMI to HDMI Coupler HDMI Jack (Female) to HDMI Jack (Female)

EXP-HDMI-CPL

WyreStorm
Essentials

Specification Sheet



4K HDR 2160p 4:4:4 60 HDMI HDCP 2.2

WyreStorm - Powerful. Reliable. Simple.

Introduction

The EXP-HDMI-CPL is perfect for scenarios where the embedded HDMI cable is not long enough and the cable cannot be replaced with a longer cable.

Key Features

- Connects 2 HDMI cables together for longer transmission distance
- Bidirectional support of up to 4K@60 4:4:4 transmission

In the Box

1x EXP-HDMI-CPL HDMI to HDMI Coupler

Specifications

Audio and Video	
Input	1x HDMI: 19-pin type A Female
Output	1x HDMI: 19-pin type A Female
Output Video Encoding	Uncompressed
Encoding Data Rate	18 Gbps
End to End Latency	Zero
Audio Formats	2ch PCM Multichannel: LPCM and Up to DTS-X and Dolby Atmos
Video Resolutions (Max)	1920x1080p @240Hz 8bit RGB 2560x1440p @120Hz 8bit RGB 4096x2160p @60Hz 10bit HDR 4:2:0 4096x2160p @60Hz 12bit HDR 4:2:2 4096x2160p @60Hz 10bit HDR 4:4:4 4096x2160p @60Hz 10bit RGB
Supported Standards	DCI RGB HDR HDR10 Dolby Vision HLG BT.2020 BT.2100
Maximum Pixel Clock	600MHz
Communication and Control	
HDMI	TMDS HDCP 2.2 EDID
Supported Functions	Ethernet Audio Return Channel (ARC) CEC Auto Low Latency Mode (ALLM) Variable Refresh Rate (VRR)
Environmental	
Operating Temperature	32°F ~ 113°F (0°C ~ 45°C) 10% ~ 90%, non-condensing
Storage Temperature	-4°F to ~ 140°F (-20°C ~ +60°C) 10% ~ 90%, non-condensing
Maximum BTU	N/A
Dimensions and Weight	
Height	11.8mm/0.5in
Width	23.5mm/0.9in
Depth	29.6mm/1.2in
Weight	0.01kg/0.02lbs
Regulatory	
Safety and Emission	CE FCC RoHS RCM EAC

Right Product for the Right Application.



Note: WyreStorm reserves the right to change product specification, appearance or dimensions of this product at any time without prior notice.