



New blink code system makes it easier to diagnose line faults

- ● ● ● ● ● Startup sequence
- ● Digital command error
- ● ● Microprocessor error
- ● ● ● GFCI hardware error
- ● Power quality issue
- ● Over-voltage
- ● ● Over-current trip
- ○ Grounded neutral fault
- ○ ○ Low-level ground fault
- ○ ○ ○ High-level ground fault
- ○ ○ ○ ○ Cold-start ground fault
- Mechanical trip (ex: short circuit)

Ordering information

Contact your local Eaton representative today for more information about Eaton's spa panels or scan the QR code.



Warranty

- Limited lifetime warranty on Type CH spa panels, thermal-magnetic and GFCI branch circuit breakers
- 10-year limited warranty on Type BR spa panels, thermal-magnetic and GFCI branch breakers



Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton
1000 Eaton Boulevard
Cleveland, OH 44122
United States
Eaton.com

© 2023 Eaton
All Rights Reserved
Printed in USA
Publication No. SA00308001E / Z27452
April 2023



Eaton spa panels

Reliable protection



Save time and money with a simplified connection that meets special NEC® requirements.

Designed to save time

- Prewired—ready to install
- Factory-installed ground bar—no kits required
- Factory-assembled circuit breaker
- Bottom fed or top fed using a raintight hub
- Outdoor enclosure

Designed for safety

- Padlockable door prevents unauthorized persons from switching the breaker off
- Push-to-trip button easily allows routine breaker testing
- Meets code requirements for a safety disconnect



Eaton spa panels are available in two types

Type BR

Features

- 10-year warranty
- UL® Listed
- Factory-installed two-pole ground fault circuit interrupter (GFCI)



Type BR two-pole GFCI

Product selection

Catalog number	Main ampere rating	Enclosure type	Dimensions in inches	Factory-installed circuit breaker	Wire size range Cu/Al 60 °C or 75 °C for main lugs
BR40SPAST	40	Outdoor	9.75 H x 5.00 W x 4.00 D	GFTCB240	#8-#2
BR50SPAST	50	Outdoor	9.75 H x 5.00 W x 4.00 D	GFTCB250	#8-#2

Type CH

Features

- Two extra circuits for additional loads
- Limited lifetime warranty
- UL Listed
- Tough powder-coated galvanized steel enclosure
- Factory-installed two-pole GFCI



Type CH two-pole GFCI

Product selection

Catalog number	Main ampere rating	No. of extra circuits available	Enclosure type	Dimensions in inches	Factory-installed circuit breaker	Wire size range Cu/Al 60 °C or 75 °C for main lugs
CHSPA30	30	2	Outdoor	11.75 H x 6.75 W x 4.25 D	CHN230GF	#14-1/0
CHSPA40	40	2	Outdoor	11.75 H x 6.75 W x 4.25 D	CHN240GF	#14-1/0
CHSPA50	50	2	Outdoor	11.75 H x 6.75 W x 4.25 D	CHN250GF	#14-1/0
CHSPA60	60	2	Outdoor	11.75 H x 6.75 W x 4.25 D	CHN260GF	#14-1/0

The National Electrical Code® safety requirements for spa pumps:

- GFCI protection
- Visible disconnect

