



Punches 7/8" or 1 11/32" holes

| Part # | Description | Weight | Punch # | Weight | Die # | Weight |
|--------|-------------|--------|---------|--------|-------|--------|
| SP-7 | Stud Punch | 6 lbs | 43-52 | 1 lb | 43-95 | 1 lb |

Stud Punch



Stud Punch Accessories: Universal Stud Insulators provide code mandated* 360° protection for cable runs through increasingly popular metal studs, where sharp hole edges could otherwise gouge plastic or rubber-jacketed electric, communications or network cable. The patented one-piece design and folding tabs make installation literally a snap, resulting in a tight and secure attachment to the stud. The smooth, hang-free surface eases pulls, while the high-density design accommodates any shape pre-punched hole or standard 1 1/32" field-punched holes.

*Meets requirements of NEC Article 300-4(b) and CEC Rule 12-516.

| Part # | Description | Package | Quantity |
|--------|----------------------|---------|----------|
| SI-25N | Metal Stud Insulator | Bag | 25 |

Features:

Interchangeable design allows you to select a 7/8" (22.2mm) or 1 11/32" (34.1mm) size punch.

- Spring loaded sleeve that increases the life and accuracy of the punch while providing a smoother cutting action.
- Easily punches "H" studs without damaging flanges.
- Automatic stripper.
- High-leverage design permits punching holes in aluminum studs and mild steel (up to 20-gauge) with minimum effort.
- From the center of the punch to the back of the housing measures 2".