

# Global Manufacturing- Yellow Pulling Rope



## Features

Our Global Manufacturing Yellow Pulling Rope is made of polypropylene for longer durability and strength. It is a rugged, lightweight and mildew resistant rope. This low friction rope slides easily through conduit and piping without being snagged. It features a unique braided design which ensures strength and resistance to rot, mildew and stretching. It comes in varied tensile strengths and lengths to meet the needs of any job application.

## Sizing and Features

Product	Size	Product Description	Box Qty.
GYR316250	3/16"	Yellow - 250'	
GYR316600	3/16"	Yellow - 600'	
GYR3161000	3/16"	Yellow - 1000'	
GYR14250	1/4"	Tensile Strength - 1130 - 250'	
GYR14600	1/4"	Tensile Strength - 1130 - 600'	
GYR141200	1/4"	Tensile Strength - 1130 - 1200'	
GYR142400	1/4"	Tensile Strength - 1130 - 2400'	
GYR516600	5/16"	Tensile Strength - 1710 - 600'	
GYR5161200	5/16"	Tensile Strength - 1710 - 1200'	
GYR38250	3/8"	Tensile Strength - 2440 - 250'	
GYR38600	3/8"	Tensile Strength - 2440 - 600'	
GYR381200	3/8"	Tensile Strength - 2440 - 1200'	
GYR382400	3/8"	Tensile Strength - 2440 - 2400'	
GYR12250	1/2"	Tensile Strength - 3780 - 250'	
GYR12600	1/2"	Tensile Strength - 3780 - 600'	
GYR12600W	1/2"	Tensile Strength - 3780 - 600'	
GYR121200	1/2"	Tensile Strength - 3780 - 1200'	
GYR58250	5/8"	Tensile Strength - 5600 - 250'	
GYR58600	5/8"	Tensile Strength - 5600 - 600'	
GYR581200	5/8"	Tensile Strength - 5600 - 1200'	
GYR34250	3/4"	Tensile Strength - 7650 - 250'	
GYR34600	3/4"	Tensile Strength - 7650 - 600'	
GYR341200	3/4"	Tensile Strength - 7650 - 1200'	



- Low-friction polypropylene rope slides easily through conduit
- Non-sliver surface can be handled without gloves
- Will not rot or mildew
- Rugged, lightweight construction

