



VIS-POE4-1FG

4 Port PoE Switch with 1 Up-link Ports. Full Gigabit

Features

- Conforms to IEEE802.3, IEEE 802.3u, IEEE 802.3ab, IEEE802.3af, IEEE802.3at
- Provides 5 10/100/1000Base-TX ports
- Provides 4 PoE injector and 65W Built-in power supply
- Extra 1 SFP Port
- High back-plane bandwidth 12Gbps
- IEEE802.3x Flow control
- EMI standards complies with FCC, CE class B

Power	
Power Supply	Built-in power supply
Voltage Range	AC 100~240 V
Consumption	123.2W for PoE
Ethernet	
Speed	1-8 Port: 10/100/1000Mbps Uplink:10/100/1000Mbps
Transmission Distance	100Meter (328ft)
Network Switch	
Ethernet Standard	IEEE 802.3/802.3u/802.3ab/802.3af/at
Switching Capacity	18G
Transfer Rate	14,880 pps for 10Mbps 148,800 pps for 100Mbps 148,8000 pps for 1000Mbps
MAC Address	4 K MAC address table
LINK/ACT	
On. Green	The port is connecting
Blinks	The port is receiving or transmitting data
Off	The port is not linked successfully with the device
POE	
On. Orange	PD is connected
Off	No PD is connected or power forwarding fails
PoE pin assignment	V- (Rj45 Pin1 ,2),V + (Rj45 Pin3,6)
Working Environment	
Working Temperature	32°F ~104°F (0°C~40°C)
Storage Temperature	-40°F ~158°F (-40°C~70°C)
Humidity(Non-condensing)	0-85%
Mechanical	
Dimension(L*W*H)	11.2 x 7.3 x 1.7 in (285 x 186.5 x 44mm)
Out Shell	Galvanized Sheet
Color	Gray

Ordering Information

VIS-POE4-1FG: 4 Port PoE Switch