


Occupancy Sensor - Low-Voltage Power Pack Item IOS-PP24



PRODUCT DESCRIPTION

An IOS-PP24 power pack is required to provide power to the IOS-CMP-LV sensor and enable a manual ON for the vacancy sensor.

An IOS-PP24 power pack is required to provide power to the IOS-CMP-LV sensor and enable a manual ON for the vacancy sensor.

FEATURES

- ► Controls up to six low-voltage sensors
- ► Zero-crossing technology for long life and performance
- ► Incandescent/Fluorescent/CFL/LED compatible
- ► Controls up to six low-voltage sensors
- ► Zero-crossing technology for long life and performance
- ► Incandescent/Fluorescent/CFL/LED compatible

APPLICATIONS

► For use with Low-Voltage Occupancy Sensors IOS-CMP-LV and IOS-CMP-DT-LV

TECHNICAL DATA

General	
Model Number	IOS-PP24
Description	Low-Voltage Power Pack
UPC Code	078275139930
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty	2-Year limited
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Occupancy Sensor Power Type	Low Voltage
Control Specifications	
Sensor Technology	Zero-crossing
Dimensions	
Product Dimensions (H x W x D) in	2 3/4 x 1 15/16 x 1 5/8 in
Material Specifications	
Color	White
Load Ratings	
Incandescent Load Ratings Ranges	15 A, 120 VAC, 50/60 Hz
Inductive	20 A, 120 VAC, 50 Hz; 20 A, 240 VAC, 50 Hz; 20 A, 277 VAC, 50 Hz; 20 A, 120 VAC, 60 Hz; 20 A, 240 VAC, 60 Hz; 20 A, 277 VAC, 60 Hz
Motor	1 HP, 120-240 VAC, 50 Hz;1 HP, 120-240 VAC, 60 Hz
Inductive Range(s)	20 A, 120/240/277 VAC, 50/60 Hz
Packaging	
Shipping Weight (lbs)	0.35



Unit Carton Dimensions (H x W x L) in 2.5 x 3 x 3.75 in

Environmental Specifications

Temperature (operation) 32 °F to 131 °F / (0 °C to 55 °C)

Standards and Certifications

UL Certification cULus

California Proposition 65 None