



Catalog Number 73370
UPC Number 60198673370
Description LED Cold Weather Wet Location
High Lumen Output
Remote Capable Emergency Light



Features

- Wet Location & Cold Weather Rated LED Emergency Light
- Remote Capable - up to 2 additional 9.6V remote lamp heads (see pg DD14 for compatible LED Remote Lamp Heads)
- Dual 120/277 voltage
- Charge Rate/power "ON" LED Indicator Light and sealed push-to-test switch for mandated code compliance testing
- High Output 9.6V 1900mah maintenance-free, rechargeable Ni-cad Battery
- Internal Solid-State Transfer Switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination
- Fully Automatic Solid-State, Dual-rate Charger initiates battery charging to recharge a discharged battery in 24 hours
- Flame Retardant, UV-stabilized Polycarbonate Gasketed Housing, Integral Breather Vent & External Mounting Brackets
- Sealed and Gasketed Weatherproof High Output Lamp Heads with chrome reflector and tempered glass lens
- Top and side KO's provided for conduit feed applications
- Meets UL924 for Wet Locations, NFPA 101 Life Safety Code, NEC, OSHA

Remote Capability for up to 2 Additional LED Remote Lamp Heads (Use Only LED Remote Heads)

- 2 heads - 3 hours operation (Base Unit)
- 3 heads - 2 hours operation (Base Unit + 1 Head)
- 4 heads - 1.5 hours operation (Base Unit + 2 Heads)

General

Housing: Polycarbonate
Lamps: LED
Mounting: Top and Side KO's

Dimension Information

Length: 8"
Height: 12-3/16"
Depth: 3-5/8"

Specifications

Voltage: 120/277
Input Current: .03A @ 120V; .013A @ 277V
Input Watts: 2.7W
Output Watts: 1.3
Output Lumens: 53 Lumens per Head
Battery: Ni-Cad Battery 9.6V 1900mah
Listing: UL 924, NFPA 101 Life Safety Code, NEC, OSHA
Operating Temperature: -4°F to +122°F
Warranty: 5 Years

Packaging

Box Qty 1
Master Carton Qty 2

