




Catalog Number 73427
UPC Number 60198673427
Description Emergency Light
LED
Black Housing
High Output Remote Capable

Features

- ▶ Long Life Energy Saving LED Lamps
- ▶ Completely Self-Contained
- ▶ Fully Automatic Operation
- ▶ Push to Test Switch
- ▶ Automatic Low Voltage Disconnect (LVD)
- ▶ 120 or 277 VAC Operation
- ▶ Charge Rate/Power On LED Indicator Light
- ▶ Energy Consumption of Less than 4 Watts for Red letters
- ▶ Injection-Molded, UL 94 V-O Flame Retardant, High Impact, Thermoplastic Housing
- ▶ Fully Adjustable Glare-Free LED Lamps
- ▶ Heads Rotate 180°+ for Maximum Field Flexibility
- ▶ Universal Mounting Canopy for Top or Back J-box Installation & 2 Snap-fit Face Plates
- ▶ Field replaceable chevron directional indicators
- ▶ Integral wiring channels to facilitate installation
- ▶ 3.6 Volt 1800 mAh Sealed Ni-Cad Rechargeable Maintenance-Free Battery
- ▶ 90 Minute Minimum Battery run Time
- ▶ Input Current: .22A 120V .10A 277V
- ▶ Input Wattage: 2.5W Remote Capable
- ▶ Environmentally-Coated, Solid State Charger
- ▶ Damp Location Rated
- ▶ UL 924 Listed
- ▶ 5 Year Warranty



Remote Capable - Accommodates up to 2 Additional LED Remote Lamp Heads

2 Heads - 3 Hours of Operation (Base Unit)

3 Heads - 2 Hours of Operation (Base Unit + 1 Remote Head)

4 Heads - 1.5 Hours of Operation (Base Unit + 2 Remote Heads)

Dimension Information

L Inches 9"
H Inches 4-3/4"

Specifications

Input Rating Amps: .22A@120V .10A@277V
Input Rating Watts: 2.5W
Frequency: 60 Hz
Voltage Rating: 120/277
Flammability Rating: UL94V-0

Packaging

Box Qty 1
Master Carton Qty 6

Certifications

UL UL 924
cUL No
RoHS Yes