




**Catalog Number** See Table  
**UPC Number**  
**Description** Dual Rated Aluminum Split Bolt  
 4/0 Thru 500 MCM



- Features**
- Manufactured from High Strength High Conductivity Aluminum Alloy
  - Electro-Tin Plated
  - CU-AL Dual rated for AL/AL, AL/CU, CU/CU Applications
  - Conductor Spacer to accommodate dissimilar conductors

**General**  
 Conductor Size: 4/0 - 500 MCM  
 Material: 6061-T6 Aluminum Alloy  
 Finish: Electro-Tin Plating



**Dimension Information**  
 See Table

**Specifications**  
 Temperature Rating 75° C  
 Voltage Rating 600  
 Flammability Rating N/A  
 Amp Rating To Conductor

**Packaging**  
 Box Qty See Table

**Certifications**  
 UL UL 486B Dual Rated  
 CSA Yes  
 RoHS N/A

Cat No.	AWG	Max Run To Max Tap	Min Run To Min Tap	Max Run To Min Tap	Min Equal Tap & Run	Temp Rating	Torque In-Lb	B	C	H	L	R	V	W	Box Qty
90412	6	4-4	8-14	4-14	8-8	75°C	165	0.492	0.625	0.83	1.06	0.413	0.165	0.722	100
90414	4	4-4	6-14	4-14	8-8	75°C	165	0.709	0.812	1.04	1.24	0.579	0.268	0.938	50
90416	2	2-2	2-14	2-14	6-6	75°C	275	0.748	0.812	1.13	1.44	0.614	0.326	0.938	50
90418	1/0	1/0-1/0	1-14	1/0-14	4-4	75°C	385	0.787	0.937	1.25	1.73	0.708	0.374	1.08	50
90420	2/0	2/0-2/0	2-6	2/0-14	2-2	75°C	385	0.866	1.06	1.3	1.71	0.807	0.421	1.23	25