

Direct Wire-in Photo Controls - "Button" Type

Suitable for wet locations


- Threaded stem, 3/4" in length, with a 3/8"-18 thread.
- Turn on between 1 and 5 foot candles.
- Turn on / turn off ratio: 1:5.
- Single-pole, single-throw switching.
- Built-in time delay prevents any false switching at night due to any momentary flashes of light.
- Contact position at night normally closed.
- With 6" color-coded lead wire.
- Temperature range: -40°F (-40°C) to 149°F (65°C).



Durable, Weatherproof Construction

Durable polycarbonate housing is weatherproof and corrosion resistant. The polycarbonate case and lens are sonically welded in place to seal out moisture.

Ideal for wall packs and post lamps. All units come with locknut, rubber gasket and easy-to-read instructions.



With Anodized Aluminum Wall Plate & Gasket No. 30855

| Catalog No. | Voltage | Tungsten (watts) | Ballast (volt amps) | Carton Quantity | Weight per 100 units |
|-------------|---------|------------------|---------------------|-----------------|----------------------|
| 30850 | 120 | 1800 | 1100 | 10 | 16 lbs. |
| 30853 | 208-277 | 1200 | 1100 | 10 | 20 lbs. |
| 30855 | 120 | 1800 | 1100 | 10 | 30 lbs. |

Basic Wiring Diagram

