NUDTW-88/23345	Туре	
EDUR 120V Edge-Lit Under Cabinet - Selectable CCT & Output	Project Catalog No. Notes	
Source: 7W to 16W 275Im or 475Im per foot		
RODUCT DESCRIPTION EDUR LED Under cabinet luminaires include two switches to change the color temperature and lumen output. Five color emperature options and two lumen outputs creates ten different fixtures in one! Color temperature options range from 700K, 3000K, 3500K, 4000K or 5000K @ 90 CRI. Luminaires produces an 275 lumens or 475 lumens average per foot. LEDL niform reflectance is excellent when used under cabinet over granite, polished stone or any reflective surface, additional s excellent in retail display lighting where diode image might distract from display merchandise.		
EATURES Ten fixtures in one! (5 CCT options and 2 lumen outputs) Five color temperatures in each fixture (2700K, 3000K, 3500K, 4000K or 5000K) Two lumen outputs in each fixture (275lm or 475lm per foot) Edge lit design eliminates LED diode image Available in five different lengths Dark Bronze or White Finish Built-in on/off rocker switch Linkable up to 400 Watts fixtures 3 wire grounded electrical port on both ends for power or linking Quick connect stab-in connectors included Captive Screws for easy mounting Integral dimmable driver	Selectable CCT	
LECTRICAL nput Voltage: 120V umens: 275Im or 475Im per foot (field selectable) Vattage: I" = 7W; 18" = 9W; 22" = 11W; 32" = 16W; 42" = 16W olor Temperature: Selectable CCT: 2700K / 3000K / 3500K / 4000K / 5000K (<u>Note</u> : Preset to 3000K) olor Rendering Index: 90+ CRI	Five position sliding switc 27K / 30K / 35K / 40K / 50 3 position lumen selection rocker switch	
p erating Temp.: 0°C to 45°C ambient temperature l aximum Run Length: 400W l imming: Triac or ELV t <mark>lick Here</mark> or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab.	Captive Screws for easy mounting located a each end under removable cap	
ONSTRUCTION I ousing: Rear wireway access cover with stab-in electrical connectors facilitate wiring without opening the fixture. dditional knock-outs for top and back wiring.		
istallation: Mounting hardware is included with each unit. Captive screws allow for quick installation, simply wire using ear door and quick connects, and hold in place and drive captive screws into material. Captives screws are covered with a included cap for a beautiful finished look.	an Length Length	
icluded with every fixture: Mounting Hardware and ½" die-cast metallic cable clamp, end to end connector, lumen outpu witch and color temperature switch.	NUDTW-8818 18-1/4"	
IBELS AND LISTINGS CULus Listed for Dry Location ENERGY STAR® Certified <u>5-Year Limited Warranty</u> Certified to the high efficacy requirements of California Title 24 JA8-2019	NUDTW-8822 22/4" NUDTW-8832 32/4" NUDTW-8842 42"	

LEDUR 120V Edge-Lit Under Cabinet - Selectable CCT and Output

			•
Series	Length	CCT	Finish
NUDTW-88	11 = 11"	/23345 = 2700K, 3000K, 3500K, 4000K, 5000K	BZ = Bronze
	18 = 18"		WH = White
	22 = 22"		
	32 = 32"		
	42 = 42"		

Example: NUDTW-8822/23345WH = 22" LEDUR 120V Edge-Lit Under Cabinet, Selectable CCT and Output, White Finish



NUDTW-88/23345

LEDUR 120V Edge-Lit Under Cabinet - Selectable CCT & Output Source: 7W to 16W

275lm or 475lm per foot

Type
Project
Catalog No.
Notes

Junction Box

NUA-802B Black NUA-802W White Used to power NUDTW-88 series using Jumper Cables or NUA-804 Hardwire Connector. Finish: Black or White



End to End Connector

NUA-803 Used to join two NUDTW-88 fixtures seamlessly together. 3-wire grounded connector. Finish: White



72" 3-Wire Grounded Hardwire Connector

 NUA-804B
 Black

 NUA-804W
 White

 Used to hardwire NUDTW-88 fixtures to
 NUA-802 or junction box (by others).

 Finish: Black or White
 Finish: Black or White



72" Cord & Plug

NUA-805BBlackNUA-805WWhiteConvert NUDTW-88 series fixtures fromhardwire to direct plug-in units.Finish: Black or White



Jumper Cable

NUA-806B	6" Black				
NUA-806W	6" White				
NUA-812B	12" Black				
NUA-812W	12" White				
NUA-824B	24" Black				
NUA-824W	24" White				
NUA-872B	72" Black				
NUA-872W	72" White				
Used to join NUDTW-88 fixtures					
together or to NUA-802.					
Finish: Black or White					