



PN1A-16X16-2

16 Ch NVR with 16 Plug & Play Ports, 112 Mbps, 2 HD Bays, 4K

Standard Features

- 16 Plug & Play Ports for easy camera setup PoE (Power Over Ethernet) available on all ports
- Up to 8 Megapixel Resolution Recording
- 112 Mbs Bit Rate Input
- Supports up to 16 channel simultaneous playback
- Works with ONVIF or other supported IP cameras
- Local HDMI main monitor output with 4K Support
- Local VGA main monitor output up to 1080p
- True P2P Connectivity with QR Code Connect
- Multiple video search options including Analytic and Thumbnail Search for quick retrieval of footage.
- H.265/H.264 Video Compression
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software to easily manage your system from your Apple computer

| | |
|--------------------------|---|
| System | PN1A-16X16-2 |
| Compression | Standard H.265, H.264 |
| OS | Embedded Linux |
| Video | |
| Network Input | 16 CH IPC Input |
| Network Access Bandwidth | 112Mbps |
| Network Access Format | 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P@25 / 30fps |
| Output | HDMI x 1 : 3840 x 2160 / 1920 x 1080 / 1280 x 1024 / 1024 x 768 VGA x 1 : 1920 x 1080 / 1280 x 1024 / 1024 x 768 |
| Audio | |
| Network Input | 16 CH IPC audio input |
| 2-way Audio | RCA x 1 |
| Local Output | RCA x 1 |
| Record | |
| Record Stream | Dual stream recording |
| Resolution | 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P@25 / 30fps |
| Mode | Manual, timer, motion, sensor |
| Playback | |
| Simultaneous Playback | Max 16 CH |
| Search | Time slice / time / event / tag search |
| Function | Play, pause, FF, FB, digital zoom, etc. |
| Alarm | |
| Mode | Manual, sensor, motion, exception |
| Input | Support IPC alarm input |
| Output | Support IPC alarm output |
| Triggering | Record, snap, preset, e-mail, etc. |
| Network | |
| Interface | RJ45 10 / 100 / 1000 Mbps x 1 |
| PoE Port | RJ45 x 16 |
| Protocol | TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP |
| MobileDevice | |
| Web Client | 10 |
| OS | iOS, Andriod |
| Storage | |
| HDD | SATA x 2, up to 8TB per HDD |
| Backup | |
| Local Backup | USB, USB to HDD |
| Network Backup | Yes |
| Port | |
| USB | USB 2.0 x 2 (one in the front panel and the other in the rear panel) |
| Remote Controller | Included |
| Other | |
| Power Supply | DC48V |
| Consumption | ≤ 15W (without HDD) |
| Dimensions (mm) | 380 x 268 x 52 (W x D x H) |
| Work Environment | -10 50 °C 10% 90% humidity |

Ordering Information

PN1A-16X16-2/2TB: 16 Ch, 16 PnP Ports, 2 TB

Also available with: 4, 8, 10, 16 TB



PN1A-16X16-2/2DS: 16 Ch, 16 PnP, 2 TB, with Data Recovery

Also available with: 4, 8, 16 TB

(For more info on Data Recovery visit www.invidtech.com/data)