



## Pass and Seymour Weather-Resistant Commercial Grade Receptacles, White Part No. WR20TRW

Weather-Resistant Commercial Grade Receptacles, 20 amp, 125 volts, Ivory, WR20TRI



### Features & Benefits

Auto-ground clip assures positive ground.

WR marking on face as required by UL Standard.

Zinc-plated steel mounting screws for greater ease of installation and removal in wet or damp locations.

Strap tabs wrap around face to prevent strap from separating from face and back body.

Tri-drive brass terminal screws. Internal screwpressure plate back and side wire capability. Two back wire holes for more wiring flexibility.

Heavy-duty, brass strap for added strength and ground conductivity.

UV-resistant nylon face for longer life under adverse environmental conditions.

Two drive screws anchor strap to backbody and face where abrupt removal torque is strongest.

Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring.

.032 inch thick brass triple-wipe power contacts for lasting retention.

For covering patents, see [www.legrand.us/patents](http://www.legrand.us/patents).

For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, [click here](#).

### Specifications

#### General Info

Color	White	UPC Number	785007242577
Country Of Origin	Mexico	Product Line	Pass & Seymour
Application Sector	Commercial	Standard	UL498, CSA C22.2 No. 42

#### Listing Agencies / 3rd Party Agencies

cULus Listed	Yes	cULus ListingNumber	140596
--------------	-----	---------------------	--------

#### Technical Information

Number of Poles	Double Pole	Voltage	125 V
Connection	Side wire	Dielectric Strength	Withstands 1500V minimum
Temperature Rating	Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +50°C, minimum -40°C without impact	Wire Size	#14 - #10

---

Number of  
Wires 3

Environmental Conditions

Flammability: UL94 V2

---