

Project: _____ Type: _____ Prepared By: _____ Date: _____



Features and Benefits

Replacement for conventional fluorescent T5HE tubes

Integral Driver enables lamp to be wired directly to line voltage without need for an external driver or ballast

Single ended wiring method

50,000 hour Lifespan

Rated for use in enclosed and open fixtures in dry or damp locations

Diffused frosted lens will maintain the same light quality over time

Instant on full brightness

Environmentally friendly, no mercury used

NSF Listed: NSF/ANSI Standard 2 - Food Equipment - Splash Zone (Not for Direct Food Zone without additional fixture considerations)

UL Classified, DLC Listed

Phase cut dimming

Technical Specifications		
<p>Performance</p> <hr/> <p>Product Type: Linear</p> <p>Input Wattage: 13W</p> <p>Lumens (Nominal): 1750lm</p> <p>Efficacy: 135 lm/W</p> <p>Color Accuracy (CRI): 80</p> <p>L70 Lifespan: 50,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations</p>	<p>Dimming: Phase cut dimming. Dimming capabilities were tested and verified on Lutron DVELV-300P dimming system.</p> <p>LED Characteristics</p> <hr/> <p>Color Temperature: 3500K</p> <p>Construction</p> <hr/> <p>Length Nominal: 4FT</p> <p>Bulb Shape: T5</p> <p>Enclosure Material: Glass</p> <p>Housing Finish: Aluminum</p>	<p>Lens Finish: Frosted</p> <p>Base Type: G5</p> <p>Beam Angle: 180°</p> <p>Electrical</p> <hr/> <p>THD: ≤20%</p> <p>Power Factor: >0.9</p>

Technical Specifications (continued)

Electrical

Operating Temperature:

-20°C-45°C

Input Voltage:

120-277V

Operating Frequency:

50/60Hz

Installation

Installation Method:

UL TYPE B, Ballast Bypass - Single Ended Wire

Other

Equivalency:

F28T5

Technology EQ:

Fluorescent

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Compliance

Safety Listing:

UL Classified, UL Recognized

Environment/Fixture Rating:

Damp / Enclosed

NSF Listing:

NSF/ANSI Standard 2 - Food Equipment (non-contact), Splash Zone, and Non-Food Zone. (Not for Direct Food Zone without additional fixture considerations)

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15 of the FCC Rules

DLC Model Number:

T10169 (T5HE-13-48G-835-SE-BYP)

DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.
DLC Product Code: PL9HIOSPP7G7

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
48.03 x 18.5 x 3.54	0

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	25	48.12	5.28	25
PALLET	0	47.24	0.85	0.85

Dimension

