

## PASS & SEYMOUR®

UL Hospital Grade USB Chargers 15 & 20A, 125V



# Charge ahead with the UL Hospital Grade USB duplex receptacle.

TR8200HUSB, TR8300HUSB

Pass & Seymour® Hospital Grade Tamper-Resistant Duplex Receptacles with USB Charging capabilities are designed with strength and durability in mind. They were designed for the healthcare market, and are capable of withstanding heavy use due to their UL Hospital Grade certification. This product features an improved overall 3.1A USB charging capability, auto-ground clips, zinc-plated ground terminal screw, as well as triple-wipe brass contacts for lasting retention. The screwpressure-plate back wiring makes installation fast and easy.

#### Features & Benefits

## Overall 3.1A USB charging capability

Combination AC duplex receptacles include two 5-volt DC USB ports that work with USB 2.0 & 3.0 compatible devices

AC receptacles available in 15 and 20 Amp, 125V

AC receptacles are tamper-resistant as standard - patented shutter system prevents improper insertion of foreign objects



TR8300HUSBI

Multiple color options available

Back and side wire terminals


accommodate #14 AWG - #10 AWG stranded and solid copper wire.

Stainless steel auto-ground clips assure positive ground

## **3rd Party Compliance**



cULus Listed, UL Fed Spec Listed Complies with test requirements UL 498, UL 1310, Fed Spec WC596, CSA C22.2 No. 42, CSA C22.2 No. 223





## **Technical Information**

Performance		
Electrical		
Dielectric Withstand Voltage	Withstands 1500V minimum	
Maximum Working Voltage	125V	
Current Interrupting	Certified for current interrupting at full-rated current (receptacle only)	
Mechanical		
Terminal Identification	Terminal Identification in accordance with UL 498 (Brass, White, Green)	
Terminal Accommodation	Back and side wire terminals accommodate #14 AWG - #10 AWG stranded and solid copper wire	
Product Identification	Ratings are a permanent part of the device	
Environmental		
Flammability	UL94 V2 (for device cover) 5V (for device body and frame)	
Operating Temperature	Maximum continuous +60°C, minimum -40°C without impact	



TR8300HUSBI

#### Materials

Face	Polycarbonate	
Back Body	Nylon	
Contacts	CDA 260 Brass	
Mounting Strap	.049" Zinc-Plated Steel	
Terminal Screws	Tri-Drive Zinc-Plated Steel with Either Clear or Black Chromate For Color Identification	
Ground Screw	Tri-Drive Steel with Green Chromate	
Mounting Screws	Tri-Drive Steel	
Auto-Ground Clip	Stainless Steel	

## Warranty

1 Year



## **Ordering Information**

## **Duplex Tamper-Resistant Receptacle with USB Charger**

Rating				NEMA
Catalog Number	Α	V	Color	Configuration No.
TR8200HUSB	15A	125V	Brown	5-15R
TR8200HUSBW	15A	125V	White	5-15R
TR8200HUSBLA	15A	125V	Light Almond	5-15R
TR8200HUSBI	15A	125V	Ivory	5-15R
TR8200HUSBBK	15A	125V	Black	5-15R
TR8200HUSBGRY	15A	125V	Gray	5-15R
TR8200HUSBRED	15A	125V	Red	5-15R
TR8300HUSB	20A	125V	Brown	5-20R
TR8300HUSBW	20A	125V	White	5-20R
TR8300HUSBLA	20A	125V	Light Almond	5-20R
TR8300HUSBI	20A	125V	Ivory	5-20R
TR8300HUSBBK	20A	125V	Black	5-20R
TR8300HUSBGRY	20A	125V	Gray	5-20R
TR8300HUSBRED	20A	125V	Red	5-20R





SF20138 — October 2018 — For latest specs visit www.legrand.us





UL Hospital Grade USB Chargers 15 & 20A, 125V

## **Vertical Markets**


Healthcare

Education

Institutional

## Also available in the radiant® collection...

- Hospital Grade Devices
- SPD & Isolated Ground Devices
- Ground Continuity Monitoring (GCM)
- Straight Blade Plugs & Connectors
- Turnlok® Locking Devices
- Weatherproof Boxes & Covers
- IEC 309 Industrial Products
- Flexcor® Wire Mesh Grips
- Bulk Solutions



All brand and product names referenced in this document are registered trademarks or trademarks of their respective holders.



Legrand, North America 60 Woodlawn Street West Hartford, CT 06110 1.877.BY.LEGRAND (295.3472) www.legrand.us 905.738.9195 www.legrand.ca

