

LED Temporary High Bay Fixture

120V/277V: 100 Watt and 150 Watt

Features

- Up to 75% energy savings over HID
- Weighs less than 6 lbs.
- Vibration, shock, and impact resistant
- Corrosion resistant heavy-duty safety cage
- 6 foot power cord; Type SJTW300V
- Includes 20" safety cable
- Ambient operating temperature: -22°F to 140°F
- Self-locking hook/carry handle can be interchanged with included eyebolt ring
- New air convection design allows improved heat dissipation
- M8 screw thread for tripod and eyebolt ring
- Sturdy tripod constructed of PVC and carbon steel with durable black finish, sold separately (17P3TRI)



Applications

Suitable for use in the following areas:

- New building construction or renovation
- Any location where temporary lighting is required



Catalog Number	UPC	Wattage	Lumens	CCT	Operating Voltages	HID Replacement Wattage	Ship Case	Weight/Case
17100LEDP3	03784	100W	12,000	5000K	120V/277V	320 to 400W	4	22
17150LEDP3	03785	150W	18,000	5000K	120V/277V	400 to 600W	4	24

Catalog Number	UPC	Minimum Height	Maximum Height	Maximum Height with Fixture	Width of Open Tripod Base	Ship Case	Weight/Case
17P3TRI	03786	39.37"	78.74"	88.39"	35.43	6	30