

Rigid Straps

One Hole - Malleable Iron

Features

- Inverted rib for strength

Applications


- Indoor or outdoor use
- Use to secure Rigid or IMC conduit to wood, masonry or similar surfaces where greater load bearing is required
- To be used with clamp back

Standard Material

- Malleable iron

Standard Finish

- Zinc plated



Catalog Number	UPC	Size	Hole Size	Unit Carton	Ship Case	Weight/Case	Inches A	B	C
561	15350	1/2"	.31	100	1000	40	2.25	.66	.94
562	15360	3/4"	.31	50	500	25	2.56	.75	1.22
563	15370	1"	.31	25	250	20	3.06	.81	1.50
564	15380	1-1/4"	.43	20	200	20	3.69	.88	1.88
565	15390	1-1/2"	.45	10	100	16	4	1	2.06
566	15400	2"	.55	---	25	9	5.06	1.13	2.56
567	15410	2-1/2"	.57	---	25	17	5.94	1.38	3.06
568	15420	3"	.57	---	25	25	7.44	1.63	3.81
569	15430	3-1/2"	.69	---	10	15	8.19	1.81	4.38
570	15430	4"	.71	---	10	22	8.69	2	5
570A	15441	5"	.96	---	10	35	9.375	2.6875	6
570B	15442	6"	1.18	---	10	45	10.375	3.125	7