

EMT Connectors

Compression Type with Insulated Throat - Steel

Features

- Compression type connectors
- Concrete tight
- Assembled with a steel locknut
- Insulated throat

Applications

- Use to join EMT to box or enclosure

Standard Material


- Steel

Standard Finish

- Zinc plated

Applicable Third Party Standards

- UL Standard: UL 514B
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FB1-2014



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	Inches		
						A	B	C
651Si	16850	1/2"	25	250	30	1.75	1.25	.406
652Si	16860	3/4"	25	250	33	1.813	1.563	.406
653Si	16870	1"	10	100	28	2	1.813	.406
654Si	16880	1-1/4"	---	25	8	2.75	2.188	.50
655Si	16890	1-1/2"	---	20	9	3	2.438	.50
656Si	16900	2"	---	15	12	3.188	2.938	.688
657Si	16901	2-1/2"	---	12	19	3.875	3.688	.75
658Si	16902	3"	---	12	25	4.375	4.313	.938
659Si	16903	3-1/2"	---	6	15	4.50	4.875	.938
660Si	16904	4"	---	6	19	4.75	5.375	.938