

# Rigid Conduit Bodies

## Threaded C Type



### Features

- Threaded C type
- NPT tapered hubs
- Suitable for use in concrete
- Suitable for use in wet locations

### Applications

- Provides access to conductors for pulling, splicing and maintenance

### Standard Material


- Copper free aluminum die cast

### Standard Finish

- Powder coat

### Applicable Third Party Standards

- UL Standard: UL 514A
- Fed. Spec: W-C-586D
- NEMA: FB 1



Catalog Number	UPC	Size	Wire Size		Unit Carton	Ship Case	Weight/Case	Inches		
			Max. Number	Max. Size				A	B	C
<b>C1</b>	19900	<b>1/2"</b>	1	6 AWG	10	100	24	4.72	1.37	1.33
<b>C2</b>	19910	<b>3/4"</b>	2	6 AWG	10	50	21	5.57	1.625	1.54
<b>C3</b>	19920	<b>1"</b>	3	6 AWG	5	25	15	6.46	1.90	1.74
<b>C4</b>	19930	<b>1-1/4"</b>	3	2 AWG	2	10	15	8.528	2.77	2.49
<b>C5</b>	19940	<b>1-1/2"</b>	3	2 AWG	2	10	17	8.528	2.77	2.49
<b>C6</b>	19950	<b>2"</b>	3	2/0 AWG	1	5	13	10.831	3.335	3.10
<b>C7</b>	19960	<b>2-1/2"</b>	3	4/0 AWG	---	1	6	13.50	4.06	4.45
<b>C8</b>	19970	<b>3"</b>	3	250 MCM	---	1	6	13	4.685	4.45
<b>C9</b>	19980	<b>3-1/2"</b>	3	350 MCM	---	1	8	15.937	5.45	5.50
<b>C10</b>	19990	<b>4"</b>	4	350 MCM	---	1	8	15.937	5.45	5.50