

Rigid Conduit Bodies

Threaded LB Type - Hot Dip Galvanized

Features

- Hot dip galvanized finish provides superior protection against severe environmental factors

Applications

- Compatible with all Form 5 & Form 35 series conduit bodies and covers
- Provides taps for branch conduit runs
- Enables 90 degree bends in conduit runs

Standard Material


- Malleable iron

Standard Finish

- Hot dip galvanized



Conforms to finish thickness ASTM
A123/123M
UL 514A and UL 514D
Fed. Spec. A-A-50563
NEMA FB 1



Catalog Number	UPC	Size	Wire Size		Internal Volume (in ³)	Ship Case	Weight/Case	Inches		
			Max. Number	Max. Size				A	B	C
LB1MHDG	86613	1/2"	---	---	4.5	10	7	4.69	2.18	1.36
LB2MHDG	86614	3/4"	3	6 AWG	7.5	10	9	5.42	2.36	1.57
LB3MHDG	86615	1"	3	4 AWG	12.5	5	6	6.28	2.86	1.79
LB4MHDG	86616	1-1/4"	3	2 AWG	32.3	5	12	8.12	3.49	2.52
LB5MHDG	86617	1-1/2"	3	1/0 AWG	35.3	2	11	8.15	3.69	2.52
LB6MHDG	86618	2"	3	4/0 AWG	73	1	6	10.53	4.52	3.15
LB7MHDG	86619	2-1/2"	3	300 MCM	142	1	10	13.76	5.39	4.45
LB8MHDG	86620	3"	3	400 MCM	173	1	13	13.82	6.18	4.45
LB9MHDG	86621	3-1/2"	3	500 MCM	300	1	22	16.65	7.19	5.53
LB10MHDG	86622	4"	3	500 MCM	328	1	24	16.65	7.36	5.53