

# EMT and Rigid Combination Conduit Bodies

## LL Type

### Features

- Combination LL type
- NPT tapered hubs
- Suitable for use in concrete
- NEMA FB 1 rated for wet locations use with threaded rigid metal conduit only

### Applications

- Provides access to conductors for pulling, splicing and maintenance

### Standard Material

- Copper free aluminum die cast
- Steel screws


### Standard Finish

- Powder coat



E195124

UL Standard: 514A  
Fed. Spec. W-C-586D  
NEMA FB 1



Catalog Number	UPC	Size	Max. Number	Max. Size	Unit Carton	Ship Case	Weight/Case	Inches		
								A	B	C
<b>LL1SS</b>	21042	<b>1/2"</b>	1	6 AWG	10	100	28	4.56	1.31	2.06
<b>LL2SS</b>	21052	<b>3/4"</b>	2	6 AWG	10	50	23	5.31	1.62	2.23
<b>LL3SS</b>	21062	<b>1"</b>	3	6 AWG	5	25	18	6.25	1.88	2.50
<b>LL4SS</b>	21072	<b>1-1/4"</b>	3	2 AWG	2	10	14	8.22	2.50	3.40
<b>LL5SS</b>	21082	<b>1-1/2"</b>	3	2 AWG	2	10	16	8.22	2.67	3.48
<b>LL6SS</b>	21092	<b>2"</b>	3	2/0 AWG	---	5	14	10.48	3.29	4.07