

Rigid Conduit Bodies

Threaded LL Type



Features

- Threaded LL type
- NPT tapered hubs
- Suitable for use in concrete
- Suitable for use in wet locations

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material


- Copper free aluminum die cast

Standard Finish

- Powder coat

Applicable Third Party Standards

- UL Standard: UL 514A
- Fed. Spec: W-C-586D
- NEMA: FB 1



Catalog Number	UPC	Size	Wire Size		Unit Carton	Ship Case	Weight/Case	Inches		
			Max. Number	Max. Size				A	B	C
LL1	21040	1/2"	1	6 AWG	10	100	28	4.295	1.37	2.03
LL2	21050	3/4"	2	6 AWG	10	50	23	5.09	1.625	2.33
LL3	21060	1"	3	6 AWG	5	25	18	5.915	1.90	2.65
LL4	21070	1-1/4"	3	2 AWG	2	10	14	7.894	2.77	3.385
LL5	21080	1-1/2"	3	2 AWG	2	10	16	7.894	2.77	3.385
LL6	21090	2"	3	2/0 AWG	1	5	14	10.134	3.335	3.81
LL7	21100	2-1/2"	3	4/0 AWG	---	1	6	13	4.063	5.709
LL8	21110	3"	3	250 MCM	---	1	6	12.75	4.682	5.506
LL9	21120	3-1/2"	3	350 MCM	---	1	8	15.50	5.452	6.171
LL10	21130	4"	4	350 MCM	---	1	8	15.50	5.452	6.171