

# Knockout Bushings

## 6/6 Nylon

### Features

- Suitable for use with electrical knockouts

### Application

- For use in mounting panels up to 1/4" thick, convert raw edged holes to smooth, neat, insulated holes
- Insulate and mechanically protect electrical and telecommunications cables, tubing, hose, rope and utility lines
- Locking fingers snap into holes with fingertip pressure; capable of withstanding a push back force of greater than 35 pounds



### Standard Material

- 6/6 nylon

Catalog Number	UPC	Inside Diameter	KO Size	Unit Carton	Ship Case	Weight/Case
<b>SB8756</b>	32620	<b>3/8"</b>	1/2"	100	1000	4
<b>SB8757</b>	32630	<b>7/16"</b>	1/2"	100	1000	4
<b>SB8758</b>	32640	<b>1/2"</b>	1/2"	100	1000	4
<b>SB8759</b>	32650	<b>9/16"</b>	1/2"	100	1000	4
<b>SB87510</b>	32660	<b>5/8"</b>	1/2"	100	1000	4
<b>SB87511</b>	32670	<b>11/16"</b>	1/2"	100	1000	4
<b>SB109313</b>	32690	<b>13/16"</b>	3/4"	100	1000	6
<b>SB109314</b>	32700	<b>7/8"</b>	3/4"	100	1000	6
<b>SB109315</b>	32710	<b>15/16"</b>	3/4"	100	1000	6
<b>SB137514</b>	32760	<b>7/8"</b>	1"	100	1000	8
<b>SB137516</b>	32770	<b>1"</b>	1"	100	1000	8
<b>SB175022</b>	32810	<b>1-3/8"</b>	1-1/4"	50	500	6
<b>SB200026</b>	32820	<b>1-5/8"</b>	1-1/2"	50	500	7
<b>SB2.531</b>	32840	<b>1-31/32"</b>	2"	10	100	4
<b>SB3.039</b>	32850	<b>2-15/32"</b>	2-1/2"	10	100	4
<b>SB3.547</b>	32860	<b>2-15/16"</b>	3"	10	100	4
<b>SB4.055</b>	32870	<b>3-7/16"</b>	3-1/2"	10	100	4