

Color: Bronze

Weight: 9.4 lbs

<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

Driver Info		LED Info	
Type	Constant Current	Watts	60/50/40W
120V	0.50A/0.42A/0.33A	Color Temp	3000/4000/5000K
208V	0.29A/0.24A/0.19A	Color Accuracy	81-83 CRI
240V	0.25A/0.20A/0.17A	L70 Lifespan	100,000 Hours
277V	0.22A/0.18A/0.14A	Lumens	5,736-8,806 lm
Input Watts	38.8-59.9W	Efficacy	135.4-157.2 lm/W

## Technical Specifications

### Field Adjustability

#### Field Adjustable:

Field Adjustable Light Output:  
60W/50W/40W (factory default: 60W)  
Color Temperature Selectable:  
3000K, 4000K and 5000K (factory default:4000K)  
Photocell Selectable:  
Built-in on/off photocell (factory default: off)

### Compliance

#### UL Listed:

Suitable for wet locations

#### IESNA LM-79 & LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

#### IP Rating:

Ingress protection rating of IP65 for dust and water

#### DLC Listed:

This product is listed by Design Lights Consortium (DLC) as an ultra-efficient premium product that qualifies for the highest tier of rebates from DLC Member Utilities.

DLC Product Code: S-KHC8R2 (Stairwell and Passageway Luminaires)

DLC Product Code: S-HMZ62Z (Parking Garage Luminaires)

### Electrical

#### Drivers:

Constant Current, Class 2, 120-277V, 50/60 Hz:  
60W: 120V: 0.50A, 208V: 0.29A, 240V: 0.25A, 277V: 0.22A  
50W: 120V: 0.42A, 208V: 0.24A, 240V: 0.20A, 277V: 0.18A  
40W: 120V: 0.33A, 208V: 0.19A, 240V: 0.17A, 277V: 0.14A

#### Dimming Driver:

Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

#### THD:

3.79% at 120V, 4.1% at 277V

#### Power Factor:

99.9% at 120V, 97.4% at 277V

#### Surge Protection:

L-N: 4kV  
L/N-PE: 6kV

#### Photocell:

Built-in photocell included with on/off switch

#### Battery Backup:

Battery backup will operate the fixture for 90 minutes if power fails. Wired for 120-277V.

### Battery Backup Light Loss Factor:

60W: 16.15%  
50W: 18.96%  
40W: 22.85%

### LED Characteristics

#### LEDs:

Long-life, high-efficacy, surface-mount LEDs

#### Color Uniformity:

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

### Performance

#### Lifespan:

100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

#### Performance Data:

[Click here for the VAN17-60 performance data](#)

### Construction

#### Cold Weather Starting:

The minimum starting temperature is 0°C (32°F)

## Technical Specifications (continued)

**Maximum Ambient Temperature:**

Suitable for use in up to 40°C (104°F)

**Housing:**

Precision die-cast aluminum housing and door frame

**Lens:**

Vandal-resistant polycarbonate textured opaque for low-glare lens

**Reflector:**

Plastic

**Finish:**

Formulated for high durability and long-lasting color

**Green Technology:**

Mercury and UV free. RoHS-compliant components.

**Installation**

---

**Mounting:**

Retrofit mounting plates for ceiling mounting

**Optical**

---

**BUG Rating:**

60W: B3 U0 G2

50W: B3 U0 G2

40W: B2 U0 G2

**Other**

---



**5 Yr Limited Warranty:**

The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

**Buy American Act Compliance:**

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

**Dimensions**



**Features**

- 50,000-Hour LED lifespan
- 0-10V Dimming
- IP65 Rated
- 5-Year, limited warranty

**Ordering Matrix**

Family	Wattage (Size)	Color Temp	Finish	Driver	Options
VAN17	-	60			/E
	30 = 30/25/20W (8" x 8") 90 = 90/80/70W (10" x 10") 60 = 60/50/40W (10" x 10") 50 = 50/40/30W (8" x 8")	Blank = 3000/4000/5000K CCT Adjustable	Blank = Bronze W = White	Blank = 120-277V, 0-10V Dimming, On/Off Photocell	Blank = Standard /E = Battery Backup