



## Technical Specifications (continued)

### Construction

#### Material:

Plastic

#### Trim Style:

Smooth Trim

#### Shape:

Round

### Mounting:

Recessed ceiling

### Operating Temperature Range:

-20°C - 40°C (-4°F - 104°F)

### Other


#### Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

### Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

## Dimensions



## Features

Shallow baffle trim provides extremely thin depth for shallow ceiling installation

Flexible 360° rotation and 25° tilt for any direction illumination

5 color temperatures in 1 SKU (2700K, 3000K, 3500K, 4000K, 5000K)

No recessed housing or J-box required

IC and airtight rated

## Ordering Matrix

Family	Size	Shape	Wattage	CRI/Color Temp	Voltage	Finish	Trim
WFRLA	4	R	8	9FA	120	W	S
	4 = 4" 6 = 6"	R = Round	8 = 8W 12 = 12W	9FA = 90 CRI, Field Adjustable	120 = 120V	W = White	S = Smooth