Description

The E7RICAT is a compact and efficient recessed housing optimized and listed for EISA compliant tungsten-halogen, CFL and LED lamps as well as incandescent. Housing is suitable for residential or light commercial applications. For installation in insulated ceilings* and non-insulated ceilings with airtight code compliant construction. Use with a variety of trims and finishes to create different lighting effects or to match any decor. May be retrofit with compatible HALO LED lighting systems.

Hinged junction box w/

(4) ½" conduit pry-outs

14-2, 14-3, 12-2 Canadian

Quick Connect[™] Wiring Tray

· Aids in speed & reliability

Compact 10 in³ box volume

conductors in box

whole circumference

Air-Tite[™] code compliant

Certified under ASTM E283

No additional caulk required

against the ceiling

frame & ceiling

brass screw shell

Thermal Protector

Socket

.

Remodel Flange

Hinged door for easy access

• (3) Color coded push wire nuts

in captive tray for one-handed

Clear caps for wire connection

Listed for maximum (6) No. 12 AWG

or (8) No. 14 AWG 90° C splice

· Die formed flange maintains precise

Integral flange secures fixture

· Exclusive gasket seals aperture,

Porcelain socket with nickel plated

Snap-in springs secure socket to

Self resetting thermal protector

deactivates fixture if overheating occurs due to improper lamping

socket plate, and may be detached

when using socket supporting trims

Slide-N-Side™

connection

visibility

cULus Listed

Specification Features

Housing

- Single wall die-formed aluminum housing
- Housing features a precision rolled interlocking collar which maintains aperture geometry for greater assurance of installation results
- Integral Air-Tite gasket for coderequired gasket between fixture and finished ceiling - seals aperture without need for additional caulk
- Shipped with socket overspray protector installed
- For installation from below the finished ceiling. Integral flange secures fixture against ceiling

Remodel Retention System -Speed Clamps

- Exclusive two integral speed clamps securely lock housing to ceiling, accommodating 3/8" to 2" ceiling
- materials Use screwdriver or power driver to set clamps

Socket Plate

- Rigid socket plate adjusts and locks without tools for various lamp sizes.
- Socket plate and bracket may be removed when using socket supporting trims

Includes:


Remodel Speed Clamps

- (2) Exclusive integral speed clamps • Speed clamp tabs securely lock to
- ceilina Speed clamps can be loosened for easy repositioning
- Speed clamps feature internal drive screws - a power screwdriver speeds installation
- Two-tier tabs adjust for 3/8" to 2" of various ceiling materials


Attached-Arm Design

- Attached arm gets into tight spaces Ease of installing through the ceiling
- aperture
- Smaller footprint for packing and distributor shelf space

Dimensions



COOPER



Trims

multiple trim options in a variety of design styles, and functional beam distributions to control beam angle and lumen delivery in accommodating various lamp types including Halogen, CFL and LEDD

Catalog #

Comments

Prepared by

Project

- insulation and combustible material*
- Air-Tite code compliant. Certified under ASTM E283; not exceeding 2.0 cfm (0.944 L/s) air leakage rate tested at a 1.57 psf (75 Pa) pressure differential
- RoHS compliant

*Not to be used in direct contact with spray foam insulation (Consult NEMA ISD57-2013)





E7RICAT

6" IC, Air-Tite, **Remodel Housing**

E26 Screw base housing

FOR USE IN INSULATED CEILINGS

FOR DIRECT CONTACT WITH INSULATION*

Special Features

Hinged J-Box with Slide-N-Side™ Quick Connect™ push wire nuts Air-Tite[™] code compliant Speed Clamps

TD518052EN 2/24/2016



Compliance

- cULus Listed 1598 Luminaire
- cULus Listed Damp Location
- cULus Listed for Wet Location, covered ceiling, with select trims
- cULus Listed for direct contact with

Type

HALO®

Date

Ordering Information

Sample Number: E7RICAT 6110WB Order housing, trim and lamp (by others) separately for a complete luminaire.

Housing E7RICAT = 6" insulated ceiling, airtight recessed housing, remodel, 120V Trims Reflectors 312 Coilex[®] Baffle OD: 7-1/4" [184mm] 78 BR/PAR30 Eyeball 30° Tilt, Self-flange OD: 8" [203mm] 30 Reflector, Self-flange 312W=White Coilex Baffle and Trim 78P=White Eyeball and Trim OD: 7-1/4" [184mm] 30HAT=Haze Reflector, White Trim 78PAT=White Eyeball and Trim, Air-Tite 78SN=Satin Nickel Eyeball and Trim 312P=Black Coilex Baffle, White Trim 30RGAT=Residential Gold Reflector, White Trim 78TBZ=Tuscan Bronze Eyeball and Trim 353 Metal Baffle 30CAT=Clear Specular Reflector, White Trim OD: 7-1/4" [184mm] 353SN=Satin Nickel Baffle and Trim 376 PAR30 Regressed Gimbal 30° Tilt, 30SBAT Reflector, Self-flange 353TBZ=Tuscan Bronze Baffle and Trim Self-flange OD: 7-1/4" [184mm] OD: 7-1/4" [184mm] **30SBAT**=Black Specular Reflector, Self-flange **376W**=White Baffle and Trim 6100 Tapered Metal Baffle with (2) Trim Rings 0D: 7-1/8" [181mm] 376P=Black Baffle and White Trim 426 Reflector Cone 6100WB=White Baffle, Narrow and Wide White OD: 7-1/4" [184mm] Trims (included) 420 BR/PAR30 Regressed Eyeball 30° Tilt, 426=Clear Specular Reflector Cone, White Trim 6100BB=Black Baffle, Narrow and Wide White Self-flange OD: 7-1/4" [184mm] 426MB=Black Specular Reflector Cone, White Trims (included) Trim 420W=White Eyeball, Baffle and Trim 426H=Haze Reflector Cone, White Trim 6101 Straight Metal Baffle with (2) Trim Rings 420P=White Eyeball, Black Baffle, White Trim 426SN=Satin Nickel Reflector Cone and Trim OD: 7-1/8" [181mm] 426TBZ=Tuscan Bronze Reflector Cone and Trim 6101WB=White Baffle, Narrow and Wide White 478 PAR38 Adjustable Regressed Gimbal with Splay 25° Tilt, Self-flange OD: 7-1/4″ [184mm] Trims (included) 429 Dayform White Cone 6101BB=Black Baffle, Narrow and Wide White OD: 7-1/4" [184mm] 429P=White Reflector and Trim 478P=White Splay and Trim Trims (included) 6102 Tapered Metal Baffle, Self-flange 6130 BR/PAR30 Eyeball 35° Tilt, Self-flange 4261 White Reflector Cone, Self-flange OD: 7-3/4" [197mm] OD: 7-3/4" [197mm] OD: 7-1/4" [184mm] 4261P=White Reflector and Trim 6102WB=White Baffle and Trim 6130WH=White Eyeball and Trim 6102BB=Black Baffle, White Trim 6170 PAR38 Gimbal 25° Tilt, Self-flange OD: 7-3/4" [197mm] 6106 Straight Reflector Cone, Self-flange OD: 7-3/4" [197mm] 6103 Straight Metal Baffle, Self-flange OD: 7-3/4" [197mm] 6103WB=White Baffle and Trim 6170WH=White Gimbal and Trim 6106SC=Specular Reflector, White Trim 6170BK=Black Gimbal and Trim 6103BB=Black Baffle, White Trim 6170SN=Satin Nickel Gimbal and Trim 6107 Tapered Reflector, Self-flange 6170TBZ=Tuscan Bronze Gimbal and Trim OD: 7-3/4″ [197mm] 6107SC=Specular Reflector, White Trim 6108 Coilex[®] Straight Plastic Baffle, Self-flange OD: 7-3/4″ [197mm] 6108WB=White Plastic Straight Coilex Baffle, 6215 PAR30 Double Gimbal 35°-50° Tilt, <u>Self-flange</u> OD: 7-3/4" [197mm] 6120 Full Cone Reflector, Self-flange OD: 7-3/4" [197mm] White Trim 6108BB=Black Plastic Straight Coilex Baffle, 6215WH=White Gimbal and Trim 6120WH=White Reflector and Trim White Trim 6215BK=Black Gimbal and Trim 6120SN=Satin Nickel Reflector and Trim 6108BKBB=Black Plastic Straight Coilex Baffle, 6215SN=Satin Nickel Gimbal and Trim 6120TBZ=Tuscan Bronze Reflector and Trim 6215TBZ=Tuscan Bronze Gimbal and Trim Black Trim 6121 Shallow Full Cone Reflector, Self-flange 6109 Coilex[®] Tapered Baffle, Self-flange OD: 7-3/4" [197mm] 6222 Regressed PAR30 Adjustable 45° Tilt, OD: 7-3/4" [197mm] Self-flange 6121WH=White Reflector and Trim 6109WB=White Tapered Coilex Baffle, OD: 7-3/4" [197mm] White Trim 6222WB=White Baffle and Trim **Baffles** 62228B=Black Baffle and Trim 6222SC=Specular Clear Reflector, White Trim $\textbf{6109BB}{=} \textsf{Black Tapered Coilex Baffle,}$ White Trim 30 Baffle, Self-flange OD: 7-1/4" [184mm] 6109BKBB=Black Tapered Coilex Baffle, 6222H=Haze Reflector, White Trim Black Trim 30WAT=White Baffle, Reflector and Trim Lenses & Wet Location Showerlights 30WATH=White Baffle, Clear Reflector and 6110 Perftex Baffle, Self-flange OD: 7-3/4" [197mm] 6110WB=White Perftex Baffle and Trim White Trim 170 Albalite Lens with Reflector 30PAT=Black Baffle, Clear Reflector and OD: 8" [203mm] White Trim 170P=Frosted Albalite Glass Lens, White Trim 6110BB=Black Perftex Baffle, White Trim 30SNAT=Satin Nickel Baffle, Reflector and Trim 170PS=Frosted Albalite Glass Lens, White 6110BKBB=Black Perftex Baffle and Trim 30TBZAT=Tuscan Bronze Baffle, Reflector and Plastic Trim, Showerlight, Air-Tite Trim 6125 Full Cone Baffle, Self-flange 171 Drop Opal Lens with Reflector OD: 7-3/4" [197mm] 6125WB=White Baffle and Trim 310 Coilex[®] Baffle OD: 7-1/4" [184mm] OD: 8" [203mm] 171P=Drop Opal Glass Lens, White Trim 6125BB=Black Baffle, White Trim 310W=White Coilex Baffle and Trim 171PS=Drop Opal Glass Lens, White Plastic 6125BKBB=Black Baffle and Trim 310P=Black Coilex Baffle, White Trim Trim, Showerlight, Air-Tite 310SN=Black Coilex Baffle, Satin Nickel Trim 6126 Shallow Full Cone Baffle, Self-flange 310TBZ=Black Coilex Baffle, Tuscan Bronze Trim 172 Dome Lens with Reflector OD: 7-3/4" [197mm] OD: 7-3/4" [197mm] 6126WB=White Baffle and Trim 172PS=Frosted Glass Dome, White Plastic Trim 6126BB=Black Baffle, White Trim 172SNS=Frosted Glass Dome, Satin Nickel Plastic Trim Adjustable - Eyeballs & Gimbals 172TBZS=Frosted Glass Dome, Tuscan Bronze 74 PAR30 Eyeball 30° Tilt, Self-flange Plastic Trim OD: 8" [203mm] 74P=White Eyeball and Trim continued 76 PAR38 Gimbal 30° Tilt, Self-flange OD: 8" [203mm]


76P=White Gimbal and Trim

*Outdoor rated lamp only (purchase separately)



Ordering Information

Sample Number: E7RICAT 6110 Order housing, trim and lamp (by others) separately for a complete luminaire.



*Outdoor rated lamp only (purchase separately)



Cooper Lighting Solutions 1121 Highway 74 South Peachtree City, GA 30269 P: 770-486-4800 www.cooperlighting.com

LISTED For use in Halo listed housings. Select trims are classified for use in others housings. See www.cooperlighting.com.